

c]67

No. F6/DFS/MS/DMRC/NDZ/2025/ 47

Dated: 27/01/2025

FIRE SAFETY CERTIFICATE

Issued on 97 01 2025 at New Delhi by.

DIRECTOR

DIRECTOR

COLUMN SERVICE

Copy to:-

- Delhi Metro Rail Corporation Limited, located at Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi - 110001.
- 2. The Director, Rcube Projects Private Limited located at 2nd floor, Plot No. 3, Local Shopping Center, Sector B, Pocket, Vasant Kunj, New Delhi 110070.

Conditions for the validity of Fire Safety Certificate

- 1. This certificate is valid for P.D Area situated on ground floor, First floor, Second floor & Third floor only.
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

M/20

+		- 4	INSPECTION RE	PORT					
1	Name	& address of the buildi	- ut	PD area at New Ashok Nagar, Delhi Metro Rail Corporation Ltd. Delhi					
2	Buildir	g is comprised of	Ground plus Ground floor	Ground plus three upper floors Ground floor (Shops/Restaurants), first floor (bank/Vacant), 2 nd floor (Domion Office/Vacant), 3 rd					
3	Type o	f occupancy	Assembly Bu		AS WILM				
4	Type o		Renewal						
5		of previous FSC	2.227(0)(0)(4)						
6	E112 - 117/1-117	fety direction letter no	F6/MS/DFG/I	F6/DFS/MS/DMRC/NDZ/2022/94 Dated 04.03.2022					
7				F6/MS/DFS/BP/2009/3096 Dated 27.10.2009					
(2)		f inspection	The Table of the Control of the Cont	20.01.2025					
8		of the inspecting office	Yashwant Sir	Ashok Kumar Jaiswal, Divisional Officer / East & Yashwant Singh Meena, A.D.O / Laxmi Nagar					
9		of the designation of on the building side	officer Mr. Avnish K	Mr. Avnish Kumar (Fire Officer) &					
10		of construction	2009	Mr. Promod Kumar (Manager)					
11	CHILDRED E	cant's letter no							
S.N	M	inimum Standards on revention and fire saf requirements U/R 33	fire Directives fety Requiremen		025 Remarks MR/NMR				
1	Acc	ess to building							
	a	Road width	09 mtrs.	12 mtrs.	MD				
	b	Gate width	NA NA	NA NA	MR NA				
	c	Width of internal roa		NA NA	NA NA				
2	Nu	Number, Width, Type and Arrangement of Exits							
	A	Number of staircase	es						
		a Upper floor	02 nos.	02 nos.	MR				
	1 2	b Basement	NA	NA NA	NA				
	В	Width of staircases			1 1121				
		a Upper floor	02 mtrs.	2.4 m, 3.2 m & 1.2 m	n MR				
	- 17	b Basement	NA	NA	NA				
	C	Protection of exits							
	- 1	a Fire check door	Required	Provided	MR				
		b Pressurization	NA	NA	NA				
	D	No. of cont	inuous 01 nos.	02 nos.	MR				
	E	staircases to terrace	277						
	F	Width of corridor Door size	NA	NA	NA				
3		mpartmentation	2.0 mtrs.	2.0 mtrs.	MR				
-	a	Fire check door	D 1	D :111	1 100				
	b	Sealing of electrical sl	Required NA	Provided NA	MR NA				
	c	Fire rating of shaft do		NA NA	NA NA				
	d	Water curtain	NA NA	NA NA	NA NA				
	е	Fire dampers	NA NA	NA NA	NA NA				
4		noke Management Sys	tem.	234.1	****				
	a Basement		approximation — III————————————————————————————————	90	(31,000)				
	a	Basement	NA	NA	NA				



MM

a	_		nguisher numbers	12 nos.	15 nos.	MR
t	+	_		CO ₂ & ABC	CO ₂ & ABC	MR
-		ypes		ISI marked	ISI marked	MR
_			arking	151 Illaikeu	IOI III	
			-Hose Reels.	04 ===	04 nos.	MR
-			numbers of each floor	04 nos. 30 m	30 m	MR
			th of hose reel hose	05 mm	05 mm	MR
-	cl	Nozz	le diameter			
TC -	Automatic fire detection and alarmin			ing system.	Heat & Smoke Provided	
	a Type of detectors			Security Room	Provided	MR
	b	Loc	ation of main panel	NA	NA	NA
	С	Loc	ation of repeater panel	Required	Provided	MR
	d		ernate source of power	Required	Provided	MR
	e		oters	Required	Provided	MR
8)EF		Required	Provided	MR
9	Pu	blic a	address System.	<u> </u>		20.24
10	Au		atic Sprinkler System.	NA NA	NA	NA
	a	(ement	Required	Provided	MR
	b	Upp	er floors	NA	NA	NA
	c		nkler above false ceiling	14.	Internal Pur	mpjiri
11	Internal Hydrants			100 mm	100 mm	MR
	a	a Size of riser		04 nos.	04 nos.	MR
	b	Nur	nber of hydrants per floor	04 nos.	04 nos.	MR
	С	c Hose Box				
12	Yard Hydrants.			NA	04 nos.	MR
STATES.	a	Tota	al number of hydrants	NA NA	04 nos.	MR
	b	Hose Box				
13	Pumping Arrangements.					
	A		Ground Level	1800 LPM	2850 LPM	MR
		a	Discharge of main Pump	70 m	70 m	MR
		b	Head of Main Pump	01 no.	01 no.	MR
į.	H.	c	Number of main pumps	180 LPM	180 LPM	MR
		d	Jockey pump out put	70 m	70 m	MF
		e	lockey pump head	1800 LPM	2850 LPM	MI
	1	f	Standby pump out put	70 m	70 m	MI
		g	Standby pump head	Required	Provided	IVII
		h	Auto starting /manual		D sided	M
			stopping	Required	Provided	
	i Pump House Access		Pump House Access		NIA	N.
	В	T	errace Level	NA	NA NA	N
		a	Discharge of pump	NA	NA NA	N
		b	Head of the Pump	NA	NA NA	N
		C	Power supply Auto Starting of pump	NA	NA	

14	Ca	Captive Water Storage for Fire Fighting.						
	a	Underground tank capacity	1, 00,000 Liters.	1, 20,000 Liters	MR			
	b	Draw-off connection	Required	Provided	MR			
2.0	c	Fire service inlet	Required	Provided	MR			
	d Access to tank		Required	Provided	MR			
	e Overhead Tank capacity		NA	NA	NA			
15	Exit Signage.		Required	Provided	MR			
16	Provision of Lifts.							
711	a	Pressurization of Lift Shaft	NA	NA	NA			
1	b	Pressurization of Lift lobby	NA	NA	NA			
	С	Communication in lift car	Required	Provided	MR			
	d	Firemen's grounding switch	Required	Provided	MR			
	e	Lift Signage	Required	Provided	MR			
17	St	andby power supply	Required	Provided	MR			
18	Refuge Area.							
	a	Total area	- NA	NA	NA			
,	b	Location	NA	NA	NA			
19	Fire Control Room							
	a	Detector system panel	Required	Provided	MR			
	b	Flow switch panel	NA	NA	NA			
	c	PA system panel	NA	NA	NA			
	d		NA	NA	NA			
	e	The same of the sa	Required	Provided	MR			
20	Special Fire Protection systems for protection of special Risks, if any:		:	NA	NA			

NOTE: - Fire pumps including jockey pump are provided independently for P.D Area & DMRC station in common pump house. There 2 underground water static tank of capacity 1,00000 liters for DMRC & 1,20,000 liters for P.D Area.

The fire protection system was randomly checked and tested and was found

functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under Rules the FSC issued vide letter No. F6/DFS/MS/DMRC/NDZ/2022/94 Dated 04.03.2022, renewal under Rules 35 is recommended.

Signature of the Inspecting Officer

Name : Yaswant Singh Meena

Designation: ADO /Laxmi Nagar

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal

Designation: Divisional Office/ East

Dy cfg(NDZ) - ON Leave

24/01/2025

OT.