

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F6/DFS/MS/2025/SZ/ 320

FIRE SAFETY CERTIFICATE

Dated: 12/06/2025

Certified that the M/s PD Area at Tughlakabad Metro Station, New Delhi, comprised of ground, concourse, platform, 3rd floor, 4th floor & 5th floor, but PD Area is running at Ground, 1st and 3rd floor only has already been issued FSC by this department vide letter No. F.6/DFS/MS/DMRC/SZ/2022/89 dated 28.02.2022 for ground floor. The premises was re-inspected by the officer concerned of this department on 02.06.2025 in the presence of Mr. Manish Gandhi (GM operation) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class 'Mixed occupancy (Mercantile + Assembly) for PD Area ground, 1st and 3rd floor only with effect from 12 06 2025 for a period of 03 (Three) years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 12 06 2025 at New Delhi by

Chief Fire Officer

De

Chy

Copy to:-

1. Ref No.DMRC/Fire/182/2025/05/413 dated 08.05.2025.

2. M/s PD Area at Tughlakabad Metro Station, New Delhi.

Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management/occupier.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized construction.

- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency. http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/

http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

			INSPE	CTION REPORT				
-	Name & 2	ddress of the building	M/s P	D Area at Tughlaka	bad Metro Station, New D	elhi-		
		ccupancy	Merca	ntile Building				
2.	Comprise	of building	Groun	nd Concourse, platform, 3 rd floor, 4 th floor & 5 th floor				
-	T-ma of C	ase	New C	Case for PD Area Ground, 1st and 3rd floor				
-	D-taile of	Previous INOC	F.6/DF	S/MS/DMRC/SZ/2022/89 dated 28.02.2022 for metro station				
<u>).</u>	Fire Safet	directives letter No		FS/MS/BP/2022/470 dated 23.11.2022.				
_	Data of in	enection	02.06.	.2025 jay Kumar Sharma (ADO Rohini)				
0	Name of	ADO Romm)						
<u>0.</u> 9.	Name and	designation of officers	Mr. M	r. Manish Gandhi (GM Operation) 08 & 2009				
	From the l	uilding side	2008 &					
10.	0. Year of Construction			Ref No DMRC/Fire/182/2025/05/413 dated 08.05.2025				
11.	. Applicant	s letter No. Standards on fire prev		NBC	Provided at site	Kemaiks		
	Minimun	Standards on the pre-	CII (10 - 10 - 10 - 10 - 10 - 10 - 10 - 10	Requirement		MR/NMR		
0	and fire safety, U/R 33			•				
4	Access to building			09m	18m	MR		
		ad width		4.5m	Directly accessible from	MR		
	• Ga	te width		4.5111	road	37.4		
				-NA-	-NA-	-NA-		
	Width of internal road Number, Width, Type & Arrangement of			Exits				
	Number,	Width, Type & Arrange				. m		
	100	r of staircases Upper Floors		Required	GF to CC level (1st floor)- 03 nos. GF to 3rd floor-	MR		
	2.1	Opper Freeze		-NA-	04nos. -NA-	-NA-		
	•	Basements		-IVA-				
	b. Width	of staircases			GF to CC level (1st floor)-			
		Upper Floor		Required	1.5m (1nos.) & 2.4m (02nos.) GF to 3 rd floor-2.0m each	MR		
	1000			-NA-	-NA-	-NA-		
		Basements						
	c. Protec	tion of exits		Required	Provided	MR		
	•	Fire check door		-NA-	-NA-	-NA-		
Į,	•	Pressurization			-NA-	-NA-		
		ontinuous staircases to t	errace	-NA-	Provided	MR		
		of Corridor		2m	Provided	MR		
	f. Door S			1.5m	Provided	1,114		
	Comparti	nentation				MR		
	a) Fire check door			Required	Provided			
	b) Sea	ling of electrical shafts		Required	Provided	MR		
	c) Fire Rating of shaft door			-NA-	-NA-	-NA-		
		ter Curtain		-NA-	-NA-	-NA-		
	e) Fire Dampers		-NA-	-NA-	-NA-			
87	Smoke Management System							
	a) Basements			-NA-	-NA-	-NA-		
		per floors		12 a/c per hour	Provided	MR		
	Fire Extin	Carlo delle letteri.	1					
	a) Total numbers			40nos.	Provided	MR		
	b) Typ			ABC/CO2	ABC/CO2	MR		
				93 SATE AS STORES -		MR		
		narking		ABC/CO2 ISI marked	Yes			



	First-Aid Hose Reels					
	a) Total numbers on each floor	04nos.	Provided	MR		
	b) Length of hose reel hose	30mm	Provided	MR		
	c) Nozzle diameter	5m	Provided	MR		
7.	Automatic fire detection and alarming system					
	a) Type of detectors	Required	Smoke type	MR		
	b) Location of Main Panel	Required	Stn. Control room	MR		
	c) Location of Repeater Panel	Required	Stn. Control room	MR		
	d) Alternate source of power	Required	Provided DG set	MR		
	e) Hooters' Location	Required	Provided to all levels	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	required	-			
	a) Basement	-NA-	-NA-	-NA-		
	b) Ground & Upper Floors	Required	Provided	MR		
	c) Sprinkler above false ceiling	-NA-	-NA-	-NA-		
11.	Internal Hydrants	144	* 14 *			
~ (2017)	a) Size of riser/down-comer	1500mm	Provided	MR		
	b) Number of hydrants per floor	04nos.	Provided	MR		
	c) Hose Box	04nos.	Provided	MR		
12.	Yard Hydrants					
	a) Total number of hydrants	05nos.	Provided	MR		
	b) Hose Box	05nos.	Provided	MR		
13.	Pumping Arrangements		=======================================			
	Ground Level					
	Discharge of main Pump	2850lpm	Provided	MR		
	Head of Main pump	80m	Provided	MR		
	Number of main pumps	02nos.	Provided	MR		
	> Jockey Pump out put	180lpm	Provided	MR		
	> Jockey pump head	80m	Provided	MR		
	Standby Pump out put	2850lpm	Provided	MR		
	➤ Standby Pump Head➤ Auto Starting/Manual Stopping	80m	Provided	MR		
	> Pump House Access	Required	Provided	MR		
		Required	Provided	MR		
	Terrace level					
	Discharge of pump	-NA-	-NA-	-NA-		
	➢ Head of the pump➢ Power Supply	-NA-	-NA- ·	-NA-		
14.	> Auto Starting of pump	-NA-	-NA-	-NA-		
	➤ Auto Starting of pump -NA- Captive Water Storage for fire fighting					
14.	III. day and day and a second					
	Underground tank capacity	2,00,000ltr	Provided	MR		
	> Draw-off connection	Required	Provided	MR		
	> Fire service inlet	Required	Provided	MR		
	> Access to tank	Required	Provided	MR		
	Overhead Tank capacity	20,000ltr	Provided	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
10.	a) Pressurization of Lift Shaft	Required	Provided			
	a) Tressure		- 10 / Ided	MD		
-	b) Pressurization of Lift lobby	Required	Provided	MR MR		

	c) Communication In lift Car	Required	Provided) (D			
/	d) Fireman's Grounding Switch	Required	Provided	MR			
	e) Lift Signage	Required	Provided	MR MR			
_	Standby power supply	Required	DG set Provided	MR			
7.	Refuge Area.						
8.	a) Total Area	-NA-	-NA-	-NA-			
	b) Location	-NA-	-NA-	-NA-			
9.	Fire Control Room						
	a) Detector System Panel	-NA-	-NA-	-NA-			
	b) Flow Switch Panel	-NA-	-NA-	-NA-			
	c) PA System Panel	-NA-	-NA-	-NA-			
	1 0 0 1 move	-NA-	-NA-	-NA-			
	battery backup Building Floor Plans	-NA-	-NA-	-NA-			
0.	Special Fire Protection System for Protection of special Risks, if any:	Required	Co2 flooding system found provided near elect. Panel	MR			

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and

found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 51 dated 04.02.2025, the FSC issued vide letter no. F.6/DFS/MS/DMRC/SZ/2022/89 dated 28.02.2022-Previously for ground floor only, and how FSC under rule 35 of the Delhi Fire Service Rules, 2010 is recommended for 1st & 3rd floor.

> Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO(Rohini)

Appeller Sleps

FT letty is part up for kind
powered and Separative please

ms cell