GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

F.6/DFS/MS/GH/2025/SZ/Q3

Dated: .03/.01/2025

FIRE SAFETY CERTIFICATE

Certified that the Lodging House in the Name & Style of M/s Prakash Guest House at 5606, Basant Road Pahar Ganj, New Delhi- 110055 comprised of Ground plus three upper floor, Ground floor to 3rd floor (07 Guest Rooms at each floor) Total 28 guest rooms was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/NDZ/2022/37 dated 18/01/2022. The premise was re-inspected by the officer concerned of this department on 30/12/2024 in the presence of Mr. N.D Rai (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential, Group-A' (Ground floor to 3rd floor (07 Guest room at each floor) with effect from and validity upto 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010

Issued on 03 01 /2025 at New Delhi by

Copy to: -

1. The Commissioner, MCD, Civic Centre New Delhi, to ensure the occupancy as detailed above and deviation (if any).

2. The Addl. Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-110049 (Ref. MHA Portal 2024052608156 dated 12/12/2024)

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six



| _ | INSPECTION REPORT | | | | |
|--------|---|--|-------------------------|-------------------|--|
| 1 | Name & Address of the Building | M/s Prakash Guest House at 5606, Basant Roa Pahar Ganj, New Delhi | | | |
| 2 | Type of Occupancy | Residential, "Group-A" (Guest House) | | | |
| 3 | Building Comprised of | Ground + 03 upper floors (Total 28 Guest Rooms) | | | |
| 4 | Type of Case | Renewal | | | |
| 5 | Details of Previous NOC | | | | |
| 6 | Fire Safety Directives Letter No | F6/DFS/MS/GH/NDZ/2022/37 dated 18/01/2022 | | | |
| 7 | Date of Inspection | Nil | | | |
| 8 | Name of the Inspecting Officers | 30/12/2024 APO (PGP) | | | |
| 9 | | ADO (BCP) | | | |
| | Name & Designation of Officers from the building side | Mr. ND Rai (Manager) | | | |
| 10 | Year of construction | 1981 GF to 3 rd Floor Total 28 Guest room | | | |
| 11 | Applicant letter No. | MHA Portal 2024052608156 dated 12/12/2024 | | | |
| S. No. | Minimum standards on Fire Prevention and Fire Safety U/R 33 | Old NOC requirements | Provided at Site | Remarks MR/NMR | |
| 1 | Access to Building. | ave jail | A TANKS OF THE PARTY OF | MINIMA | |
| | Road width | -NA- | 06 mtr | MR | |
| | Gate width | -NA- | -NA- | -NA- | |
| | Width of internal road | -NA- | -NA- | -NA- | |
| 2 | Number, width, type & arrangement of exits. | | | | |
| | a) Number of Staircase | 9 - | | | |
| | Upper floors. | 02 Nos | Provided | MR | |
| | Basement floor. | -NA- | -NA- | -NA- | |
| | b) Width of Staircase | | | | |
| | Upper floors | 0.80 mtr | 0.88 mtr & 1.01 mtr | MR | |
| | ➢ Basement floor | -NA- | -NA- | -NA- | |
| | c) Protection of exits | 100.1 | | | |
| | ➤ Fire check door | -NA- | -NA- | -NA- | |
| | ▶ Pressurization | -NA- | -NA- | -NA- | |
| | d) No. of continuous staircase to terrace | -NA- | -NA- | -NA- | |
| | e) Width of corridor | -NA- | NA- | -NA- | |
| | f) Door size | 1m | 1.0 m | MR | |
| 3 | Compartmentation. | process of the second | 1.0 III | IVIK | |
| | Fire check door. | -NA- | -NA- | -NA- | |
| | Sealing of electrical shafts. | -NA- | -NA- | -NA- | |
| | Fire rating of shaft door. | -NA- | -NA- | -NA- | |
| | Water curtain | -NA- | -NA- | -NA- | |
| | Fire dampers. | -NA- | -NA- | -NA- | |
| 4 | Smoke Management system. | As per clause 7.31 of UBBL 2016 | | | |
| | Basement | 30 ACPH | -NA- | -NA- | |
| | Upper floors | 12 ACPH | Natural / exhaust | MR | |
| 5 | Fire Extinguishers. | PATE I | | 350-350 | |
| | Total numbers | 08 Nos | Provided | MR | |
| | Types | ABC / CO2 | ABC & CO2 | MR | |
| | ISI Marking | ISI marked | Provided | MR | |
| 6 | First Aid Hose Reels. | | and the second | | |
| | Total numbers on each floor. | One | Provided | MR | |
| | Length of hose-reel hose. | 30 mtr | Provided | MR | |
| | Nozzle Diameter | 5 mm | Provided | MR | |

| | Automatic fire detection & alarming system. As per clause 7.31 of UBBL 2016 | | | |
|-----|--|-----------------------|----------------------|-------|
| | Type of detectors | As per clause 7.31 of | | MR |
| 1 | Location of Main Panel | Co. Mo. Type | Provided | MR |
| 1 | • Location of Repeater Panel | Required | Provided | -NA- |
| | Alternate source of power | -NA- | -NA- | MR |
| | Hooter's location | Required | Provided Provided | MR |
| 8 | MOEFA | Required | | MR |
| 9 | Public Address System | Required | Provided | MR |
| 0 | Automatic Sprinkler System | Required | Provided | IVIA |
| | Basement | NA . | -NA- | -NA- |
| | Upper floors. | -NA- | -NA- | -NA- |
| i e | | -NA- | -NA- | -NA- |
| 11 | Sprinkler above false ceiling Internal Hydrants. | -NA- | -INA- | |
| | | | -NA- | -NA- |
| | Size of Riser/Down-comer | -NA- | -NA- | -NA- |
| | Number of Hydrant per floor | -NA- | -NA- | -NA- |
| 10 | Hose box. | -NA- | -NA- | 1,1,2 |
| 12 | Yard Hydrants. | 3*4 | -NA- | -NA- |
| | Total number of hydrants. | -NA- | -NA- | -NA- |
| 10 | Hose box. | -NA- | -NA- | 137.5 |
| 13 | Pumping arrangements. | | | |
| | Ground Level | | -NA- | -NA- |
| | Discharge of main pump. | -NA- | -NA- | -NA- |
| | Head of main pump. | -NA- | -NA- | -NA- |
| | Number of main pumps. | -NA- | -NA- | -NA- |
| | Jockey Pump output. Jockey Pump head. | -NA- | NA. | NA |
| | > Standby Pump output. | -NA | -NA- | -NA- |
| | Standby Pump head. | -NA- | -NA- | -NA- |
| | ➤ Auto Starting/Manual Stopping. | -NA- | -NA- | -NA- |
| | > Pump house access. | -NA- | -NA- | -NA- |
| | Terrace Level | -1474 | | |
| | Discharge of pump. | · 180 LPM | Provided | MR |
| | Head of pump. | 30 m | Provided | MR |
| | > Power supply. | Provided | Provided | MR |
| | > Auto starting of pump. | Provided | Provided | MR |
| 14 | Captive water storage for fire fighting. | 217,10127 | The second second | |
| 14 | Underground tank capacity. | -NA- | NA | -NA- |
| | Draw-off connection. | -NA- | -NA- | -NA- |
| | > Fire Service Inlet. | -NA- | -NA- | -NA- |
| | Access to tank. | -NA- | -NA- | -NA- |
| | Overhead tank capacity. | 2,500 ltr | 2,500 ltrs | MR |
| - | CONTRACTOR AND ADMINISTRATION OF THE ADMINIS | Required | Provided | MR |
| 15 | Exit Signage. | Required | Tiovided | IVIK |
| 16 | Provision of Lifts. • Pressurization of lift shaft. | -NA- | -NA- | -NA- |
| | Pressurization of lift shaft. Pressurization of lift lobby. | -NA- | -NA- | -NA- |
| | | -NA- | -NA- | -NA- |
| | Communication in lift car. Fireman's switch. | · -NA- | -NA- | -NA- |
| | | -NA- | -NA- | |
| | Lift signage. Standby Power Symply | Required | Provided | -NA- |
| 17 | | Required | riovided | MR |
| 18 | Refuge Area • Total area | -NA- | -NA- | 177 |
| | | 10,770 8/8 | | -NA |
| | Location | -NA- | -NA- | -NA- |



| | Detector system panel. | -NA- | -NA- | -NA- |
|----|--|------|------|------|
| | Flow switch panel. | NA- | -NA- | -NA- |
| | PA system panel. | -NA- | -NA- | -NA- |
| | Battery backup. | -NA- | -NA- | -NA- |
| | Building floor plan. | -NA- | -NA- | -NA- |
| 20 | Special Fire Protection System for the Protection of special Risk, if any. | | | -NA- |

The fire protection system provided in the building were randomly checked and found

functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/GH/NDZ/2022/37 dated 18/01/2022, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

DO (CD