01105

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI- 110001

No.F.6/DFS/MS/GH/2025/SZ/ 2-2-2

Dated: 21/04/2025

## **FIRE SAFETY CERTIFICATE**

Certified that the M/s. Priyanka Guest House at 4449-50, Katra Raiji, Main Bazar, Pahar Ganj, New Delhi, comprised ofgroundfloor (reception&06 guest rooms), 1sto3rdfloor (08 guest rooms at each floor), 4rd floor not in use (affidavit submitted) (total 30 guest rooms only), was issued FSC by this department vide letter No.F.6/DFS/MS/GH/NDZ/2022/175 dated 30.03.2022. The premises was reinspected by the officer concerned of this department on dated 16.04.2025 in the presence of Manager, and found that the guest house have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class "Residential" (Guest house) (30 guest rooms up-to 3rd floor) w.e.f. 2100 2005 for a period of three yearsin accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 21042025 at New Delhi.

(Atul Garg)
Director

Delhi Fire Service

Copy to: -

1 The Commissioner, MCD, Delhi: to ensure the occupancy as detailed above and deviation, if any.

2 Online application Id 2025032004118 dated 21.03.2025.

## Conditions for the validity of fire safety certificate: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

## INSPECTION REPORT

1. Name & address of the building

: M/s. Priyanka Guest House at 4449-50, Katra Raiji, Main Bazar Pahar Ganj, New Delhi- 110055.

2. Building is comprised of

: G+4 upper floors (30 guest rooms), ground floor (06 guest rooms & reception), 1st to 3nd floor (08 guest rooms at each floor), 4th floor not in use as per affidavit

3. Type of Occupancy

: Residential (Guest House)

4. Type of Case

Renewal

5. Details of Previous FSC letter

: F.6/DFS/MS/GH/NDZ/2022/175 dated 30.03.2022

6. Fire Safety direction letter No

: N/A

7. Date of Inspection

: 17.04.2025

8. Name of the Inspecting officers

: ADO R.K. Yadav (JKP)

9. Name and designation of officer

Manager

from the building side

2005

10. Year of construction

Sr. No.		um Standards on Fire tion and Fire Safety U/R33	Requirements as per FSC dt. 30.03.2022	Provided at Site	Remarks MR/NMR		
l	Access	to Building.					
	•	Road width	N/A	4.0 m	N/A		
		Gate width	N/A	N/A	N/A		
	•	Width of internal road	N/A	N/A	N/A		
2	Numb	er, Width, Type and Arrang	ement of Exits.				
	a. Num	ber of Staircases					
		Upper floor	01 Nos.	01 Nos.	MR		
		Basement	N/A	N/A	N/A		
	B. Wid	th of Staircases					
	•	Upper floor	0.90 m	1.13 m	MR, old case		
	• 4	Basement	N/A	N/A	N/A		
	c. Prote	ction of Exits					
	•	Fire check door	Required	Provided	MR		
		Pressurization	N/A	N/A	N/A		
	d. No.	of Continuous Staircases to	N/A	N/A	N/A		
		h of Corridor	N/A	N/A	N/A		
	f. Door		1.0 m	1.0 m	MR, old case		
3	Compartmentation.						
		Fire check door	N/A	N/A	N/A		
		Sealing of electrical shafts	N/A	N/A	N/A		
		Fire rating of shaft door	N/A	N/A	N/A		
		Water curtain	N/A	N/A	N/A		
	•	Fire dampers	N/A	N/A	N/A		
4	Smok	Management System.					
	-	Basement	N/A	N/A	N/A		
	•	Upper floor	12 ACPH	Provided	MR		
5.	Fire F	ktinguishers.					
		Total numbers	10 nos.	Provided	MR		
	. •	Types	ABC /CO <sub>2</sub>	Provided	MR		
		IS marking	ISI marked	Provided	MR		

06	First-Aid-Hose Reels.	1 10.42	,64 X	MR		
	Total numbers on each floor					
		30 m	Provided	MR MR		
	<ul> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> </ul>	05 mm	Provided			
07	Automatic Fire Detection, CO detection and Alarming System.					
07			Provided	MR		
	CO Type of detectors	Required	Provided at GF	MR		
	<ul> <li>Location of main panel</li> </ul>	Required	N/A	N/A		
	<ul> <li>Location of repeater panel</li> </ul>	N/A	Provided	MR		
	<ul><li>Alternate source of power</li><li>Hooter's location</li></ul>	Required Required	Provided at each floor	MR		
08	MOEFA	Required	Provided	MR		
09	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.		X 12	, et <u>al</u>		
		N/A	N/A	N/A		
	Basement & Stilt	N/A	N/A	N/A		
	<ul><li>upper floor</li><li>sprinkler above false ceiling</li></ul>	N/A N/A	N/A	N/A		
			The state of the s	B)		
11	Internal Hydrants	111111111111111111111111111111111111111	NI/A	N/A		
	size of riser/down-comer	N/A	N/A N/A	N/A		
	<ul> <li>Number of hydrants per floor</li> </ul>	N/A	N/A N/A	N/A		
	Hose box	N/A	IV/A			
2	Yard Hydrants.					
	Total number of hydrants	N/A	N/A	N/A		
	Hose box	N/A	N/A	N/A		
13	Pumping Arrangements.		The same of	175		
	> Ground Level					
	Discharge of main pump		27//	>7/A		
	Head of main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby pump out put	N/A	N/A	N/A		
	Standby pump head	N/A	N/A	N/A		
	Auto starting /manual	N/A	N/A	N/A N/A		
	stopping	N/A	N/A	N/A		
	Pump house access     Terrace Level	il i				
		450 LPM	450 LPM	MR		
	Discharge of pump	40 m	40 m	MR		
	Head of the pump	Required	Provided	MR		
	<ul> <li>Power supply</li> <li>Auto Starting of pump</li> </ul>	Required	Provided	MR		
	Captive Water Storage for Fire Fighti	ng.				
4	Captive Water Storage for The Again	N/A	N/A	N/A		
	Underground tank capacity	N/A	N/A	N/A		
	<ul> <li>Draw-off connection</li> </ul>	N/A	N/A	N/A		
	<ul> <li>Fire service inlet</li> </ul>	N/A	N/A	N/A		
	<ul><li>Access to tank</li><li>Overhead Tank capacity</li></ul>	5,000 ltrs	5,000 ltrs	MR		
1	- I Werneau Laux Capaciti					

/	Provision of Lifts.						
		Pressurization of Lift Shaft	N/A	N/A	N/A		
A		Pressurization of Lift lobby	N/A	N/A	N/A		
V		Communication in lift car	N/A	N/A	N/A		
17		Firemen's grounding switch	N/A	N/A	N/A		
	•	Lift Signage	N/A	N/A	N/A		
	Standb	y power supply	Required	Provided	MR		
8	Refuge	Refuge Area.					
	•	Total area	N/A	N/A	27/4		
	•	Location	N/A	N/A	N/A N/A		
19	Fire Control Room						
	•	Detector system panel	N/A	N/A	N/A		
	•	Flow switch panel	N/A	N/A	N/A		
		PA system panel	N/A	N/A	N/A		
	•	Battery backup	N/A	N/A	N/A		
		Building Floor Plans	N/A	N/A	N/A		
20	Special	Fire Protection systems for ion of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/GH/NDZ/2022/175 dated 30.03.2022, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note: - As per undertaking submitted by the guest house management (placed at C-C) the guest house building comprised of ground floor (06 guest rooms & reception), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (08 guest rooms at each floor (total 30 guest rooms) & 4<sup>th</sup> floor not in use (undertaking submitted) and not using any floor above third floor.

Signature of Inspecting Officer

Name: - R.K. Yadav Designation: - ADO (JKP)

DO (\$XV)

4/25

mgs 19

12/4//302

Mas /skn