



FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2025/NDZ/ 1214

Dated:

30/09/2025

FIRE SAFETY CERTIFICATE

Certified that the Puspanjali Modern Public School located at Main Road Tukmirpur Extn., Near Delhi Police Camp, Delhi -110090, comprised of Ground plus two upper floors (two separate blocks) owned/occupied by Puspanjali Modern Public School was issued FSC vide letter No. F.6/DFS/MS/2022/NDZ/943 dated 02/09/2022. The premises was re-inspected by the officer concerned of this department on 22/09/2025 in the presence Sh. Yogesh Vats, Managerand observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of Delhi Fire Service Rules 2010 and that the premises is fit for occupancy class "Educational" (Group-B) with effect from 30/09/2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010& also conditions printed below.

Issued on 30 09 2025 at New Delhi by.

(VIRENDRA SINGH)
CHIEF FIRE OFFICER

To.

1. The Dy. Director of Education, B-Block, Yamuna Vihar, Delhi-110053

2. The Manager, Puspanjali Modern Public School located at Main Road Tukmirpur Extn., Near Delhi Police Camp, Delhi -110090

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the firefightingequipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

1. Name & address of the building

: Puspanjali Modern Public School

Main Road Tukmirpur Extn., Near Delhi Police Camp, Delhi-110090

2. Building is comprised of

: G+2 (Two separate blocks)

3. Type of Occupancy

: Educational, Group-B

4. Type of Case

: Addition/Alteration

5. Details of Previous NOC letter

: F.6/DFS/MS/ 2022/NDZ/943 dt 02/09/2022

6. Fire Safety direction letter No.

: NBC Part IV

7. Date of Inspection

: 17/09/2025

8. Name of the Inspecting officers

: ADO Deepak Kumar

9. Name and designation of Officer

from the building side

: Sh. Yogesh Vats, Manager

10. Year of Construction

: 2012 & 2013

11. Applicant's letter No

: ppushpanjalischool@gmail.com dated 02/09/2025

Sr. No.	Minimum Standards on fire prevention and fire safety U/R33	NBC Part IV/BBL Requirement	Provided at Site	Remarks MR/NMF			
01	Access to building						
	Road width	06 m	06 m	MR			
	Gate width	N/A	N/A	N/A			
	 Width of internal road 	N/A	N/A	N/A			
02	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper Floor	01 no. first block) 01 no. 2 nd block)	01 no. (first block) & 01 no. (2 nd block)	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases • Upper Floor	1.50 m + 1.50 m	1.50 m (first block) & 1.50 m. (2 nd block).	MR			
		N/A	N/A	N/A			
	Basement	N/A	N/A	N/A			
	c. Protection of exits	N/A	N/A	N/A			
	 Fire check door 	N/A	N/A	N/A			
	 Pressurization 						
	d. No. of continuous staircases	01 nos. in	01 nos. in each	MR			
	to terrace	each block	block				
		1.50 m	1.60 m & 1.55	MR			
	e. Width of Corridor f. Door Size	01 m	01 m	MR			
03	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	 Sealing of electrical shafts 	N/A	N/A	N/A			
	 Fire rating of shaft door 	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	12 ACPH	Provided	MR			
	Upper floor	N/A	N/A	N/A			

05.	Fire Extinguishers	12 nos.	16 nos.	MR				
	Total numbers	ABC /CO ₂	ABC /CO ₂	MR				
	• Types	ISI marked	ISI marked	MR				
	IS marking							
06	First-aid-Hose Reels. O1 no +01 no. Provided MR							
	Total numbers on each floor	01 no +01 no.	Provided	MR				
	Length of hose reel hose	30 mtr	Provided	MR MR				
	i diamater	05 mm	Provided	IVIR				
07	Nozzle diameter Automatic fire detection and alarming system. Automatic fire detection and alarming system.							
07		N/A	N/A	N/A				
	Type of detectors	N/A	N/A	N/A				
	Location of main panel Location of repeater panel	N/A	N/A	N/A				
		N/A	N/A	N/A				
	Alternate source of power	N/A	N/A	N/A				
	Hooter's	18003						
	location	N/A	N/A	N/A				
08_	MOEFA System	N/A	N/A	N/A				
09_	Public address System.							
10	Automatic Sprinkler System.	N//A	N/A	N/A				
	Basement	N/A	III EATOMIO CHE					
	upper floor	N/A	N/A	N/A				
	to the state of the coiling	N/A	N/A	N/A				
44	sprinkler above false ceiling Internal Hydrants							
11		N/A	N/A	N/A				
10	size of riser/down-comer	N/A	N/A	N/A				
	 Number of hydrants per floor 			N/A				
	Hose Box	N/A	N/A	IN/A				
12	Yard Hydrants.							
14		N/A	N/A	N/A				
	Total number of hydrants	N/A	N/A	N/A				
	Hose Box							
13	Pumping Arrangements.							
	Ground Level	N/A	N/A	N/A				
	Discharge of main Pump	N/A	N/A	N/A				
	> Head of Main Pump	N/A	N/A	N/A				
-	> Number of main pumps	N/A	N/A	N/A				
	> Jockey pump out put	N/A	N/A	N/A				
	> Jockey pump head	N/A	N/A	N/A				
	> Standby pump out put	N/A	N/A	N/A				
	Standby pump Head	N/A	N/A	N/A				
	> Auto Starting /Manual	N/A	N/A	N/A				
	stopping	1	75.90	£ I				
	Pump House Access							
	Terrace Level							
	Discharge of pump	450 lpm	450 lpm	MR				
	Head of the Pump	40 mtr	40 mtr	MR				
	Power supply	Required	Provided	MR				
	Auto Starting of pump	Required	Provided	MR				

14	Captive Water Storage for Fire Fighting.	I N/A	N/A	N/A		
		N/A	N/A	N/A		
	Underground tank capacity	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	> Fire service inlet	Required	Provided	MR		
_	> Access to tank	10,000 ltr	10,000 ltr	MR		
	Overhead Tank capacity	Required	Provided	MR		
15	Exit Signage.	Required				
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
			N/A	N/A		
	 Pressurization of Lift lobby 	N/A	N/A	N/A		
	Communication in lift car	N/A	N/A	N/A		
	Firemen's grounding switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	N/A	INIZA			
17_	Define Area					
8	Reluge Alea.	N/A	N/A	N/A		
	Total area	N/A	N/A	N/A		
		Location				
9	Fire Control Room					
9		N/A	N/A	THE ACCUSAGE AND ADDRESS OF TH		
10	 Detector system panel 	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	WARRED D	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Puilding Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	INA	10:00.45		

The fire protection systems provided in the building were tested/checked and found

functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter No. prevention and fire safety required under the rules the FSC issued vide letter No. F.6/DFS/MS/ 2022/NDZ/943 dt 02/09/2022 renewal under rule 35 of the Delhi Fire Service

Rule, 2010 is recommended.

Signature of the Inspecting Officer
Name :- Deepak Kumar

Name Designation

:- A.D.O (Shahdara)

DOLEDI -

LIV Pyloghs

25 91 (202

Principal Director

Of to

25/39/25

ADO (stati)

To ly