

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001**



No F 6/DFS/MS/Cinema/WZ/2025/ 277

Dated: 30 05 1 075

FIRE SAFETY CERTIFICATE

Certified that the PVR INOX Cinema (Audi 1 to 4) located at 3rd, 4th & 5th floor, DLF City Centre Mall, A- Block, Community Centre, Shalimar Bagh, New Delhi in a building comprised of Lower Basement, Upper Basement, Ground and Five upper floors was issued fire safety certificate vide Letter No. F6/DFS/MS/Cinema/WZ/2022/291 dated 29/06/2022 was reinspected by the officer concerned of this department on 15.05.2025 in the presence of Sh. Jitender (Manager) & Sh. Surender Singh (FSSO) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premise is fit for occupancy class "Assembly Building Group D with effect from 30 05 2005 for a period of three years in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30 05 202」 at New Delhi by

Conditions for the validity of Fire Safety Certificate:

1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able at the time of emergency.

2. All the fire safety arrangement provided there-in shall be maintained in good working

conditions at all times.

3. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

This certificate cannot be treated in any case for regularizations of unauthorized

construction.

The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

www.dfs.delhigovt.nic.in

9. The FSC is issued for the cinema only (3rd, 4th & 5th floor).

Copy to: -

1. The SDM (HQ-1)/ Kanjhawala, District North West, Kanjhawala, Delhi- 110081.

2. The Dy. Health Officer, MCD, Sec. 5, Rohini Zone, Rohini, Delhi- 110085.

The Authorized Signatory, PVR INOX Cinema (Audi 1 to 4) located at 3rd, 4th & 5th floor, DLF City Centre Mall, A- Block, Community Centre, Shalimar Bagh, New Delhi.

INSPECTION REPORT Name & address of the building: PVR INOX Cinema (Audi Ito 4) located at 3rd, 4th & 5th floor, DLF City Centre Mall, A- Block, Community Centre, Shalimar Bagh, New Delhi. Type of Occupancy Cinema (Assembly) **Building Comprised of** Lower Basement, Upper Basement, Ground plus five upper floors. 4. Type of Case Renewal (for cinema only) 5. Details of Previous NOC F6/DFS/MS/Cinema/WZ/2022/291 Dated 29/06/2022 6. Fire Safety directives letter No : F6/DFS/MS/BP/2004/2443 Dated 14/10/2004 (for Mall) 7. Date of inspection 15/05/2025 8. Name of Inspecting Officer R.K.Sinha, ADO (BW) 9. Name and designation of officers From the building side Sh. Jitender Singh (Manager) & Sh. Surender Singh (FSSO) 10. Year of Construction 2005-06 11. Applicant's letter No. Outdoor Diary No. 1444 dated 07/05/2025 Minimum Standards on fire S. **BBL/Inspection** Provided at site prevention and fire safety U/R 33 No. Remarks report 10/06/2022 MR/NMR 1. Access to building Road width 12 m Provided MR Gate width 4.5 m Provided MR Width of internal road 6 m Provided MR 2. Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors 04 08 MR Basements NA NA NA b. Width of staircases Old case Upper Floor 1.5 m × 5, 1.93 m, 1.48 m, 2 m MR Old case Basements Provided MR c. Protection of exits Required Fire check door Provided MR Required Pressurization Provided MR d. No. of continuous staircases to 04 Provided MR terrace Width of Corridor Required Provided MR Audi-1 = 2×1.82 m, 1.76 m & 1.93 m Old case MR(old Audi-2 = 2 × 1.82 m, 1.75 m & 1.71 m case) f. Door Size Audi-3 = $2 \times 1.8 \text{ m} \& 2 \times 1.75 \text{ m}$ Audi-4 = 2×1.75 m, 1.80 m & 1.83 m Compartmentation 3. Required Fire check door Provided MR Required Sealing of electrical shafts Provided MR Required Fire Rating of shaft door Provided MR Required Water Curtain Provided MR Fire Dampers Required Provided MR Smoke Management System 4. Basements Required Provided MR Upper floors Required Provided MR Fire Extinguishers 5. Total numbers 04 in each Audi Provided MR Types ABC,Co2 & WCO2 Provided MR IS marking Required Provided MR First-Aid Hose Reels 6. Total numbers on each floor 2 in each Audi Provided MR Length of hose reel hose 30 m Provided MR Nozzle diameter 5 mm Provided MR 7. Automatic fire detection and alarming system Type of detectors Beam Detector Provided MR Location of Main Panel G.F. Provided MR Location of Repeater Panel

Provided

Provided

MR

MR

G.F.

Required

Alternate source of power

	7 E 8	Required	Provided	MR		
	Hooters' Location	Required	Provided	MR		
8	MOEFA	Required Provided		MR		
9	Public Address System	100,000				
10.	Automatic Sprinkler System Basement	Required	Provided	MR		
		Required	Provided	MR		
	Upper Floor The second of the seco	Required	Provided	MR		
	Sprinkler above false ceiling					
11.	Internal Hydrants	150 mm	Provided	MR		
	Size of riser/down-comer	2 in each Audi	Provided	MR		
	Number of hydrants per floor	Required	Provided	MR		
	Hose Box					
12.	Yard Hydrants	06	Provided	MR		
	Total number of hydrants Hose Box	06	Provided	MR		
12		(Common with ma	11)			
13.	Pumping Arrangements (Common with mall) Ground Level					
	➤ Discharge of main Pump	4500 lpm	Provided	MR		
		60 m	Provided	MR		
	➤ Head of Main pump) (D		
	> Number of main pumps	3	Provided	MR		
	> Jockey Pump out put	180 lpm × 2	Provided	MR		
	➤ Jockey pump head	60 m	Provided	MR		
	Standby Pump out put	4500 lpm	Provided	MR		
	Standby Pump Head	60 m	Provided	MR		
	➤ Auto Starting/Manual	Required	Provided	MR		
	Stopping	Deguised	Provided	MR		
	> Pump House Access	Required	Flovided	MAK		
	Terrace level					
	➢ Discharge of pump	450 lpm	NA	NA		
	➤ Head of the pump	40 m	NA	NA .		
	➤ Power Supply	Required	Provided	MR		
	Auto Starting of pump	Required.	Provided	MR		
14.	Captive Water Storage for fire fighting (Common with mall)					
	Underground tank capacity	3,00,000 ltrs	Provided	MR		
	> Draw-off connection	Required	Provided	MR		
	> Fire service inlet	Required	Provided	MR		
	> Access to tank	Required	Provided	MR		
	Overhead Tank capacity	30,000 ltrs	Provided	MR		
15.	Exit Signage.	Required	Provided			
16.	Provision of Lifts					
	Pressurization of Lift Shaft	Required	Provided	MR		
	Pressurization of Lift lobby	Required	Provided	MR		
	Communication In lift Car	Required '	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
17.	Standby power supply					
		Required	DG Set (450 K.V.A)	MR		
18.	Refuge Area.					
	> Total Area	NA	NA	NA NA		
10	► Location	NA	NA	NA		
19.	Fire Control Room					
			T			
	Detector System Panel	Required	Provided	MR		

AMR PA	System Panel	N-52			
Bat	tery backup	Required			
• Bui	lding Floor DI	Required	Provided	MR	
Special Riv	0 D 4	Required	Provided	MR	
Protection	of special Risks, if any:	NA	Provided	MR	
			NA		
functio fire saf issued Delhi I	The fire protection systemal at the time of inspection Keeping in view of deem fety measures as required vide letter no. F6/DFS/Maire Service Rules, 2010.	Inder rules it is recomm IS/Cinema/WZ/2022/29	ouilding were tested, cominimum standards of innended to renew the firm of the dated 29/06/2022 under the Signature of Name : R	checked and found fire prevention and re safety certificate ader rule 37 of the Of Inspecting Officer Rajeev Kumar Sinha ion: ADO/B.W.	