## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2025/WZ/GH/ 119

Dated: 06 03 2025

## FIRE SAFETY CERTIFICATE

Certified that the M/s Meridian Plaza Situated at R-41, R-Block, Greater Kailash-1, New Delhi 110048., comprised of Basement, Ground + 03 upper floors, but guest house running at Ground + 03 upper floors, (Total -28 guest rooms) was earlier granted FSC by this department vide letter No. F.6/DFS/MS/GH/2021/SZ/383 dated 14.09.2021. Now, the premises was re-inspected by the officer concerned of this department on 20.02.2025 in the presence of Mr. Manoj (Manager) and deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Residential, Sub Division-A-1, for Ground + 03 upper floors, (Total -28 guest rooms) with effect from 06/03/2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on \_\_\_\_\_\_\_ 06 03 2025 at New Delhi by

Copy to: -

1. MHA Portal ID- 2025021301836 dated 13.02.2025.

2. The Addl. Commissioner of Police (Lic), 1st floor, P.S. Defence Colony New Delhi.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building

5. This fire safety certificate cannot be treated in any case for regularizations of unauthorized

- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms

		INSPE	CTION REPORT				
FI	Name & address of the building	M/s N	feridian Plaza Situa	ated at R-41, R-Block, G	reater Kailash-1.		
	= 60	New Delhi 110048					
2.			ntial, "Group-A" (Guest House)				
4.	Type of Case Renew		ent (Vacant), Groun	nd + 03 upper floors			
			newal (Ground + 03 upper floors, Total 28 Guest rooms)				
6.	Fire Safety directives letter No	tives letter No NBC Part IV					
7.							
8.	ADO (Rohini)						
9.	Name of Inspecting Officer Name and designation of officers	ло (коши)					
10	From the building side  O. Year of Construction	2008	on MCD Portal				
_	. Applicant's letter No.						
S.	Minimum Standards on fire pre	Unline	Old NOC	25021301836 dated 13.02 Provided at site	Remarks		
No	and fire safety U/R 33	vention	requirement	Provided at site	MR/NMR		
1.	Access to building						
	Road width		Required	9m	MR		
	Gate width		-NA-	-NA-	-NA-		
	Width of internal road		-NA-	-NA-	-NA-		
2.	Number, Width, Type & Arrang	ement of	Exits				
	a. Number of staircases						
	Upper Floors		Required	02nos.	MR		
	Basements		Required	02nos.	MR		
	b. Width of staircases			OZHOS.	- 74		
	ST WILLIAM STATE CLOSES				MR		
	Upper Floor		1.25m	1.25m & 0.90m	(low occupancy load height increasing 15n as per UBBL)		
1	Basements		1.25m	1.25m	MR		
	c. Protection of exits			20000000	100 30 50-000		
	Fire check door		-NA-	-NA-	-NA-		
	Pressurization		-NA-	-NA-	-NA-		
ė	d. No. of continuous staircases to terrace		Required	Olnos.	MR		
	e. Width of Corridor		-NA-	-NA-	-NA-		
	f. Door Size		1m	1m (final exit)	10000000		
3.	Compartmentation		****	Tili (Illiai exit)	MR		
	a) Fire check door		-NA-	NA	37.		
	b) Sealing of electrical shafts		-NA-	-NA-	-NA-		
	c) Fire Rating of shaft door		-NA-	-NA-	-NA-		
	d) Water Curtain		4-15-17-77	-NA-	-NA-		
	100		-NA-	-NA-	-NA-		
	e) Fire Dampers		-NA-	-NA-	-NA-		
•	Smoke Management System		1 20 /				
	a) Basements		30 a/c per hour	Exhaust fan & open able windows	MR		
	b) Upper floors		12 a/c per hour	Exhaust fan	MR		
5.	Fire Extinguishers						
	a) Total numbers		10nos.	Provided	MR		
	b) Types		ABC/CO2	ABC/CO2	MR		
	c) IS marking		ISI marked	Yes	MR		
$\neg$	First-Aid Hose Reels		-CA HIMAROU	103	IVIK		

By

	a) Total numbers on 1.5				
	multipels on each those	01nos.	Provided	MR	
	b) Length of hose reel hose c) Nozzle diameter	30mm	Provided	MR	
	, and a state of the state of t	5m	Provided	MR	
	Automatic fire detection and alarming system				
	a) Type of detectors	Co2	Provided	MR	
	b) Location of Main Panel	-NA-	-NA-	-NA-	
	c) Location of Repeater Panel	-NA-	-NA-	-NA-	
	d) Alternate source of power	-NA-	-NA-	-NA-	
*	e) Hooters' Location	-NA-	-NA-	-NA-	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System				
	a) Basement	Required	Provided	MR	
	b) Ground & Upper Floors	-NA-	-NA-	-NA-	
	c) Sprinkler above false ceiling	-NA-	-NA-	-NA-	
11.	Internal Hydrants		n!11	MR	
	a) Size of riser/down-comer	Required	Provided Provided	MR	
	b) Number of hydrants per floor	01nos.	に対象が2000年2	MR	
	c) Hose Box	01nos.	Provided	IVIX	
12.	Yard Hydrants		-NA-	-NA-	
	a) Total number of hydrants	-NA-	-NA-	-NA-	
J.	b) Hose Box	-NA-	-NA-		
13.	Pumping Arrangements				
	Ground Level	-NA-	-NA-	-NA-	
	> Discharge of main Pump	-NA-	-NA-	-NA-	
	> Head of Main pump	-NA-	-NA-	-NA-	
	> Number of main pumps	-NA-	-NA-	-NA-	
	> Jockey Pump out put	-NA-	-NA-	-NA-	
	> Jockey pump head	-NA-	-NA-	-NA-	
	<ul><li>Standby Pump out put</li><li>Standby Pump Head</li></ul>	-NA-	-NA-	-NA-	
	C A famual Stonning	-NA-	-NA-	-NA-	
		-NA-	-NA-	-NA-	
11	> Pump House Access				
	Terrace level	450lpm & 180lpm	Provided	MR	
	Discharge of pump	35m .	Provided	MR	
	➤ Head of the pump	Required	Provided	MR	
	> Power Supply	Required	Provided	MR	
	Auto Starting of pump Required				
14.	Captive Water Storage for fire fighting	-NA-	-NA-	-NA-	
	<ul> <li>Underground tank capacity</li> </ul>	OA-SWATE	-NA-	-NA-	
	Draw-off connection	-NA-	M-00032	MR	
	➢ Fire service inlet	Required	Provided		
	> Access to tank	-NA-	-NA-	-NA-	
		5,000ltr	Provided	MR	
	Overhead Tank capacity  This is a second to the second term of th	Required	Provided	MR	
15.	Exit Signage.				
16.	Provision of Lifts.	-NA-	-NA-	-NA-	
	a) Pressurization of Lift Shaft	Required	Provided	MR	
	b) Pressurization of Lift lobby	-NA-	-NA-	-NA-	
	c) Communication In lift Car	112 5		-	

JZ						
	d) Fireman's Grounding Switch	-NA-	-NA-	-NA-		
V	e) Lift Signage	-NA-	-NA-	-NA-		
17. 18.	Standby power supply	Required	Provided	MR		
	Refuge Area.					
	a) Total Area	-NA-	-NA-	-NA-		
	b) Location	-NA-	-NA-	-NA-		
19.	Fire Control Room					
	a) Detector System Panel	-NA-	-NA-	-NA-		
	b) Flow Switch Panel	-NA-	-NA-	-NA-		
	c) PA System Panel	-NA-	-NA-	-NA-		
	d) Battery backup	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
20.	e) Building Floor Plans  Special Fire Protection System for Protection of special Risks, if any:	-NA-	-NA-	-NA-		

Accordingly, the fire protection systems provided in the building were tested/ checked randomly

and found in working condition at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2021/SZ/383 dated 14.09.2021 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010.

> 1211115 Signature of the Inspecting Officer

Ajay Kumar Sharma Name Designation ADO(Rohini)

DO( SØ)

for letter or pur up for kind presalt and Sonatur Geore.