GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELIII HEADQUARTERS: DELIII FIRE SERVICE: NEW DELIII- 110001



No. F6/DFS/MS/School/NDZ/2025/ 58

Dated: 24/01/2025

FIRE SAFETY CERTIFICATE

Certified that the Raghukul Public School at Gharoli Mayur Vihar, Phase - III, Delhi — 110096, building comprised ground plus one upper floor owned/occupied by Raghukul Public School was issued Fire Safety Certificate vide letter No. F6/DFS/MS/School/2018/NDZ/652 dated 10/04/2018. The School building was re-inspected by the officer concerned of this department on 10/01/2025 in presence of Mr. Yoginder Kumar (Manager) and observed that all the fire prevention and fire safety requirements in the premises found in good working condition. The premises have therefore deemed complied with the Fire Prevention and Fire Safety requirements in accordance with Circular No. 262 - 362 dated 17/01/2005 issued by Director of Education and that the building is fit for occupancy class (Group - B) "Educational Building" with effect from 24/01/2025 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010. Subject to conditions printed below.

Issued on 24 01 2025 at New Delhi by.

(AZUZ GARG)
/ DIRECTOR
/ CDELHI FIRE SERVICE

Copy to:-

- The Dy. Director of Education, D- Block, Anand Vihar, Delhi 110092.
- 2. The Manager, Raghukul Public School at Gharoli Mayur Vihar, Phase III, Delhi 110096.

Conditions for the validity of Fire Safety Certificate

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

1 1	\·	INSPE	CTION REPORT				
1	Nar	ne & address of the building	Raghukul Public School at Gharoli Mayur Vihar				
2	Bui	lding is comprised of	Phase - III, Delhi - 110096.				
3	Tyr	e of occupancy	Ground plus one upper floor only				
4			Educational Building				
	Type of case Renewal						
5	Det	ails of previous FSC	F6/DFS/MS/School/2018/NDZ/652 dated 10/04/2018.				
6	Fire safety directives letter no. Circular No. 262 - 362 dated 17/01/2005				2005		
7	Dat	e of inspection	10/01/2025.				
8		ne of the inspecting officers	Yashwant Singh I	Yashwant Singh Meena ADO/Laxmi Nagar			
9	Naı	me of the designation of cer from the building side	A A Comment of the Co				
10		ar of construction	2006	The second	1 10 11		
11	350	plicant's letter no.	Outdoor Dairy No	o. 10675 dated 24/	12/2024		
S.No	M	inimum standard of fire safety requirements as per circular no.262-362 dated 17.01.2005	Requirement Circular	- III Domork			
1	Ac	cess to Building:	ALL ALL THE				
	A	Road width	6.0 mtrs.	3.0 mtrs.	MR/except as earlier		
19.0	В	Gate width	4.5 mtrs.	6.0 mtrs.	MR		
- 4	C	Width of internal road	N/A	N/A	N/A		
2		mber, Width, Type and Arra					
	A Number of staircases						
	-	a Upper floor	01 no.	01 no.	MR		
		c Basement	N/A	N/A	N/A		
	В	Width of staircases		Abenting A. A.	entre se bret		
		a Upper floor	1.5 mtrs	1.5 mtrs	 MR		
		b Basement	N/A	N/A	N/A		
	C	Protection of exits	- A-W				
	۳	a Fire check door	N/A	N/A	N/A		
		b Pressurization	N/A	N/A	N/A		
	D	No. of continuous staircases to terrace	01 no.	01 no.	MR		
	E	Width of corridor	1.5 mtrs.	1.5 mtrs.	MR		
	F	Door size	1.0 mtr.	1.0 mtr.	MR		
3	Co	mpartmentation:	1 100	an angle in the second	1 100		
	A	Fire check door	NA	NA NA	NA		
8	В	Sealing of electrical shafts	N/A	N/A	N/A		
	C	Fire rating of shaft door	N/A	/ N/A	N/A		
	D	Water curtain	N/A	N/A	N/A		
4	E	Fire dampers	N/A	N/A	N/A		
4	+	noke Management System:					
	A	Basement	N/A	N/A	N/A		
	B	Upper floor	N/A	N/A	N/A		

<i>-</i>	N112						
5.	Fire Extinguisher:						
	A	Total numbers	04 nos.	04 nos.	MR		
	B	Types	CO ₂ & ABC	CO ₂ & ABC	MR		
	C	ISI marking	ISI Marked	Provided	MR		
6	Fi	rst-Aid-Hose Reel:					
	A	Total numbers of each	01 no	01 no	MR		
	D	floor	30 m	30 m	MR		
	B	Length of hose reel hose Nozzle diameter	05 mm	05 mm	MR		
_	Automatic Fire Detection and Alarming System:						
7			N/A	N/A	N/A		
	A	Type of detectors	N/A	N/A	N/A		
	B	Location of main panel Location of repeater panel	N/A	N/A	N/A		
	C	Alternate source of power	N/A	N/A	N/A		
	D		N/A	N/A	N/A		
0	E	Hooters	N/A	N/A	N/A		
8		OEFA:	N/A	N/A	N/A		
9		blic Address System:	IN/A	11/74	1971		
10		tomatic Sprinkler System:	NY/A	NT/A	N/A		
	A	Basement	N/A	N/A			
	В	Upper floor	N/A	N/A	N/A		
	C	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants:						
	A	Size of riser/down-comer	N/A	N/A	N/A		
	В	Number of hydrants per floor	N/A	N/A	N/A		
	C	Hose box	N/A	N/A	N/A		
12	Yard Hydrants:						
	A	Total number of hydrants	N/A	N/A	N/A		
	В	Hose box	N/A	N/A	N/A		
13	0.7757	mping Arrangements:		(FU-dame	he to th		
1	Ground level						
(*)	A	Discharge of main pump	N/A	N/A	NT/A		
	B	Head of main pump	N/A	20 Xenda (e)	N/A		
	C		100000000000000000000000000000000000000	N/A	N/A		
	D	Number of main pumps	N/A	N/A	N/A		
	E	Jockey pump out put Jockey pump head	N/A	N/A	N/A		
	F	Standby pump out put	N/A	N/A	N/A		
	G		N/A	N/A	N/A		
	Н	Standby pump head Auto starting /manual	N/A	N/A	N/A		
		stopping	N/A	N/A	N/A		
2	I	Pump house access	N/A	N/A	N/A		
2	Terrace Level						
	A	Discharge of pump	220 LPM	220 LPM	MR		
	B	Head of the pump	40 m	40 m	MR		
	C	Power supply	Required	Provided	MR		
	D	Auto starting of pump	Required	Provided	*****		

Raghukul Public School at Gharoli Mayur Vihar, Phase-III, Delhi-96.

14	Çaj	Captive Water Storage for Fire Fighting:					
	A	Underground tank capacity	N/A	N/A	N/A		
4	B	Draw-off connection	N/A:	N/A	N/A		
- 1	C	Fire service inlet	N/A	N/A	N/A		
- 1	D	Access to tank	N/A	N/A	N/A		
,	E	Overhead tank capacity	2500 liters.	2500 liters.	MR		
15	_	t Signage:	N/A	N/A	N/A		
16	Provision of Lifts:						
7	A	Pressurization of lift shaft	N/A	N/A	N/A		
	В	Pressurization of lift lobby	N/A	N/A	- N/A		
1	C	Communication in lift car	N/A	N/A	N/A		
	D	Firemen's grounding switch	N/A	N/A	N/A		
	E	Lift signage	N/A	N/A	N/A		
17		andby Power Supply:	N/A	N/A	N/A		
18	Defuge Area						
10	A	Total area	N/A	N/A	N/A		
	B	Location	N/A	N/A	N/A		
19	Fine Control Doom:						
13	-	Detector system panel	N/A	N/A	N/A		
	A B	Flow switch panel	N/A	N/A	N/A		
	C	PA system panel	N/A	N/A	N/A		
	D	Battery backup	N/A	N/A	N/A		
	10	Duilding floor plans	N/A	N/A	N/A		
20	Sp	ecial Fire Protection systems for prote	ection of specia	al Risks, if	N/A		

The fire protection system was randomly checked and tested and was found functional at the time of inspection.

In view of deemed compliance of the minimum standards of fire prevention and fire safety measured as required under the rules. The fire Safety Certificate issued vide letter no. F6/DFS/MS/School/2018/NDZ/652 dated 10/04/2018 renewal under the Circular No. 262 - 362 dated 17/01/2005 is recommended.

No file is pending with me before disposal of this case.

Signature of the Inspecting Officer

Name: - Yashwant Singh Meena

Designation: - ADO (L.N)

D.O/EAST

15 Janos 22/01/225

was (ND) - On leave

C.F.O. Jung Jane

Direta

Applin

P. J.0