

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001



Dated: 26 |06 | 2025

No. F6/DFS/MS/School/WZ/2025/ 835

FIRE SAFETY CERTIFICATE

Certified that the Rahul Public School, D-16, Rajiv Nagar Ext. Delhi-110086, comprised of 03 Blocks interconnected, Gr. + 1 upper floor, ground + 02 upper floor & ground + 03 upper floors, but school is running at ground + 03 upper floors owned/ occupied by Rahul Public School have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of fire service on dated 19.06.2025 in the presence of Mr. Rahul Solanki and that the building/ premise is fit for occupancy Group B Educational with effect from 26 06 2025 for one block having ground + 03 upper floor only a period of three years, in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 26 06 2025 at New Delhi by

Ph; 011-23414000

Copy to:

- 1. The Principal, Rahul Public School, D-16, Rajiv Nagar Ext. Delhi-110086.
- 2. The Director of Education, GNCT of Delhi Old Secretariat, Delhi-110054 Conditions for validity of Fire Safety Certificate;
- 1. All the fire safety arrangement provided there-in shall be maintained in good working
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+ http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms

7/M

	1		****		a			
4	NY 0.	C.1 1	INSPE	CTION REPORT				
		address of the building	Rahul Public School, D-16, Rajiv Nagar Ext. Rohini, Delhi-					
2.	Type of C	Occupancy	Educat					
3.					C- 11	d + 02 uppe		
4.	Type of C		floor &	03 Blocks interconnected Gr. + 1 upper floor, ground + 02 upper floor & ground + 03 upper floors				
	Details of Previous NOC F.6/			ase (School runnin	g at Ground + 03 uppe	er floors only)		
N-ESP				New Case (School running at Ground + 03 upper floors only) F.6/DFS/MS/School/2012/1336 dated 13.04.2012 Previous NOC				
6.	Fire CoCat 11		Ground	Ground floor only				
/ Date of increase:				NBC Part-IV 19.06.2025				
8.	Name of	Inspecting Officer	Sh. Ajay Kumar Sharma (ADO Robini)					
9.	Name and	d designation of officers		hul Solanki	ADO Romini)			
	From the	building side	IVII. IX	mui Solaliki	±			
10). Year of C	Construction	2005 &	2 2018		31 II II		
	. Applican	t's letter No.	Online	e-mail dated 29.05.	2025			
S.	Minimu	n Standards on fire prev	ention	NBC Part-IV	Provided at site	Remarks		
No	and fire	safety U/R 33		Requirement	(40	MR/NMR		
1.	Access to	building	¥					
	• R	oad width		Accessible	Accessible	MR		
	• G	ate width		Accessible	Directly accessible	MR		
	• W	dth of internal road		-NA-	-NA-	-NA-		
2.	Number,	Width, Type & Arrange	ement of	Exits				
		er of staircases						
	•	Upper Floors		02nos.	02nos.	MR		
		Basements		-NA-	-NA-	-NA-		
		th of staircases						
	•	Upper Floor		1.5m	1.5m & 2.05m	MR		
	-	Basements		-NA-	-NA-	-NA-		
				1771	-INA-	-IVA-		
	c. Prote	Fire check door		-ΝΛ-	-ΝΛ-	NA.		
		Pressurization		-NA-	-NA-	-NA-		
	1 N C	continuous staircases to	torrogo	Required	Provided	-NA-		
			terrace	1.5m		MR		
	ACID ELL MODERN STEEL	of Corridor			2m	MR		
	f. Door S	The state of the s	100	Required	Provided	MR		
•		nentation		NTA				
		e check door		-NA-	-NA-	-NA-		
	E-7	aling of electrical shafts	10.5	-NA-	-NA-	-NA-		
	c) Fire Rating of shaft door			-NA-	-NA-	-NA-		
	,	d) Water Curtain		-NA-	-NA-	-NA-		
[e) Fire Dampers		-NA-	-NA-	-NA-			
	Smoke Management System							
	a) Basements		-NA-	-NA-	-NA-			
		per floors	5.2	12 a/c per hour	Natural ventilated	MR		
7	Fire Extinguishers							
	a) Total numbers			15nos.	Provided	MR		
	b) Types			ABC/CO2	ABC/CO2	MR		
	c) IS	c) IS marking		ISI marked	Yes	MR		
+	First-Aid	Hose Reels				n-Tita		
-+	a) Tot	al numbers on each floor		01nos.	Provided	MR		
				N.,				

ayes

^-
10
0

				3		
	b) Length of hose reel hose	30mm	Provided			
	c) Nozzle diameter	5m	Provided	MR MR		
7.	Automatic fire detection and alarming system					
	a) Type of detectors	-NA-	-NA-	-NA-		
	b) Location of Main Panel	-NA-	-NA-	-NA-		
	c) Location of Repeater Panel	-NA-	-NA-	-NA-		
	d) Alternate source of power	-NA-	-NA-	-NA-		
	e) Hooters' Location	-NA-	-NA-	-NA-		
3.	MOEFA	-NA-	-NA-	-NA-		
٠.	Public Address System	-NA-	-NA-	-NA-		
10.	. Automatic Sprinkler System					
1		-NA-	-NA-	-NA-		
	b) Ground & Upper Floors	-NA-	-NA-	-NA-		
11	c) Sprinkler above false ceiling	-NA-	-NA-	-NA-		
11.				11121		
	a) Size of riser/down-comer	-NA-	-NA-	-NA-		
	b) Number of hydrants per floor	-NA-	-NA-	-NA-		
12	c) Hose Box	-NA-	-NA-	-NA-		
2.			1.55	-11//1-		
	a) Total number of hydrants	-NA-	-NA-	-NA-		
	b) Hose Box	-NA-	-NA-	-NA-		
13.				-IVA-		
	Ground Level					
	Discharge of main Pump	-NA-	-NA-	-NA-		
	➤ Head of Main pump	-NA-	-NA-	-NA-		
	Number of main pumps	-NA-	-NA-	-NA-		
	Jockey Pump out put	-NA-	-NA-	-NA-		
	> Jockey pump head	-NA-	-NA-	-NA-		
	Standby Pump out put	NA-	-NA-			
	Standby Pump Head	-NA-	-NA-	-NA-		
	> Auto Starting/Manual Stopping	-NA-	-NA-			
	> Pump House Access	-NA-	A SUNCE	-NA-		
	Terrace level -NA-					
	Discharge of pump	450lpm	4501			
	➤ Head of the pump	40m	450lpm	MR		
	➤ Power Supply	Required	40m	MR		
	➤ Auto Starting of pump	Required	Provided	MR		
14.	Captive Water Storage for fire fighting	Required	Provided	MR		
	Underground tank capacity	NT.				
		-NA-	-NA-	-NA-		
	> Draw-off connection	-NA-	-NA-	-NA-		
	Fire service inlet	-NA-	-NA-	-NA-		
	Access to tank	-NA-	-NA-	-NA-		
	Overhead Tank capacity	10,000ltr	1 202			
5.	Exit Signage.		10,000ltr	MR MR		
6.	Provision of Lifts. Required Provided					
	a) Pressurization of Life St. 6					
		-NA-	-NA-	-NA-		
	b) Pressurization of Lift lobby	-NA-	-NA-	-NA-		
	c) Communication In lift Car	-NA-	-NA-	-NA-		
	d) Fireman's Grounding Switch	-NA-	-NA-	-NA-		

CM

MR.		MA				
1)	e) Lift Signage	NA .				
17.	Standby power supply	-NA-	-NA-	-NA-		
18.	Refuge Area.	-NA-	-NA-	-NA-		
	a) Total Area					
	b) Location	-NA-	-NA-	-NA-		
19.	Fire Control Room	-NA-	-NA-	-NA-		
	a) Detector System Panel	Detector System Panel				
	b) Flow Switch Panel	-NA-	-NA-	-NA-		
	c) PA System Panel	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
	- Just odekup	-NA-	-NA-	-NA-		
20	e) Building Floor Plans	-NA-	-NA-	-NA-		
20.	Special Fire Protection System for Protection of special Risks, if any:	-NA-	-NA-	-NA-		

Accordingly, the fire protection systems provided in the building were tested/

randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 392 dated 14.05.2025, under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name Ajay Kumar Sharma Designation ADO(Rohini)

D.B Mukherjee DO (NW)