0/18



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2025/SZ/ 204

Dated: 04/03/2025

FIRE SAFETY CERTIFICATE

Certified that the Raja Ram Mohan Ray Sarvodaya Kanya Vidyalaya (School ID 1923041) located at Hauz Rani, New Delhi, 110017 comprised of Ground plus three upper floors owned/occupied by Directorate of Education Govt. of NCT of Delhi was Safety Certificate by this department vide letter No. F6/DFS/MS/School/2022/SZ/195 dated 18/02/2022. The said premises was reinspected by officer concerned of this department on 25/02/2025 in presence of Ms. Ruchkia Gupta (Incharge) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational Building Group - B" with effect from 04/03/ 2025 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner, cancelled under Rule 40 and subject to compliance of the conditions under rule 38 1/6f Delhi Fire Service Rules 2010.

Issued on 04/03 2025 at New Delhi by

PDIRECTOR II FIRE SERVICE

Copy to: -

1. The Principal, Raja Ram Mohan Rai, Sarvodaya Kanya Vidyaraya, located at Hauz

2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-54


Conditions for the validity of Fire Safety Certificate

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of firefighting system.

- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."






	INSPECTION	N REPORT	To position in the			
1	Name & Address of the Building	Sarvodaya Kanya Vidyalaya, (RRMR) Hauz Rani, New Delhi-110017 (1923041)				
2	Type of Occupancy	Educational, Group-B (School)				
3	Building Comprised of	Ground plus three upper floor				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/School/2022/SZ/195 dated 18/02/202				
6	Fire Safety Directives Letter No	Nil Nil 18/19/19/19/19/19/19/19/19/19/19/19/19/19/				
7	Date of Inspection	25-02-2025				
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)				
9	Name & Designation of Officers from the building side	Ms. Ruchika Gupta (Incharge)				
10	Year of construction	2018-19				
11	Applicant letter No.	RRMR/SKV/HR/2025/949 dated 14/02/2025				
S. No.	standards on Fire Freyention	1 PD1 2016 TO 11				
1	and Fire Safety U/R 33	Requirements	Frovided at Site	Remarks		
-	Access to Building.	- Gill Carts	A SEPTEMBER OF THE	MR/NMR		
April 1	Road width	Accessible	9 mtr	100		
	Gate width	Required	4.5m	MR		
2	Width of internal road	NIA	-NA-	MR		
	Number, width, type & arrangement of ex	its.	-NA-	-NA-		
	Trumber of Staircase	HATTER TO THE				
-22.9	> Upper floors.	04 Nos	Provided) m		
	Basement floor.	-NA-		MR		
	b) Width of Staircase	-INA-U (III)	and -NA-	-NA-		
(1-4)	➤ Upper floors	Lagger d	Tel Dari I in School I in I			
	➤ Basement floor	1.5m each	1.50 mtr each	MR		
	c) Protection of exits	-NA-	-NA-	-NA-		
		9974	Semiliary &			
	➢ Fire check door➢ Pressurization	-NA-	-NA-	-NA-		
	La Control of the Con	-NA-	-NA-	-NA-		
3332	d) No. of continuous staircase to terrace	Required	02 provided	MR		
	e) Width of corridor f) Door size	Required	1.50 m	MR		
3		1.2 m	Provided	MR		
	Compartmentation.			IVIIC		
	Fire check door.	-NA-	-NA-	-NA-		
	Sealing of electrical shafts.	-NA-	-NA-	-NA-		
	Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	• Fire dampers.	-NA-	-NA-	-NA-		
4	Smoke Management system.		Police Laster V			
	Basement	30 ACPH	-NA-	-NA-		
	Upper floors	12 ACPH	-NA-	-NA-		
5	Fire Extinguishers.	15 WOR 18	S 15 17 17 19 30 1 2			
	Total numbers	30 Nos	42 Nos	MR		
	Types	ABC / CO2	ABC & CO2	MR		
	ISI Marking	ISI marked	Provided	MR		
6	First Aid Hose Reels.		Mark Land	MIK		
0	Total numbers on each floor.	04 Nos	Provided	MR		
	Length of hose-reel hose.	30m	Provided			
		5mm	Provided	MR		
- 1-1-	Nozzle Diameter		Provided	MR		
7	Automatic fire detection & alarming system.	NY.	A 100 mm. 1.			
	Type of detectors	-NA-	-NA-	-NA-		



	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	NA-
8	MOEFA	-NA-	-NA-	-NA-
9	Public Address System	-NA-	-NA-	-NA-
10	Automatic Sprinkler System			
	Basement	-NA-	-NA-	-NA-
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
			• • • • • • • • • • • • • • • • • • • •	
11	Internal Hydrants.	-NA-	Provided	-NA-
	Size of Riser/Down-comer	20000000	04 Nos	-NA-
	Number of Hydrant per floor	-NA-	05 345 M 25 E	
	Hose box.	-NA-	04 Nos	-NA-
12	Yard Hydrants.		City Contraction	
==	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.		TO 1 101-7 19	
	Ground Level	12.01.12	APA TE AIDA	
	Discharge of main pump.	-NA-	-NA-	-NA-
	> Head of main pump.	-NA-	-NA-	-NA-
	> Number of main pumps.	-NA-	-NA-	-NA-
	> Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	➤ Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			1 1 5 7
	➤ Discharge of pump.	450 LPM x 2	Provided	MR
	➤ Head of pump.	40 m x 2	Provided	MR
	Power supply.	Required	Provided	MR
	➤ Auto starting of pump.	Required	Provided	MR
		Required		
14	Captive water storage for fire fighting.		77 200 1:	-NA-
	 Underground tank capacity. 	-NA-	55,000 ltr	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	> Fire Service Inlet.	-NA-	-NA-	
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 Ltr	Provided	MR
5	Exit Signage.	Required	Provided	IVIK
	Provision of Lifts.		Acres 14	1
6	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
12		-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
7	Standby Power Supply	10/4 / EL III	en again a Malair - M	
8	Refuge Area	-NA-	-NA-	-NA-
	Total area	- THE COLUMN TO SERVICE STATE OF THE SERVICE	-NA-	-NA-
	• Location	-NA-	- 11/1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	
9	Fire Control Room.	CONSTRUCTOR CO	TELEVISION AND THE	-NA-
7	Detector system panel.	-NA-	-NA-	I PINA



The fire protection system provided in the building were randomly checked and found functional at

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire measures as required under the rules, the FSC issued F6/DFS/MS/School/2022/SZ/195 dated 18/02/2022, renewal under rule 37 of the Delhi Fire Service vide letter no rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP)

-NA-

-NA-

-NA-

-NA-

-NA-

Approved, F-1- better in portup or your synature of