

cg

ESTATE PARTY OF THE

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F.6/DFS/MS/School/2025/NDZ/ 1134

Dated: 16/09/2025

## FIRE SAFETY CERTIFICATE

Certified that Raman Deep Vidya Bhawan at Gali No. 08, Bhola Nath Nagar, Shahdara, Delhi-110032, comprised of Ground plus two upper floors but school is running on ground plus one upper floor, owned/occupied Raman Deep Vidya Bhawan was issued FSC vide letter No. F.6/MS/DFS/2006/1689 dated 21/07/2006. The premises was re-inspected by the officers concerned of this department on dated 28/08/2025 in the presence of Sh. S. K. Bhatia, Manager and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with Circular No. 262-362 dated 17/01/2005 issued by the Director of Education and that the building/premises is fit for occupancy class 'Educational (Group-B)' with effect from ...16.09.25 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed below.

Issued on 16 09 2025 at New Delhi by

(VIRENDRA SINGH)

OC CHIEF FIRE OFFICER

To,

- The Principal, Raman Deep Vidya Bhawan at Gali No. 08, Bhola Nath Nagar, Shahdara, Delhi-110032
- 2. The Director of Education, MCD, 15<sup>th</sup> Floor, E- Block, Dr. S.P. Mukherjee *Civic Center*, JLN Marg, New Delhi-110002

## Conditions for the validity of Fire Safety Certificate

- 1. FSC is valid for ground plus one upper floor only. 2<sup>nd</sup> floor which is sealed may not be used for any purpose failing which FSC should be treaded null and void.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 6. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

NIS

1. Name & address of the building

: Raman Deep Vidya Bhawan

Gali No. 08, Bhola Nath Nagar, Shahdara, Delhi-32,

2. Building is comprised of

:Ground plus two upper floor only but

School is running ground and first floor only

(2<sup>nd</sup> floor is sealed)

3. Type of Occupancy

:Educational

4. Type of Case

:Renewal

5. Details of Previous NOC letter

:F.6/MS/DFS/2006/1689 dated 21/07/2006

6. Fire Safety directive letter No.

: Circular 262-362 dated 17/01/2005 issued by DoE

7. Date of Inspection

: 03/09/2025

8. Name of the Inspecting officers

:ADO (Shd.) Deepak Kumar

9. Name and designation of Officer

from the building side

:Sh. S. K. Bhatia,

10. Year of Construction

:2000

11. Applicant's letter No

:Kwatra.shubham@gmail.com Dated 02/09/2025

Sr.	Minimum Standards on fire	DoE Circular	Provided at Site	Remarks MR/NMR				
No.	prevention and fire safety U/R33	17/01/2005						
		Requirement						
01	Access to building							
	Road width	06 mtr.	03.10 mtr. & 2.10 mtr	MR				
	Gate width			(old case)				
	<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A				
		N/A	N/A	N/A				
02	Number, Width, Type and Arrangement of Exits							
	a. Number of Staircases							
	Upper Floor	01 nos.	01 nos.	MR				
	<ul> <li>Basement</li> </ul>	N/A	N/A	N/A				
	B. Width of Staircases							
	Upper Floor	1.50 mtr	0.90 mtr & 0.75 mtr	MR				
	Basement	N/A	N/A	N/A				
	c. Protection of exits							
	Fire check door	N/A	N/A	N/A				
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A				
	d. No. of continuous staircases	01 no.	01 no.	MR				
	toterrace							
	e. Width of Corridor	1.50 mtr	1.50 mtr	MR				
	f. Door Size	01 mtr.	01 mtr.	MR				
03	Compartmentation.							
	Fire check door	N/A	N/A	N/A				
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A				
	<ul> <li>Fire rating of shaft door</li> </ul>	N/A	N/A	N/A				
	Water curtain	N/A	N/A	N/A				
	<ul> <li>Fire Dampers</li> </ul>	N/A	N/A	N/A				
04	Smoke Management System.							
	Basement	N/A	N/A	N/A				
	Upper floor	N/A	N/A	N/A				

05.	Fire Extinguishers						
	Total numbers	04 nos.	05 nos.	MR			
	Types	ABC /CO <sub>2</sub>	ABC /CO <sub>2</sub>	MR			
	IS marking	ISI marked	ISI marked				
06	First-aid-Hose Reels. ISI marked ISI marked MR						
	Total numbers on each floor 01 no. 01 no.						
	<ul> <li>Length of hose reel hose</li> </ul>	30 mtr	01 no. 30 mtr	MR			
	Nozzle diameter	05 mm		MR			
07	Automatic fire detection and alarming system.  05 mm 05 mm MR						
	Type of detectors	N/A	N1/A	T			
	<ul> <li>Location of main panel</li> </ul>		N/A	N/A			
	Location of repeater panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooter's location	N/A	N/A	N/A			
08	MOEFA	N/A	N/A	N/A			
09	Public address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.	N/A	N/A	N/A			
	Dasement	N/A	N/A	N/A			
	<ul> <li>upper floor</li> </ul>	N/A	N/A	N/A			
11	sprinkler above false ceiling	N/A	N/A				
1.1	Internal Hydrants						
	<ul> <li>size of riser/down-comer</li> </ul>	N/A	N/A	NI/A			
	<ul> <li>Number of hydrants per floor</li> </ul>	N/A	N/A	N/A N/A			
12	Hose Box  Yard Huden to	N/A	N/A	1,045,01 5			
12	Yard Hydrants.						
	<ul> <li>Total number of hydrants</li> </ul>	N/A	NI/A	T			
40	<ul> <li>Hose Box</li> </ul>	N/A	N/A	N/A			
13	Pumping Arrangements.	IN/A	N/A	N/A			
	Ground Level	N/A	N	1			
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main Pump		N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby nump out must	N/A	N/A	N/A			
	Otdiluby hilms List	N/A	N/A	N/A			
	Auto Starting /Manual	N/A	N/A	N/A			
	otoppii id	N/A	N/A	N/A			
	Pump House Access     Terrace Level	N/A					
	> Discharge of	IV/A	N/A	N/A			
	Discharge of pump  Head of the Pump	220 1					
	, OVER SIIDEL	220 lpm	220 lpm	MR			
	<ul> <li>Auto Starting of pump</li> </ul>	40 mtr	40 mtr	MR			
	starting of pump	Required	Provided	MR			
		Required	Provided	MR			



14	Captive Water Storage for Fire Fighting.	NVA T					
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	➤ Fire service inlet	N/A	N/A	N/A			
	> Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	N/A	N/A	N/A			
15	Exit Signage.	2,500 ltr	2,500 ltr	MR			
16	Provision of Lifts.	Required	Provided	MR			
	Pressurization of Lift Shaft     N/A     N/A     N/A     N/A						
		IN/A	N/A	N/A			
	- 1 TOO BUT LITT TO DO DY	N/A	N/A	N/A			
	+ Communication in lift car	N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	N/A			
17	Lift Signage     Standburg	N/A	N/A	N/A			
18	Standby power supply	N/A	N/A	N/A			
10	Refuge Area.						
	Total area	N/A	N/A	N/A			
10	• Location	N/A	N/A	N/A			
19	Fire Control Room						
_	Detector system panel	N/A	N/A	N/A			
	<ul> <li>Flow switch panel</li> </ul>	N/A	N/A	N/A			
	<ul> <li>PA system panel</li> </ul>	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
20	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A			

**Note:-** The school management has been submitted undertaking that the 2<sup>nd</sup> floor is sealed and not being used for school and any purpose.

The fire protection system provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rule. The FSC issued vide letter no. F.6/MS/DFS/2006/1689 dated 21/07/2006 renewal under rule 35 of the Delhi Fire Service Rules, 2010 is recommended.

19/2015

Signature of the Inspecting Officer

Name

:-Deepak Kumar

Designation

:-ADO (Shd.)

CEOL

8 191 Do 25

Principal Director

Go to Gen

ADO Charh,

10/9/2000

Cof of

ज्यकि। १३

P.T.O