

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

**NEW DELHI- 110 001** 

No. F.6/DFS/MS/GH/2025/NDZ/ 509

Dated: 22/09/2015

## FIRE SAFETY CERTIFICATE

Certified that the M/s Rhea Lodge Guest House located at 4518, Shahid Bhagat Singh Street, Gali No. 06, Pahar Ganj, New Delhi, comprised of Ground floor (reception +02 guest rooms), 1st floor (03 guest rooms), 2<sup>nd</sup> floor (04 guest rooms) & 3<sup>rd</sup> floor (01 guest room + 02 store rooms), Total 10 guest rooms only upto 3<sup>rd</sup> floor (4<sup>th</sup> floor sealed by the owner) owned/occupied M/s Rhea Lodge letter department this granted **FSC** by earlier House was F.6/DFS/MS/GH/NDZ/2022/292 dated 20/06/22. The premises was re-inspected by the officer concerned of this department on 09/09/2025 in the presence of Sh. Raj Kumar Mehra, Owner and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class "Residential "Sub- Division- A-1, Ground floor (reception +02 guest rooms) 1st floor (03 guest rooms), 2nd floor (04 guest rooms) & 3rd floor (01 guest room + 02 store rooms), Total 10 guest roomsonly up to third floor with effect from 29 09 22 up to valid 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

22 09 2025 ....at New Delhi by

To,

1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy a detailed above.

2. Sh. Raj Kumar Mehra, M/s Rhea Lodge Guest House located at 4518, Shahid Bhagat Singh Street, Gali No. 06, Pahar Ganj, New Delhi

MCD online ID 2025082012698

## Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

:M/s Rhea Lodge Guest House,

Located at 4518, Shaid Bhagat Singh Stree, Gali No. 06, Pahar Ganj, New Delhi

2. Type of Occupancy

:Residential, Sub Division-A-1 (Guest House)

3. Building is comprised of

: Ground + 04 upper floors but guest house is running

ground to 3<sup>rd</sup> floor only (4<sup>th</sup> floor sealed by the owner)

Ground floor (reception +02 guest rooms) 1st floor (03 guest rooms), 2nd floor (04 guest rooms)

& 3<sup>rd</sup> floor (01 guest room + 02 store rooms), Total 10 guest rooms

4. Type of Case

BC

:Renewal

5. Details of Previous NOC letter

: F.6/DFS/MS/GH/NDZ/2022/292 dated 20/06/22

6. Fire Safety directive letter No

: N/A

7. Date of Inspection

: 09/09/2025

8. Name of the Inspecting officers

:ADO (Shd.) Deepak Kumar

9. Name and designation of Officer

from the building side

: Sh. Raj Kumar Mehra, Owner

10. Year of Construction

: 2000

11. Applicant's letter No

:2025082012698 dated 20/08/2025

Sr. No.	Minimum Standards on fire prevention and fire safety U/R33	Requirement/ Existing fire safety arrangement	Provided at Site	Remarks MR/NMR			
01	Access to building.						
23		N/A	2.30 mtr.	MR			
	Road width	N/A	N/A	N/A			
	Gate width	N/A	N/A	N/A			
02	Width of internal road     Number, Width, Type and Arrange						
02			A				
-	a. Number of Staircases	01 no.	01 no.	MR			
ě.	Upper Floor	N/A	N/A	N/A			
	Basement     Advisored	1077					
	B. Width of Staircases	1.50 mtr	1.50 mtr & 1.55 mtr	MR			
Ą.	Upper Floor     Basement	N/A	N/A	N/A			
	Basement						
	c. Protection of exits	N/A	N/A	N/A			
	Fire check door	N/A N/A	N/A	N/A			
	<ul> <li>Pressurization</li> </ul>	IN/A					
	d. No. of continuous staircases	01 no.	01 nos.	MR			
	to terrace e. Width of Corridor	N/A	N/A	N/A			
	e. Width of Comaci	01 no.	01 nos.	MR			
	f. Door Size	o i no.	*				
03	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
100	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
t	Water curtain	N/A	N/A	N/A			
91 S	Fire Dampers	N/A	N/A	N/A			
)4	Smoke Management System.						
		12 a/c per hour	N/A	N/A			
	Basement	12 a/c per hour	Natural/Exhaust fan	MR			
-	Upper floor  Fire Fishing wighers	in are per ilear	The second secon	macrata.			
)5.	Fire Extinguishers.  OR nos						
Z .	<ul> <li>Total numbers</li> </ul>	08 nos.	08 nos.	MR			
w.	• types	ABC/CO <sub>2</sub>	ABC/CO <sub>2</sub> ,	MR			
	IS marking	Required	Provided	IVIPS			

06	First-aid-Hose Reels.	171					
	Total numbers on each floor	04.14	V				
1	Length of hose reel hose	01 No. 30 mtr.	01 No	MR			
1	Nozzle diameter	05 mm	30 mtr.	MR			
07	Automatic fire detection and alarming sys		05 mm	MR			
	Type of detectors CO						
	Location of main panel	Required	Provided	MR			
	Location of main panel     Location of repeater panel	Ground floor N/A	Provided	MR			
	Alternate source of power	Required	N/A	N/A			
	Hooter's location	0.17	Provided	MF			
08	MOEFA	Each floor	Provided	MF			
09	Public address System.	N/A N/A	N/A	N/A			
10	Automatic Sprinkler System.	IN/A	N/A	N/A			
	Basement	N/A	N/A	N/A			
	upper floor	N/A	9 880 14				
	sprinkler above false ceiling		N/A	N/A			
11	Internal Hydrants	N/A	N/A	N/A			
	size of riser/down-comer	N/A	NI/A	1 110			
	Number of hydrants per floor	N/A N/A	N/A	N/A			
	Hose Box		N/A	N/A			
2	Yard Hydrants.	N/A	N/A	N/A			
$\dashv$	Total number of hydrants	N/A 1		1			
_	Total number of hydrants     Hose Box	N/A	N/A	N/A			
_	Pumping Arrangements.	N/A	N/A	N/A			
-	Ground Level     Discharge of main Pump	N/A	N/A	N/A			
-		N/A	N/A	N/A			
	Treat or main rains	N/A	N/A	N/A			
-	Training of them parties	N/A	N/A	N/A			
-+		N/A	N/A	N/A			
-	Jockey pump head     Standby pump out put	N/A	N/A	N/A			
$\dashv$	r ctarraby parmy out put	N/A	N/A	N/A			
-		N/A	N/A	N/A			
-		N/A	N/A	N/A			
+	<ul> <li>Pump House Access</li> <li>Terrace Level</li> </ul>	N/A	N/A	N/A			
	> Discharge of pump	225 Lpm	225	MF			
	> Head of the Pump	30mtr.	30mtr.	MF			
	> Power supply	Required	Provided	MF			
	> Auto Starting of pump	Required	Provided	MF			
4	Captive Water Storage for Fire Fighting.						
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	➢ Fire service inlet	N/A	N/A	N/A			
	> Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	2,500 ltrs.	2,500 ltrs.	MR			
5	Exit Signage.	Required	Provided	MR			
6	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	14//			

.6.

17	Standby power supply	Required	Provided >	MR		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
767	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	N/A	N/A	N/A		
-	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection systems for protection of special Risks, if any:	N/A		N/A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter No. F.6/DFS/MS/GH/NDZ/2022/292 dated 20/06/22 renewal under rule 35 of the Delhi Fire Service Rule, 2010 is recommended.

Signature of the Inspecting Officer
Name : Deepak Kumar

Designation : ADO (Shd)

12/7/25 Dycko (1702) C.F.O

212 Jahrs

Binibol Dint

Cfo

5 Jan

2

181 91 2000

Ado (skab)