



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F.6/DFS/MS/School/2025/NDZ/ 1175

Dated: 23 09 2025

FIRE SAFETY CERTIFICATE

Certified that the Rosary Public School located at B-5 South Anarkali Delhi-110051, comprised of ground plus two upper floors only owned/occupied Rosary Public School was issued FSC vide letter No. F.6/MS/DFS/06/1523 dated 07/07/2006. The premises was re-inspected by the officer concerned of this department on dated 28/08/2025 in the presence of Mr. Shashi Mohan Agnihotri and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with Circular No. Circular 262-362 dated 17/01/2005 issued by the Director of Education and observed that the building/premises is fit for occupancy class 'Educational (Group-B)' with effect from 23.09.25. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed below.

Issued on 23/09/2025 at New Delhi by

To:-

The Manager,

Rosary Public School at B-5 South Anarkali Delhi-110051.

Copy to:-

The Dy. Director of Education, MCD

Udyog Sadan, Plot No. 419, FIE, Patparganj Ind. Area, Delhi- 110092

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipment's and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.

6. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

NIT

1. Name & address of the building

: Rosary Public School

B-5 South Anarkali, Delhi-51,

2. Building is comprised of

:Ground plus two upper floors only

3. Type of Occupancy

:Educational

4. Type of Case

:Renewal

Details of Previous NOC letter

:F.6/MS/DFS/06/1523 dated 07/07/2006

Fire Safety directive letter No.

: Circular 262-362 dated 17/01/2005 issued by DoE

7. Date of Inspection

: 28/08/2025

8. Name of the Inspecting officers

:ADO (Shd.) Deepak Kumar

9. Name and designation of Officer

from the building side

: Mr. Shashi Mohan Agnihotri, Manager

10. Year of Construction

:1995

11. Applicant's letter no. / Email

:mohinisrivastva456@gmail.com dt 11/08/2025

Sr.	Minimum Standards on fire prevention and fire safety U/R33	Circular Requirement	Provided at Site	Remarks MR/NMR				
No.								
01	Access to building	06 m	MR					
	Road width	06 m	N/A	N/A				
	Gate width	N/A	N/A	N/A				
	hear laternal road	N/A	IN/A					
	Width of Internal Toad Number, Width, Type and Arrangement of Exits							
02								
	Number of Staircases Upper Floor	01 no.	02 nos.	MR				
	 Basement 							
	B. Width of Staircases	4 50 mtr	0.75 m &	MR				
	Upper Floor	1.50 mtr	0.75 m (iron)	(old case)				
		N/A	N/A	N/A				
	Basement	19/75		21/2				
	c. Protection of exits	N/A	N/A	N/A				
	 Fire check door Pressurization d. No. of continuous staircases to terrace e. Width of Corridor 	N/A	N/A	N/A				
		01 m	01 m	MR				
		01111	1 50	MR				
		1.50 m	1.50 m					
		01 m	01 m	MR				
	f. Door Size	01111						
00	Compartmentation. N/A							
03	Fire check door Sealing of electrical shafts Fire rating of shaft door	N/A	N/A	N/A N/A				
		N/A	N/A	N/A				
		N/A	N/A	N/A				
		N/A	N/A	N/A				
	Water curtain	N/A	N/A					
	- Fire Dampers							
04	Smoke Management System.			N/A				
	Basement	N/A	N/A	N/A				
	Upper floor	N/A						

05.	Fire Extinguishers						
	Total numbers 06 nos. 06 nos.						
	Types	ABC /CO ₂	06 nos.	MF			
-	IS marking		ABC /CO ₂	MF			
06	First-aid-Hose Reels.	ISI marked	ISI marked	MR			
	Total numbers on each floor						
	Length of hose reel hose	01 no.	01 no.	MR			
	Nozzle diameter	30 mtr	30 mtr	MR			
07	Automatic fire detection and alarming sy	05 mm	05 mm	MR			
	Type of the Type o						
	Type of detectors	N/A					
	Location of main panel	N/A	N/A	N/A			
	Location of repeater panel Alternate	N/A	N/A	N/A			
	rate flate source of power	N/A	N/A	N/A			
80	Hooter's location MOEFA	N/A	N/A	N/A			
09	Public address System.	N/A N/A	N/A	N/A			
10	Automatic Sprinkler System.	N/A	N/A	N/A			
		IVA	N/A	N/A			
	Basement	NI/A					
	 upper floor 	N/A	N/A	N/A			
11	sprinkler above fals	N/A	N/A	N/A			
11	Internal Hydrants	N/A	N/A	N/A			
	Size of riser/down						
	Number of hydrants per floor	100 mm	100 mm	MR			
	Hose Box	01 no.	01 no.	MR			
12	Yard Hydrants.	01 no.	01 no.				
	y and the MR						
	Total number of hydrants Hose Box	N/A	NIA				
13	Pumping Arran	N/A	N/A	N/A			
	Pumping Arrangements.		N/A	N/A			
	Ground Level	N/A	N./-				
	Discharge of main Pump	N/A	N/A	N/A			
	nead of Main Pump	N/A	N/A N/A	N/A			
	missi of main pumps	N/A	N/A N/A	N/A			
	parip out but	N/A	N/A	N/A			
	pump nead	N/A	N/A	N/A N/A			
	Standby pump out putStandby pump Head	N/A	N/A	N/A			
	> Auto Starting /Manual	N/A	N/A	N/A			
	stopping	N/A	N/A	N/A			
	Pump House Access	N/A	NI/A				
	Terrace Level	14/0	N/A	N/A			
	Discharge of pump	450 lpm	450 lpm	MR			
	➤ Head of the Pump	40 mtr	40 mtr				
	Power supply	Required	Provided	MR			
	Auto Starting of nume	Required	i iovided	MR			



14	Captive Water Storage for Fire Fighting.	N/A	N/A	N/A			
	Underground tank capacity	N/A	N/A	N/A			
-	> Draw-off connection	N/A	N/A	N/A			
	> Fire service inlet	N/A	N/A	N/A			
	> Access to tank	N/A	N/A	N/A			
	Overhead Tank capacity	5,000 ltr	5,000 ltr	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
-	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply	N/A	N/A	N/A			
18	Refuge Area.						
	Total area	N/A	N/A	N/A			
	Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector system panel	N/A	N/A	N/A			
	Flow switch panel	N/A	N/A	N/A			
	PA system panel	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. The earlier communicated shortcomings issued vide letter no. F.6/DFS/MS/School/2025/NDZ/298 dated 28/04/2025.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the rule. The FSC issued vide letter F.6/MS/DFS/06/1523 dated 07/07/2006 renewal under rule 35 of the Delhi Fire Service Rule, 2010 is recommended.

> 03/09/2025 Signature of the Inspecting Officer

Name

:-Deepak Kumar

Designation

:-ADO (Shd.)

ADO (Shah)