Dated:



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

11/09/2025

No. F6/DFS/MS/2025/WZ/College/ 31

FIRE SAFETY CERTIFICATE

Certified that the Rukmani Devi Institute of Advance Studies, 2-A & 2-B, A-Block, Madhuban, Chowk, Rohini, Delhi-110085, comprised of Basement + Ground + 03 upper floors has already been issued FSC by this department vide letter No. F.6/DFS/MS/2022/WZ/College/17 dated 18.10.2022. The premises was re-inspected by the officer concerned of this department on 25.08.2025 in the presence of Dr. Raman Garg (Director) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class "Group B Educational" with effect from 11092025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 11 09 2025 at New Delhi by

(Virendra Singh) **Chief Fire Officer Delhi Fire Service**

ole

Copy to :-

1. The Director, Rukmani Devi Institute of Advance Studies, 2-A & 2-B, A-Block, Madhuban, Chowk, Rohini, Delhi-110085.

Conditions for the validity of fire safety certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized construction.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first

schedule of Delhi Fire Service Rules 2010. The form is available on

8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Fire+Safety+Acts+and+Rule s/ http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms

INSPECTION REPORT

Name & address of the building: Rukmini Devi Institute of Advance Studies, 2A & 2B, A-Block,

Madhuban Chowk, Block-A, Outer Ring Road, Phase-I, Delhi-85.

: Educational (B+G+3 upper floor) Only for A-Block 2. Type of Occupancy

: Renewal 3. Type of Case

: F.6/DFS/MS/2022/WZ/College/17 dated 18.10.2022 4. Details of Previous NOC

5. Fire Safety directives letter No : F.6/DFS/MS/BP/99/2883 dated 11.03.1999

: 25.08.2025 6. Date of inspection

: A.K.Sharma ADO(Rohini) 7. Name of Inspecting Officer

8. Name and designation of officers

: Dr. Raman Garg (Director) From the building side

9. Year of Construction

7 dated 17 07 2025

10. S. No.	Minimum Standards on fire prevention		Rule 35(6)	Provided at site	Remarks MR/NMR	
	and fire safety U/R 33					
1.	Access to building		00	18m	MR	
.•	•	Road width	09m	5.0m	MR	
		Gate width	4.5m	-NA-	-NA-	
		Width of internal road	-NA-	114.		
N.	Numb	er, Width, Type & Arrangement of	Exits			
2	Number of staircases			03nos.	MR	
	a. Ivu	Upper Floors	02nos.	Provided	MR	
			01 SC & 01 ramp	Tioviace		
	•	Basements	- UT Tamp) m	
	b. W10	th of staircases	1.5m (each)	1.5m (each)	MR	
	•	Upper Floor	1.5m & 01 ramp	1.6m & ramp 1.5m	MR	
	•	Basements				
		tection of exits	Required	Provided(only basement)	MR	
	Fire	check door	Required	Provided	MR	
	•	Pressurization	01nos.	Provided		
	d. No	o. of continuous staircases to terrace	-NA-	-NA-	-NA-	
	e. W	idth of Corridor	1.0m	1.0m	MR	
	100	oor Size	1.0111			
3.	Compartmentation					
	•	Fire check door	Required	8 5	MR MR	
		Sealing of electrical shafts	Required	Provided		
		Fire Rating of shaft door	Required	Provided	MR	
		Water Curtain	-NA-	-NA-	-NA-	
		Fire Dampers	-NA-	-NA-	-NA-	
	Smok	e Management System				
4.	Sillon	Basements	30 a/c per hour	Exhaust fan	MR	
	+ :	Upper floors	12 a/c per hour	Natural ventilated	MR	
5.	Fire	Extinguishers Total numbers	24nos.	25nos.	MR	
		Types	ABC/CO2	ABC-25	MR	
		IS marking	ISI marked	Yes	MR	
6.	First-Aid Hose Reels					
	•	Total numbers on each floor	01nos.	Provided	MD	
	•	Length of hose reel hose	30mm	Provided	MR	
		Nozzle diameter	5m	Provided	MR MR	
7.	Automatic fire detection and alarming system					
	•	Type of detectors	-NA-	-NA-	The second second	
	•	Location of Main Panel	-NA-	3-00-1000	-NA-	
	•	Location of Repeater Panel	-NA-	-NA-	-NA-	
	•	Alternate source of power	-NA-	-NA-	-NA-	
		Q., c		-NA-	-NA-	

		NTA	274	A Part				
	Hooters' Location	-NA-	-NA-	-NA				
8.	MOEFA	Required	Provided	MR				
9.	Public Address System	Required	Provided	MR				
10.	Automatic Sprinkler System	Required	D 111	To Care				
	Basement	-NA-	Provided	MR				
	Ground & Upper Floors	-NA-	-NA-	-NA-				
	Sprinkler above false ceiling	-IVA-	-NA-	-NA-				
11.	Internal Hydrants	Required	D 11.1					
	Size of riser/down-comer	-NA-	Provided	MR				
	Number of hydrants per floor	-NA-	01nos.	-NA-				
10	Hose Box	-11/1-	01nos.	-NA-				
12.	Yard Hydrants • Total number of hydrants -NANA-							
	 Total number of hydrants Hose Box 	-NA-	-NA-	-NA-				
12		-IVA-	-NA-	-NA-				
13.	Pumping Arrangements • Ground Level							
		-NA-						
	Discharge of main Pump	The Manager of the Control of the Co	-NA-	-NA-				
	> Head of Main pump	-NA-	-NA-	-NA-				
	Number of main pumps	-NA-	-NA-	-NA-				
	Jockey Pump out put	-NA-	-NA-	-NA-				
	Jockey pump head	-NA-	-NA-	-NA-				
	Standby Pump out put	-NA-	-NA-	-NA-				
	Standby Pump Head	-NA-	-NA-	-NA-				
	Auto Starting/Manual Stopping	-NA-	-NA-	-NA-				
	Pump House Access	-NA-	-NA-					
	Terrace level		-NA-	-NA-				
	Discharge of pump	900lpm	0001					
	Head of the pump	40m	900lpm 40m	MR				
	> Power Supply	Required	Provided	MR				
	➤ Auto Starting of pump	Required	Provided	MR				
14.	Captive Water Storage for fire fighting	Trovided	MR					
	 Underground tank capacity 	25,000ltr	25,000ltr) (D				
	Draw-off connection	Required	Provided	MR				
	Fire service inlet	Required	Provided	MR				
	Access to tank	Required	Provided	MR MR				
N.	Overhead Tank capacity	12,500ltr	12,500ltr					
15.	Exit Signage.	Required	Provided	MR MR				
16.	Provision of Lifts. Required Provided MR							
	Pressurization of Lift Shaft	NIA I	NI.	I NIA				
	Pressurization of Lift lobby	-NA-	-NA-	-NA-				
	Communication In lift Car	Required	Provided	MR				
	• Fireman's Grounding Switch	a separate amount of	Provided	MR				
	Lift Signage	Required	1.50 / 12-30-12-30-2	MR				
17.	Standby power supply	Required	Provided	MR				
18.	Refuge Area. Required Provided							
	N Total 4							
	Location	-NA-	-NA-	-NA-				
19.	Fire Control Room	-NA-	-NA-	-INA				
		374	-NA-	-NA-				
	Detector System PanelFlow Switch Panel	-NA-	-NA-	-NA-				
	PA System Panel PA System Panel	-NA-	-NA-	-NA-				
	Battery backup	-NA-	-NA-	-NA-				
	Building Floor Plans	-NA-	-NA-	-NA-				
	Danaing Floor Flans	//=#-3.#/#						



-NA--NA-Special Fire Protection System for -NA-Protection of special Risks, if any: Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection. In view of the deemed compliance of the minimum standards of the fire prevention and fire required under the rules the FSC issued vide F.6/DFS/MS/2022/WZ/College/17 dated 18.10.2022 is recommended for renewal of FSC under rule 37 of the Delhi Fire Service rules 2010. Signature of the Inspecting Officer Ajay Kumar Sharma Designation ADO (Rohini) Name Principal Director DCFO !- antiferror la series 8 9 1000 Kind pensel and sights.