

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2025/ 1156

Dated: 18 09/2025

FIRE SAFETY CERTIFICATE

Certified that the Saraswati Bal Mandir (ID-65605), located at A-2, Paschim Vihar, New Delhi-110063, comprised of Ground + 03 Upper Floor only owned/occupied by Samarth Shiksha Samiti (Regd.), was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/2022/1085 dated 29/09/2022. The said premise was re-inspected by the officer concerned of this department on 02/09/2025 in the presence of Sh. Pawan Palliwal (Accountant) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance D.O.E., GNCT of Delhi, Circular no.262-362 dated 17.01.2005 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 18/09/2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on ... 18/09/2025 at New Delhi by.

Virendra Singh Chief Fire Officer

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, Saraswati Bal Mandir (ID-65605), A-2, Paschim Vihar, New Delhi-110063. Conditions for validity of fire safety certificate:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building: Saraswati Bal Mandir (ID-65605), Located at A-2,

Paschim Vihar, New Delhi-110063

2. Type of Occupancy : Educational (G + 03 Upper Floor only)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/School/2022/1085 dated 29/09/2022

5. Fire Safety directives Letter No.: D.O.E. Cr. No. 262-362 dated 17.01.2005

6. Date of inspection : 02/09/2025

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. Pawan Palliwal (Accountant)

9. Year of Construction : 1996

10. Applicant's letter No. : email dated 02/08/2025

S No	Minimum standards on fire prevention and fire safety U/R 33			Provided at site	Remarks MR/NMR		
1.	Access of building	united By Oyr Edg					
H	Road width	06 m	Provided		MR		
- 1	 Gate width 	4.5 m	Provided		MR		
	 Width of internal road 				NA		
2.	Number, width, Type & Arran	gements of exits			1		
	a. Number of staircases						
- 11	 Upper floors 	2	P	rovided	MR		
- 11	 Basements 	NA		NA	NA		
- 11	b. Width of staircases				, and		
- 11	 Upper floors 	1.5 m	1.20 n	n & 1.23 m	MR(Old Case		
- 11	 Basements 	NA	222000000	NA	NA NA		
	c. Protection of exits		, NA				
11	 Fire check door 	NA		NA	NA		
1	 Pressurization 	NA		NA	NA NA		
	d. No of continuous	02	Pı	ovided	MR		
	staircase to terrace e. Width Of Corridor	1.5 m	1.75 n	n to 3.90 m	MR		
	f. Door Size	01 m		.05 m	MR		
(Compartmentation						
	Fire check door	NA		NA	NA		
Н	 Sealing of electrical 	NA	-	NA	NA NA		
	shafts			NA	INA		
	Fire Rating of shaft door	NA		NA	NA		
	Water Curtain	NA		NA	NA		
0	• Fire Dampers	NA		NΛ	·NA		
Si	moke managements System						
	• Basements	NA		NA	NA		
E.	• Upper floors	NA	1	NA	NA		
Fi	re Extinguishers						
	 Total numbers 	09 nos.	14	nos.	MR		
	• Types	ABC & CO ₂	Pro	vided	MR		
	ISI marking	ISI Marked	Pro	vided	MR		

	6. First – Aid Hose Reels				
+	Total numbers on each floor	01			
				rovided	
	isongui of nose reel nose	30m		rovided	
1	Nozzle diameter Automatic fire detection and alarmin	5mm	Pr	ovided	
H	 Automatic fire detection and alarmin Type of detectors 				-
	Location of Main Panel	NA NA		NA	
		NA NA		NA	
	Securion of Repeater Failer	NA		NA	
	Alternate source of power	NA		NA	
0	Hooters' Location	NΛ		NA	
8.	MOEFA	Required	d Pro	vided	
9.	Public Address System	Required	d Pro	vided	
10	- Sprinkler System				1
1	Basements	NA	N	ΝA	I
	Upper Floor	NA		NA.	T N
	Sprinkler above false ceiling	NA		IA	1
11.	Internal Hydrants:			А	N
	 Size of riser/down- comer 	100 mm	D	ide d	-
	Number of hydrants per floor	01	Prov	A CONTRACTOR OF THE PARTY OF TH	M
	Hose Box	Required	Prov	1000	M
12.	Yard Hydrants	Required	Provi	ided	M
	Total number of hydrants				
	Hose Box	NA	NA NA	1	N/
13.	Pumping Arrangements:	NA	NA		N/
	Ground Level	,			
	Discharge of main pump	NA	NA		NA
	Head of main pump	NA	NA		NA
	ramoer of main pumps	NA	NA		NA
	pullip out but	NA	NA		
	parity flead	NA	NA	\rightarrow	NA NA
	- unip out bill	NA	NA		NA
	- I unit lieat	NA	NA		NA_
- 1	staring/Mariual Stopping	NA	NA	-1+	NA
	Pump House Access	NA	NA	\rightarrow	NA
	Terrace level Discharge of nume		INA	-	NA
	Discharge of pump	450 lpm &	Drovid	-1	
	N 11 1 2 2 .		Provid	ea	MAD
	P Head of the mini-	180 lpm	1		MR
	Head of the pump	180 lpm 40 m	Dravid		
	Power supply	40 m	Provide		MR
	Power supplyAuto starting of pump	40 m Required	Provide	ed	MR MR
l. C	Power supply Auto starting of pump aptive water Storage for fire fighting:	40 m		ed	MR
i. C	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity	40 m Required Required	Provide Provide	ed ed	MR MR MR
4. C	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Praw off connection	40 m Required Required	Provide Provide NA	ed ed	MR MR MR
F. C	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Poraw off connection Fire service inlet	40 m Required Required NA NA	Provide Provide NA NA	ed ed	MR MR MR NA
ł. C	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Praw off connection Fire service inlet Access to tank	40 m Required Required NA NA Required	Provide Provide NA NA Provide	ed ed d	MR MR MR NA NA MR
	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Praw off connection Fire service inlet Access to tank Overhead Tank capacity	A0 m Required Required NA NA Required NA	Provide Provide NA NA Provide NA	ed ed d	MR MR MR NA NA MR
Ex	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Praw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage	NA Required NA Required NA Required NA 5,000 Itrs.	Provide Provide NA NA Provide NA Provided	ed e	MR MR MR NA NA MR NA MR
Ex	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Poraw off connection Fire service inlet Access to tank Overhead Tank capacity cit Signage ovision of Lifts	A0 m Required Required NA NA Required NA	Provide Provide NA NA Provide NA	ed e	MR MR MR NA NA MR
Ex	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity cit Signage ovision of Lifts Pressurization of Lift Shaft	A0 m Required Required NA NA Required NA 5,000 ltrs. Required	Provided NA NA Provided NA Provided Provided	d 1 M	MR MR MR NA NA MR NA MR
Ex	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby	A0 m Required Required NA NA Required NA 5,000 ltrs. Required	Provided NA NA Provided NA Provided NA Provided NA Provided NA	ed e	MR MR MR NA NA MR NA MR MR
Ex	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Corr	A0 m Required Required NA NA Required NA 5,000 ltrs. Required	Provided NA NA Provided NA Provided NA Provided NA Provided NA NA NA	ed e	MR MR MR NA NA MR NA MR MR
Ex	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity cit Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch	NA Required NA Required NA Required NA S,000 Itrs. Required NA NA NA	Provided NA NA Provided NA Provided NA Provided NA NA NA NA NA	ed e	MR MR MR NA NA MR NA MR AA AA
Ex. Pr	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage	A0 m Required Required NA NA Required NA 5,000 ltrs. Required NA NA NA NA	Provided NA NA Provided NA Provided NA Provided NA NA NA NA	d I N N N N N N N N N N N N N N N N N N	MR MR MR NA NA MR NA MR NA MR AA
Ex. Pro	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity cit Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage	A0 m Required Required NA NA Required NA 5,000 ltrs. Required NA NA NA NA NA NA NA	Provided NA NA Provided NA Provided NA Provided NA NA NA NA NA NA NA	ed e	MR MR MR NA NA MR NA MR NA MR AA
Ex. Pro	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage indby power supply fuge Area	A0 m Required Required NA NA Required NA 5,000 ltrs. Required NA NA NA NA	Provided NA NA Provided NA Provided NA Provided NA NA NA NA	d i N	MR MR MR NA NA MR NA MR NA A A A
Ex. Pro	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage indby power supply fuge Area Total area	A0 m Required Required NA NA Required NA 5,000 ltrs. Required NA NA NA NA NA Required	Provided NA NA Provided NA Provided NA Provided NA NA NA NA NA NA NA	d I N N N N N N N N N N N N N N N N N N	MR MR MR NA NA MR NA MR NA A A A
Ex. Pro	Power supply Auto starting of pump aptive water Storage for fire fighting: Under ground tank capacity Draw off connection Fire service inlet Access to tank Overhead Tank capacity it Signage ovision of Lifts Pressurization of Lift Shaft Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch Lift Signage indby power supply fuge Area	A0 m Required Required NA NA Required NA 5,000 ltrs. Required NA NA NA NA NA NA NA	Provided NA NA Provided NA Provided NA Provided NA NA NA NA NA NA NA	d i N	MR MR MR NA NA MR NA MR MR AA AA AA AA

19. Fire control room Detector system panel	NA	NA	NA
19. Fire control room Detector system panel Flow Switch Panel	NA	NA	NA
Camici I alici	NA	NA	NA
	NA	NA	NA
Battery backup Building Floor Plans	NA	NA	NA
> Building Floor Flans	NA	NA	NA
20. Special Fire Protection Systems for Protection of special Risks, if any;			
Protection of special relate,	l in the building	were checked	and found
Fire protection systems provided	in the bunding	Were enecked	and round
functional at the time of inspection.			
In view of the deemed compliance	e of the minimum s	standards on fire	prevention
and fire safety requirements as per D.0	D.E. Circular no.	262-362 dated 1	7.01.2005,
	Certificate issue	100	tter no.
renewal of the surely			
F6/DFS/MS/School/2022/1085 dated 29/		ichaca.	1
Accordingly DFA is put up for ap	proval please.	,	1
		10	usta W
	24	(4)	1100
1		2.4	EU 18/2
(622)			mar Lathar
Dero (h)2)		ADO	(JWP)
All Area Barrens			
in the state of th			
JAME CES			
116			
VWAG			
d.d1 /30 3c	-	R	
Remet 1 No 1	O fe	5 + 3	bu.
inneepal Dercela			
	=	e p	
		-01	3/20
		1,772	
	0	12/5	
	950	1245	
	950	12/5	7 3
11 Durkolum	2	 - My	
Dycko (wm)		My	
Lycko (wm)	ar)	My	
Dyero(wm)	ary)	1 My	()
Dycko (wm)	(P)	1 My	
Sui, F-T. Letter i	orp) mulup of	hy hy	ignatinu
Sui, F.T. Letter i	and)	hy hy	ignalinu
Sui, F.T. Letter is	arp) metup of	hy hy	ignatinu
Sui, F.T. Letter is	and)	hy my	111th 1
Sui, F.T. Letter is	arp) mt-up of	hy my	ignature 111th 11 16tog 121

M