

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F 6 / DFS / MS /EH/ 2025 /WZ/231

Dated 12/06/2025

FIRE SAFETY CERTIFICATE

Certified that M/s Sufiaana (A Unit of U and Me Hospitality) located at Upper Ground Floor, C-3/4, Pocket C-3, Phase-2, Ashok Vihar, Delhi-110052 is running at Upper Ground Floor only in a building comprised of Basement, Stilt, Upper Ground floor plus three Upper Floors have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 07.06.2025 in the presence of Sh. Vikas (Manager) and found that the building/premises is fit for occupancy "Assembly" (Group D) Restaurant at Upper Ground Floor only with effect from 12/06/2025 and valid up to 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on ... 12 | 0.6 | 2025. at New Delhi by

(Atul Carg)
Director
Delhi Fire Service

Copy to:-

1. The Commissioner, MCD, Delhi:- to ensure the occupancy as detailed above and deviation if any. 9)

 The Owner/ Occupier M/s Sufiaana (A Unit of U and Me Hospitality) located at Upper Ground Floor, C-3/4, Pocket C-3, Phase-2, Ashok Vihar, Delhi-110052.

3. MCD Portal ID No. 2023091115816.

Conditions for the validity of Fire Safety Certificate:

1. Fire Safety Certificate is valid for Upper Ground Floor only.

2. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

3. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

6. This certificate cannot be treated in any case for regularizations of unauthorized construction.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate through MCD portal (https://www.mcdonline.nic.in) along with a copy of this Certificate, six months prior to its expiry".

8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

9. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

10. The basement shall be used strictly as per building bye laws.

1. Name & address of the building: M/s Sufiaana (A Unit of U and Me Hospitality) located at Upper Ground 2. Type of occupancy Floor, C-3/4, Pocket C-3, Phase-2, Ashok Vihar, Delhi- 110052. 3. Building Comprised of : Assembly (Restaurant at Upper Ground Floor Only) 4. Type of case : Basement, Stilt, Upper Ground floor plus three Upper floors. 5. Details of Previous NOC New Case 6. Fire Safety directives letter No : Nil 7. Date of inspection Nil 8. Name of inspecting Officer 07/06/2025 9. Name and designation of officers R.K.Sinha, ADO (BW) From the building side 10. Year of Construction Sh. Vikas (Manager) 11. Applicant's letter No. 2023 as per MCD Portal Minimum Standards on fire MCD Application ID No. 2023091115816 dated 23/05/2025 NBC/ UBBL Remarks prevention and fire safety U/R 33 No. Provided at site MR/NMR Requirement 1. Access to building Road widtl MR Provided 6 m Gate width NA Directly Accessible NA Width of internal road NA NA NA Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors MR 02 03 Basements NA NA NA b. Width of staircases Upper Floor MR 2 m & 1.5 m 1 × 2 m & 2 × 1.5 m Basements NA NA NA c. Protection of exits NA NA NA Fire check door NA NA NA NA Pressurization NA NA d. No. of continuous staircases to NA NA NA terrace NA e. Width of Corridor NA NA 2 m & 1.5 m 2 × 2 m & 1 × 1.60 m MR f. Door Size 3. Compartmentation Required Provided MR Fire check door Required Provided MR Sealing of electrical shafts NA NA NA Fire Rating of shaft door NA NA Water Curtain NA NA NA Fire Dampers NA Smoke Management System 4. NA NA Basements NA Required Upper Ground floor Natural Ventilation MR Fire Extinguishers 5. 05 Nos. Provided Total numbers MR ABC/Co2 Type Provided Types MR Required IS marking Provided MR First-Aid Hose Reels 6. Total numbers on each floor 01 Provided MR Length of hose reel hose 30 m Provided MR Nozzle diameter 5 mm Provided Automatic fire detection and alarming system MR 7. Type of detectors NA NA NA Location of Main Panel NA NA Location of Repeater Panel NA NA Alternate source of power NA NA NA

NA

Required

NA

NA

Provided

NA

NA

MR

Hooters' Location

MOEFA

8.

		1		NA		
	1 Alvers System	NA	NA	I INA		
	Public Address System Automatic Sprinkler System	1-27-12	NA	NA		
0.	Basement Springer	NA	NA NA	NA		
	Upper Floor	NA	NA NA	NA		
	Sprinkler above false ceiling	NA	NA			
	Internal Hydrants		, Ar	MR		
1	Size of riser/down-comer	100 mm	Provided	MR		
	Number of hydrants per floor	01	Provided	MR		
	Hose Box	01	Provided			
2.	Yard Hydrants		NA	NA		
۷.	Total number of hydrants	NA NA	NA NA	NA		
	Hose Box	NA	INA			
3.	Pumping Arrangements					
	Ground Level	NA	NA	NA		
	Discharge of main Pump	NA NA	NA NA	NA		
	Head of Main pump	147		-		
	SWOME CO.	NA	NA	- NA		
	Number of main pumps	NA	NA	NA		
	Jockey Pump out put Jockey pump head	NA	NA	NA		
	Standby Pump out put	NA	NA	NA NA		
	Standby Pump Head	NA	NA	NA NA		
	Auto Starting/Manual Stopping	NA	NA	NA		
		NA	NA	NA		
	Pump House Access					
	Terrace level		N 22.12.1	MR		
	Discharge of pump	450 lpm	Provided Provided	MR		
	Head of the pump	40 m	Flovided			
		Required	Provided	MR		
	Power Supply	Required	Provided	MR		
	Auto Starting of pump Captive Water Storage for fire fight					
14.						
	Underground tank capacity	• NA	NA			
	Draw-off connection	NA	NA	NA		
	Fire service inlet	NA	NA	NA		
	Access to tank	NA	NA	NA		
		The state of the s				
	Tarp to Group and Control of the Con	. 20,000 ltrs	Provided	MR		
15.	Overhead Tank capacity Exit Signage.	20,000 ltrs Required	Provided Provided	MR MR		
	Overhead Tank capacity Exit Signage.					
	Overhead Tank capacity Exit Signage. Provision of Lifts.	Required	Provided			
	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft	Required	Provided	MR NA		
	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby	Required NA NA	Provided NA NA	MR		
	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft	NA NA NA	Provided NA NA NA NA	NA NA NA		
	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby	NA NA NA NA	NA NA NA NA NA	NA NA NA NA		
	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car	NA NA NA NA NA NA NA	NA NA NA NA NA NA NA NA NA	NA NA NA NA NA NA		
15. 16.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	NA NA NA NA	NA NA NA NA NA	NA NA NA NA		
17.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage	NA NA NA NA NA NA NA	NA NA NA NA NA NA NA NA NA	NA NA NA NA NA NA		
17.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area.	NA NA NA NA NA Required	NA NA NA NA NA NA NA NA NA	NA		
17.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area	NA NA NA NA NA NA NA	NA NA NA NA NA NA Provided	NA NA NA NA NA NA NA NA		
16. 17. 18.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area.	NA NA NA NA NA Required	NA NA NA NA NA Provided	NA		
16. 17. 18.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room	NA NA NA NA NA Required	NA NA NA NA NA Provided	NA		
16. 17. 18.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel	NA Required	NA Provided	NA		
16. 17. 18.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel Flow Switch Panel	NA NA NA NA NA Required NA NA NA NA NA NA NA	NA NA NA NA NA Provided NA	NA		
16.	Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel	NA NA NA NA NA Required NA NA NA NA NA NA NA	Provided NA NA NA NA NA Provided NA NA NA NA NA NA NA	NA		

7.	Special Fire Protection System for			
	Protection of special Risks, if any:	NA	NA	NA
الرزي	radis, if any.			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Reeping in view of satisfactory compliance of the minimum standards of fire prevention and fire safety measures as required under rules it is recommended to grant fire safety certificate under Rule 35 of the Delhi Fire Service Rules, 2010.

Signature of Inspecting Officer Name: Rajeev Kumar Sinha Designation: ADO/B.W.

nA suga

Am m

13/18/20 19/18/20