

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2025/ 116 9

Dated: 22 09 2025

FIRE SAFETY CERTIFICATE

Certified that the Shri Daulat Ram Public School, located at Kamaradin Nagar, Nangloi, Delhi-110041, comprised of Ground + 02 Upper Floors only was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/WZ/2022/859 Dated 05/08/2025. The said premise was re-inspected by the officer concerned of this department on 12/09/2025 in the presence of Sh. C. B. Yadav (Manager) and found that the premises / building have deemed complied with the fire prevention and fire safety requirements in accordance with D.O.E. Cr. No. 262-362 dated 17.01.2005 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 22/09/2025 for a period of three years, in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010, printed below.

Issued on 22/09/2025. at New Delhi by.

Virendra Singh

Chief Fire Officer

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, Shri Daulat Ram Public School, Kamaradin Nagar, Nangloi, Delhi-110041.

Conditions for validity of fire safety certificate:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name and address of the building: Shri Daulat Ram Public School Located at

Kamaradin Nagar, Nangloi, New Delhi-110041

2. Type of Occupancy : Educational (G + 02 Upper Floors only)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/School/WZ/2022/859 Dated 05/08/2025

5. Fire Safety directives Letter No.: D.O.E. Cr. No. 262-362 dated 17.05.2005

6. Date of inspection : 12/09/2025

7. Name of the Inspecting Officer: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. C. B. Yadav (Manager)

9. Year of Construction : 2007

10. Applicant's letter No. : S.D.R./25 dated 05/08/2025

S No	Minimum standards on fire prevention and fire safety U/R		Cr. No. 262-362 17.05.2005	2 dated	Provided site	at Remarks MR/NMR	
	33	and the salety C/K	Requirements/a earlier FSC issu dated 05/08/202	ed	3110		
1.	Access of building						
		Road width	06 m		Provided	MR	
		Gate width	4.5 m		Provided	MR	
	•	Width of internal road	NA		NA	NA	
2.	Numb	er, width, Type & Arranger	ments of exits				
		Number of staircases					
	•	Upper floors	02		Provided	MR	
	•	Basements	NA		NA	NA	
	b.	Width of staircases					
1		Upper floors	1.5 m	1.2 m &	& 1.3 m	MR(Old Case	
		Basements	NA		NA	NA	
	c.	Protection of exits					
		Fire check door	NA		NΛ	NA	
		Pressurization	NA		NA	NA	
	d.	No of continuous staircase to terrace	01		Provided	MR	
- 1	2000	Width Of Corridor	1.5 m		Provided	MR	
	f.	Door Size	1 m		1.46 m	MR	
3.	Comp	artmentation			NA		
	•	Fire check door	NA		NA	NA	
	•	Sealing of electrical shafts	NA		NA	NA	
- 1	•	Fire Rating of shaft door	NA		NA	NA	
- 1	•	Water Curtain	NA		NA	NA	
	•	Fire Dampers	NA		NA	NA	
4.	Smok	e managements System					
1	•	Basements	NA		NA	NA	
	•	Upper floors	NA		NA	NA	
5.	Fire F	Extinguishers					
	•	Total numbers	10 nos.		12 nos.	MR	
	•	Types	ABC & CO ₂		Provided	MR	
		ISI marking	ISI marked		Provided	MR	

- 1	•	-	
- 17			

T	Firet	– Aid Hose Reels			
+	1 1130	Total numbers on each floor	01	Provided	MR
		T - 1 - Chara roal hose	30 m	Provided	MR
		3.1 1 11	5 mm	Provided	MR
+		omatic fire detection and alarming	system		1
		omatic fire detection and district	NA	NA	NA
		Type of detectorsLocation of Main Panel	NA	NA	NA
		Location of Main Failer F Panagter Panel	NA	NA	NA
		Location of Repeater Panel	NA	NA	NA
		Alternate source of power	NA	NΛ	NA
		Hooters' Location	NA	NA	NA
	MC	DEFA	NA	NA	NA
	Pub	olic Address System			
0.	Au	tomatic Sprinkler System	NA	NA	NA
		• Basements	NA	NA	NA
		Upper Floor	NA	NA	NA
		Sprinkler above false ceiling			
11.	Int	ernal Hydrants:	100 mm	Provided	MR
		Size of riser/down- comer	01	Provided	MR
		 Number of hydrants per 	0.1		
		floor	01	Provided	MR
		Hose Box			
12.	. Y	ard Hydrants	NA	NA	NA
		Total number of hydrants	NA	NA	NA
		Hose Box			
13	. P	amping Arrangements:			1
		 Ground Level Discharge of main pump	NA	NA	NA
		 Discharge of main pump Head of main pump 	NA	NA	NA NA
		Number of main pumps	NA	NA	NA NA
		> Jockey pump out put	NA	NA NA	NA
		Jockey pump head	NA	NA NA	NA
		Standby Pump out put	NA NA	NA NA	NA
		Standby Pump Head	NA NA	NA	NA
		> Auto Staring/Manual	INA		
		stopping Pump House Access	NA	NA	NA
		 Pump House Access Terrace level 			1
		Discharge of pump	450 lpm & 180	Provided	MR
		* · · · · · · · · · · · · · · · · · · ·	lpm		MR
		Head of the pump	40 m	Provided	MR
		> Power supply	Required	Provided Provided	MR
		> Auto starting of pump	Required	Fibrided	
1	14.	Captive water Storage for fire fighting	g: NA	NA	NA
		 Under ground tank capacity Draw off connection 	NA NA	NA	NA
		> Fire service inlet	NA	NA	NA_
		> Access to tank	NA	NA	NA MR
		 Overhead Tank capacity 	10,000 ltrs.	Provided	MR
	15	Exit Signage	Required	Provided	IVIIC
	16.	Provision of Lifts	NA	NA	NA
		 Pressurization of Lift Shaft Pressurization of lift lobby 	NA NA	NA	NA
		Communication in lift Car	NA	NΛ	NA
		Fireman's Grounding Switch	NA	NA	NA NA
		➤ Lift Signage	NA	NA	NA
	17.	Standby power supply	NA	NA	NA
	18.	Refuge Area			
	-	The state of the s	NIA	NA	NA
		> Total area > Location	NA NA	NA NA	NA

		bel	7		
19.	Fire control room		Descri		
19.	Detector system	NA	NA	NA	
	panel	NA	NA	NA	1
	Flow Switch Panel	NA NA	NA NA	NA NA	1
	PA System PanelBattery backup	NA NA	NA	NA	1
	 Battery backup Building Floor Plans 	NA	NA	NA	
	Special Fire Protection	NA	NA	NA	
20.	Systems for Protection of				
				1 - lead and found	
	special Risks, if any; Fire protection system	ns provided	in the building we	ere checked and found	
	functional at the time of inspec				
	functional at the time of maps.		once of the minin	num standards on fire	
	In view of the deen	nea compile	ance of the imme	- No. 262-362 dated	
	prevention and fire safety	requirements	as per D.O.E.	.r. No. 202-302 dates	
	17.05.2005, renewal of	Fire Safet	y Certificate iss	sued vide letter no.	1
	F6/DFS/MS/School/WZ/2022	1950 Dated (5/08/2025 is recom	mended.	1
				In. ita	14
	Accordingly DFA is po	ut up for app	roval please.	11)111 00	105
				13/09	71
	(00)			Aman Kumar Lathar	
	NO (WC)			ADO (JWP)	
D	crotwr)				
	1				
	/				
	110	8			
	(10))			
Der	, o 1				
A. Jako	CFO	HI (
124		Vwg/_	_		
	1 16	T91/20	1		
	Principal D	1. to		. 8	
	Tricipal E	Lineuta	(4	fo bo J	42
				B	
	2				-
				18/28/	2
			Cof		
				N/	
				18 91 2025	
	^	1		18/91/2025	
	PID	BMB		•	
	Si				
	F.T Istan	is bu	trub In "	Paul 12 1-	1
	Si, F.T. INTER		y or g	manal wes	2/
	1 0	*		Ĭ	
ex	0 11.//			A	1
-	9/9/ 200V			9111-1	11
	19'91 son			19/09/	25
	A 2 B			19/09/ ADD	n
	5.0			W.OO	
	MS				