

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/GH/NDZ/2025/ 400

Dated:- 06/06/2025

FIRE SAFETY CERTIFICATE

Certified that the Shri Vinayak Guest House, located at 7813-14 & 7840, Saran Building, Ram Nagar, Main Qutab Road, Pahar Ganj, New Delhi-110055, comprised of Ground + 03 Upper Floors, ground floor (reception), 1st floor to 3rd floor (06 guest rooms at each floor), Total 18 guest rooms owned/occupied by Shri Vinayak Guest House, was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/GH/NDZ/2022/131 dated 02/03/2022. The said premise was re-inspected by the officer concerned of this department on 23/05/2025 in the presence of Sh. Nitin Goel (Owner) and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises/building is fit for occupancy class Residential, Sub Division A-1 for guest house, ground floor (reception) 1st floor to 3rd floor (06 guest rooms at each floor) Total 18 guest rooms up to 3rd floor only, with effect from o 6 06 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 printed below.

Issued on 06/06/2025 at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Commissioner, Municipal Corporation of Delhi, Civic Centre, Minto Road, New Delhi-110002:in r/o computer id no. 2025051508543 dated 15/05/2025, also to ensure occupancy as detailed above

2. The Joint Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony,

3. The Authorized Signatory, Shri Vinayak Guest House, 7813-14 & 7840, Saran Building, Ram Nagar, Main Qutab Road, Pahar Ganj, New Delhi-110055.

Conditions for the validity of fire safety certificate:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building: Shri Vinayak Guest House, located at 7813-14 & 7840,

Saran Building, Ram Nagar, Main Qutab Road, Pahar

Ganj, New Delhi-110055

: Residential Group A-1, Ground + 03 Upper Floors 2. Type of Occupancy

(Total 18 Guest Rooms) Ground Floor (Reception)

1st floor to 3rd floor (06 guest rooms at each floor)

: Renewal 3. Type of Case

: F6/DFS/MS/GH/NDZ/2022/131 dated 02/03/2022 4. Details of previous NOC

5. Fire Safety directives Letter No. : N/A

: 23/05/2025 6. Date of inspection

: Aman Kumar Lathar, ADO (JWP) 7. Name of the Inspecting Officer

8. Name and designation of Officer

: Sh. Nitin Goel (Owner) from the building side

: 2006 9. Year of Construction

0. <i>A</i> S No	Minimum standards on fire prevention and fire safety U/R	existing fire safety arrangements		1101166	Remarks MR/NMR	
-1	Access of building			06 m		
1.	Road width	NA	NA NA		NA	
1	Gate width	NA	NA NA		NA	
-1	rest to Cintornal road	NA	1111			
1	Number, width, Type & Arranger	ments of exits				
2.	a. Number of staircases			Provided	MR	
1	• Upper floors	01 no.		NA NA	NA	
	Basements	NA		NA		
-	b. Width of staircases			Provided	MR	
1	Upper floors	1.25 m	NA		NA	
	Basements	NA	NA NA			
	c. Protection of exits	NA I			NA	
	 Fire check door Pressurization d. No of continuous 	NA	NA NA		NA	
		NA	NA		MR	
		01 no.		Provided	IVIIX	
	staircase to terrace	NA	-	NA	NA	
	e. Width Of Corridor	1.0 m		Provided MR		
	- Part Amparas de distribuir a securitor de la companya del companya de la companya de la companya del companya de la companya	Door Size 1.0 m				
8.	Fire check door Sealing of electrical shafts	NA		NA	NA	
		NA		NA	NA	
		NA		NA NA		
		NA		NA	NA	
	 Fire Rating of shaft door 	NA NA	NA NA		NA	
	 Water Curtain 	1177				
	Fire Dampers					
	Smoke managements System	NA		NA	NA	
	 Basements 	1200120-000	Nati	ıral/Exhaust Fan		
	 Upper floors 	Required	Ivail	II all Dallaust I all	WIRC	
33	Fire Extinguishers			D 11 1) (D	
	Total numbers	12 nos.	_	Provided	MR	
	 Types 	ABC & CO ₂		Provided	MR	
	 IS marking 	Required		Provided	MR	
		- "				
		19.2				
	ſ	Ŋ				
		18				
		L',	ills.			
	4.0	8.0			1704	

5.	First – Aid Hose Reels						
3 A. S	Total numbers on each	01 no.	Provided				
	floor	VI 110.	Flovided				
	 Length of hose reel hose 	30 m	Provided				
	 Nozzle diameter 	05 mm	Provided				
7.	Automatic fire detection and alarmi	ing system	Tiovided				
	 Type of detectors (CO Type) 	Required	Provided				
	 Location of Main Panel 	Ground Floor	Provided	_			
	Location of Repeater	NA	NA	- 1			
	Panel		144	1			
	Alternate source of power Hooters' Location	Required	Provided	N			
8.		Ground floor	Provided	N			
9.	MOEFA Public Add	Required	Provided	N			
10.	Public Address System	Required	Provided	N			
	Automatic Sprinkler System Basements			- "			
	Upper Floor	NA	NA	NA			
	Sprinkler above false	NA NA	NA	NA			
	ceiling	NA	NA	NA			
11.	Internal Hydrants:						
	 Size of riser/down- comer 	100 mm	Provided	100			
	 Number of hydrants per 	01	Provided	MR			
	floor		riovided	MR			
12.	Hose Box Yard Hydrants	01	Provided	MR			
	Try draints						
	Total number of hydrantsHose Box	NA	NA	NA			
13.	Pumping Arrangements:	NA	NA	NA			
	Ground Level						
	Discharge of main pump	NA	NA	1			
	Head of main pump	NA	NA	NA NA			
	Number of main pumps Jockey pump out put	NA	NA	NA NA			
	Jockey pump out putJockey pump head	NA	NA	NA			
	Standby Pump out put	NA NA	NA	NA			
	Standby Pump Head	NA NA	NA	NA			
	➤ Auto Staring/Manual	NA	NA NA	NA			
	stopping Pump House Access		NA.	NA			
	Terrace level	NA	NA	NA			
	➤ Discharge of pump	450 1					
	➤ Head of the pump	450 lpm 40 m	Provided	MR			
	Power supply Auto starting of nump	Required	Provided Provided	MR			
1.	rate starting of pump	Required	Provided	MR MR			
14.	Captive water Storage for fire fighting:						
	Under ground tank capacity	NA	NA	NA			
	> Draw off connection	NA	NA	N/A			
	Fire service inlet	NA	NA NA	NA NA			
	Access to tank	NA	NA	NA			
15	Overhead Tank capacity Exit Signage	5,000 ltrs.	Provided	MR			
16.		Required	Provided	MR			
10.	> Pressurization of Lift	NA	NA				
	Shaft	110	INA	NA			
	 Pressurization of lift lobby 	NA	NA	NA			
	> Communication in lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	> Lift Signage	Required	Provided				
		Required	Provided	MR MR			
17.							

DO (60)

F-1. Letter is produce for your signature tot.

[111 4 1]

Supo6/25

ADD (SWP)