

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001



No. F6/DFS/MS/School/WZ/2025/ 1078

Dated:

29/08/2025

## FIRE SAFETY CERTIFICATE

Certified that the S. M. Public School, Z-183, Prem Nagar, Nangloi, Delhi-86, comprised of interconnected 02 blocks, B+G+2 & G+2 upper floors and school running in interconnected 02 blocks of, Ground + 02 upper floors was inspected by the officer concerned of this department on 30.07.2025 in the presence of Mr. Joginder Singh (Manager) and found that the said premises have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules,2010 and that the premise is fit for occupancy Group B Educational for interconnected 02 blocks of, Ground + 02 upper floors with effect from 29/08/2025 for a period of 03 (Three) years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 29 08 2025 at New Delhi by

(Virendra Singh) Chief Fire Officer Delhi Fire Service

DIC.

Copy to:

1. The Principal, S. M. Public School, Z-183, Prem Nagar, Nangloi, Delhi-86.

2. The Director of Education, Old Secretariat, Delhi

## Conditions for validity of Fire Safety Certificate;

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized construction.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director along with a copy of this Certificate, six months prior to its expiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form "K" is available on <a href="http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/">http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms</a>

INSPECTION REPORT

1. Name & address of the building: S. M. Public School, Z-183, Prem Nagar, Nangloi, Delhi-86.

. Type of Occupancy : Educational

3. Comprised of building : 02 blocks interconnected B+G+2 & G+2 upper floors

4. Type of Case : New Case (02 blocks interconnected G+2 upper floors)

Basement scaled by brick wall school management given by

undertaking not use for basement

5. Details of Previous NOC : F.6/DFS/MS/School/2019/1789 dated 18.09.2022 previous NOC

Gr. + 02 upper floors

6. Fire Safety directives letter No : NBC Part-IV

7. Date of inspection : 30.07.2025.

8. Name of Inspecting Officer : A. K. Sharma, ADO (Rohini) & D.B Mukherjee, DO (NW)

9. Name and designation of officers

From the building side : Mr. Joginder Singh (Manager)

10. Year of Construction : 2016, 2017 & 2025

11 Applicant's letter No. : Online e-mail dated 26.06.2025.

S. No.	Minim	m Standards on fire prevention e safety U/R 33	NBC-IV Requirement	Provided at site	Remarks MR/NMR			
1	Access to building							
1	•	Road width	Accessible	Accessible	MR			
		Gate width	Accessible	Accessible	MR			
		Width of internal road	-NA-	-NA-	-NA-			
•		er, Width, Type & Arrangement of I	Exits					
2.	a. Nur	nber of staircases						
	a. Ivai	Upper Floors	02nos.	03nos.	MR			
			-NA-	-NA-	-NA-			
	•	Basements						
	b. Wid	th of staircases	1.5m	1.90m, 1.65 & 0.95m	MR			
	•	Upper Floor	-NA-	-NA-	-NA-			
	•	Basements	-NA-					
	Cold Charles Charles	ection of exits	-NA-	-NA-	-NA-			
	Fire	check door	# SASSO T		-NA-			
	•	Pressurization	-NA-	-NA- 03nos.	MR			
	d. No	of continuous staircases to terrace	02nos. 1.5m	1.5m to 2.05m	-NA-			
	e. Wi	dth of Corridor		WARRANT FOR THE PARTY OF THE PA	MR			
	f. Do	or Size	1.0m	1.0m	IVIK			
3.	Compartmentation							
×.		Fire check door	-NA-	-NA-	-NA-			
		Sealing of electrical shafts	-NA-	-NA-	-NA-			
		Fire Rating of shaft door	-NA-	-NA-	-NA-			
	•	Water Curtain	-NA-	-NA-	-NA-			
	1 ● 13	Fire Dampers	-NA-	-NA-	-NA-			
4.	Smoke Management System							
4.	Smok	Basements	-NA-	-NA-	-NA-			
	•	Upper floors	12 a/c per hour	Natural ventilated	MR			
_		xtinguishers			\$555-516C			
5.	Fire E	Total numbers	13nos.	Provided	MR			
		Types	ABC/CO2	ABC/CO2	MR			
		IS marking	ISI marked	Yes	MR			
,	First-	Aid Hose Reels		105	IVIK			
6.	THSt.	Total numbers on each floor	01nos.	Provided	MR			
		Length of hose reel hose	30m	Provided	MR			
		Nozzle diameter	5mm	Provided	MR			
7.	Autor	natic fire detection and alarming syst		riovided	INIK			
	•	Type of detectors	-NA-	-NA-	NI A			
		Location of Main Panel	-NA-		-NA-			
			Chu - h	-NA-	-NA-			

any to

M	13
A	10

	3			1/				
	Location of Repeater Panel	-NA-	-NA-	N				
	Alternate source of power	-NA-	-NA-	-				
	20 September - December 1997	-NA-	-NA-	-NA				
		-NA-	-NA-	-NA-				
	MOEFA	-NA-	-NA-	-NA-				
).	Public Address System	-IAA-	-11/1-	-NA-				
10.	Automatic Sprinkler System	-NA-	-NA-	NA				
	Basement	-NA-	-NA-	-NA-				
	Ground & Upper Floors			25-25.72				
	Sprinkler above false ceiling	-NA-	-NA-	-NA-				
11.	Internal Hydrants	NA	NA	NA				
	Size of riser/down-comer	-NA-	-NA-	-NA-				
	Number of hydrants per floor	-NA-		-NA-				
10	Hose Box	-NA-	-NA-	-NA-				
12.	Yard Hydrants			363				
	Total number of hydrants	-NA-	-NA-	-NA-				
12	Hose Box	-NA-	-NA-	-NA-				
13.	Pumping Arrangements							
	Ground Level							
	Discharge of main Pump	-NA-	-NA-	-NA-				
	➤ Head of Main pump	-NA-	-NA-	-NA-				
	Number of main pumps	-NA-	-NA-	-NA-				
	Jockey Pump out put	-NA-	-NA-	-NA-				
	Jockey pump head	-NA-	-NA-	-NA-				
	Standby Pump out put .	-NA-	-NA-	-NA-				
	Standby Pump Head	-NA-	-NA-	-NA-				
	Auto Starting/Manual Stopping	-NA-	-NA-	-NA-				
	Pump House Access	-NA-	-NA-	-NA-				
	Terrace level							
	Discharge of pump	450lpm	450lpm	MR				
	Head of the pump	40m	40m	MR				
	➤ Power Supply	Required	Provided	MR				
	Auto Starting of pump	Required	Provided	MR .				
14.	Captive Water Storage for fire fighting	91	*					
	Underground tank capacity	-NA-	-NA-	-NA-				
	> Draw-off connection	-NA-	-NA-	-NA-				
	Fire service inlet	-NA-	-NA-	-NA-				
	> Access to tank	-NA-	-NA-	-NA-				
	Overhead Tank capacity	10,000ltr	10,000ltr	MR				
15.	Exit Signage.	Required	Provided	MR				
16.	Provision of Lifts.							
SEASON	SOCIAL SECTION CONTINUES SECTI	-NA-	-NA-	-NA-				
	Pressurization of Lift Shaft     Pressurization of Lift Ishby	-NA-	-NA-	-NA-				
	Pressurization of Lift lobby     Communication In lift Com	-NA-	-NA-	-NA-				
	Communication In lift Car     Fireman's Grounding Switch	-NA-	-NA-	-NA-				
	Fireman's Grounding Switch     Lift Signage		-NA-	-NA-				
	Lift Signage	-NA-		And the				
17.	Standby power supply	-NA-	-NA-	-NA-				
18.	Refuge Area.							
	> Total Area	-NA-	-NA-	-NA-				
	> Location	-NA-	-NA-	-NA-				
19.	Fire Control Room							
19.	D	-NA-	-NA-	-NA-				
	Detector System Panel     Flow Switch Panel	-NA-	-NA-	-NA-				
	PA System Panel	-NA-	-NA-	-NA-				
	PA System Panel	-NA-	-NA-	-NA-				

NA