

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELIII FIRE SERVICE: NEW DELIII- 110001



No. F6/DFS/MS/School/SZ/2025/1393

Dated: 12/12 /2025



FIRE SAFETY CERTIFICATE

Certified that the Sony Modern Public School, D - 355 - 356 Khadar Colony, Jaitpur Part - 2, New Delhi - 110044, comprised of Ground plus one upper floor was issued earlier FSC vide letter No. F6/DFS/MS/School/2018/SZ/919 dated 04/05/2018. The school building was re-inspected by the officer concerned of this department on 03/12/2025 in presence of Mr. Ramanuj and overseed that all the Fire Prevention and Fire Safety arrangement provided found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No F.16/Estate/CC/Fire Safet/2011/3298 to 3398 dated 01/03/2011 issued by Director of Education. Govt of NCT of Delhi and that the building / premises is fit for occupancy class "Educational Building" (Group - B) with effect from 12/12/2025 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010.

Issued on 12 12 2025 at New Delhi by.

Dy. Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Director of Education, Govt of NCT of Delhi, Old Secretariat, Delhi 110054.
- 2. The Principal, Sony Modern Public School, D 355 356 Khadar Colony, Jaitpur Part 2, New Delhi -110044.

Conditions for the validity of Fire Safety Certificate

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipment's and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the firefighting equipment's shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

Nho

			CTION REPORT	Γ				
1	N	ame & address of the building	Sony Modern	Sony Modern Public School, D-355-356 Khada				
•	-		Colony, Jaitpu	r Part-2, New Delhi-1	10044			
2		ilding is comprised of	Ground plus of	Ground plus one upper floor				
3		pe of occupancy	Educational Building (Group -B)					
5	_	pe of case	Renewal Case					
		tails of previous FSC	F6/DFS/MS/School/2018/SZ/919 dated 04/05/2018					
6	Fi	re safety directives letter no.	F.16/Estate/CC/Fire Safet/2011/3298 to 3398 dated 01/03/2011					
7	Da	te of inspection	03/12/2025	***				
8	Na	me of the inspecting officers	Yashwant Singh Meena, ADO/BCP					
9	Na	ume of the designation of officer om the building side	Mr. Ramanuj 2010 Outdoor Diary No. 8440 dated 18/11/2025					
10		ear of construction						
11	Aı	oplicant's letter no.						
S.No		Minimum standard of fire evention and fire safety U/R 33	As Per DOE	Provided at site	Remarks MR/NMR			
1		ccess to Building:						
-	A	Road width	6.0 meters.	6.0 meters.	MR			
	В	Gate width	4.5 meters.	Provided	MR			
=	C	Width of internal road	N/A	N/A	N/A			
2	N	mber, Width, Type and Arrans		VENEZISTO				
	Number, Width, Type and Arrangement of Exits: A Number of staircases							
			01.21		1			
		a Upper floor b Basement	01 No. N/A	03 Nos. N/A	MR N/A			
	В	Width of staircases	IVA	IVA	IV/A			
	D	a Upper floor	1.50 m/0.75m	Ground floor to) (D			
		а Оррег ноог	1.50 m/0.75m	Ground floor to Terrace floor-1.20m, Ground floor to First floor-1.25m, 1.02m	MR			
[b Basement	N/A	N/A	N/A			
	C	Protection of exits	\$24x11.0					
		a Fire check door	N/A	N/A	N/A			
	D	b Pressurization No. of continuous staircases	N/A	N/A	N/A			
3	ע	to terrace	N/A	N/A	N/A			
	E	Width of corridor	1.50m	Provided	MR			
	F	Door size	lm	Provided	MR			
3	Co	npartmentation:			1,111			
	A	Fire check door	NA	NA	NA			
	В	Sealing of electrical shafts	N/A	N/A	N/A			
	C	Fire rating of shaft door	N/A	N/A				
	D	Water curtain	N/A	N/A N/A	N/A			
	E	Fire dampers	N/A	N/A	N/A			
1	Sm	oke Management System:		IV/A	N/A			
	A	Basement	30 ACPH	27/4				
	В	Upper floor	12 ACPH	N/A	N/A			
			12 ACPH	N/A	N/A			

 $b_{n/n}$

5.	Fire Extinguisher:						
	A	Total numbers	06 No's.	06 No's.	-		
	B	Types	CO ₂ & ABC	Provided	M		
	C	ISI marking	ISI mark		M		
6	Fin	rst-Aid-Hose Reel:	101 mark	Provided	M		
	A	Total numbers of each	N/A	NIA			
	_	floor		N/A	N/		
	B	Length of hose reel hose	N/A	N/A	N/A		
	C	Nozzle diameter	N/A	N/A	N/A		
7	Au	tomatic Fire Detection and	Alarming System:		14/2		
	A	Type of detectors	N/A	N/A	N/A		
	B	Location of main panel	N/A	N/A	N/A		
	C	Location of repeater panel	N/A	N/A	N/A		
	D	Alternate source of power	N/A	N/A	N/A		
0	E	Hooters	N/A	N/A	N/A		
8	_	OEFA:	N/A	N/A	N/A		
9	Pu	blic Address System:	N/A	N/A	N/A		
10	Au	tomatic Sprinkler System:		AMAR	IV/A		
	A	Basement	N/A	N/A	N/A		
	В	opper moor	N/A	N/A	N/A		
	C	Sprinkler above false	N/A	N/A			
11	T	ceiling		IVA	N/A		
11	A	ternal Hydrants:					
	B	Size of riser/down-comer	N/A	N/A	N/A		
	В	Number of hydrants per floor	N/A	N/A	N/A		
	C	Hose box	N/A	U.			
12	Ya	rd Hydrants:	IVA	N/A	N/A		
	A	Total number of hydrants	N/A	27/4			
	B	Hose box	N/A	N/A N/A	N/A		
13	Pu	mping Arrangements:	1011	N/A	N/A		
l	Ground level						
	A	Discharge of main pump	N/A	N/A	7/4		
	B	Head of main pump	N/A	N/A	N/A		
	C	Number of main pumps	N/A	N/A	N/A		
	D	Jockey pump out put	N/A	N/A	N/A N/A		
let	E	Jockey pump head	N/A	N/A	N/A		
	F	Standby pump out put	N/A	N/A	N/A		
}	G H	Standby pump head	N/A	N/A	N/A		
	п	Auto starting /manual stopping	N/A	N/A	N/A		
_	I	Pump house access	N/A	NI/A	7/11		
	Ter	race Level	- AVA	N/A	N/A		
	A	Discharge of pump	N/A	N/A	N/A		
-	B	Head of the pump	N/A	N/A	N/A		
-	C	Power supply	N/A	N/A	N/A		
	D	Auto starting of pump	N/A	N/A	N/A		
4	Captive Water Storage for Fire Fighting:						
	A	Underground tank capacity	N/A	N/A	N/A		
	В	Draw-off connection	N/A	N/A	N/A		
	-	Fire service inlet	NIA				
ŀ	C	rife service iniet	N/A	N/A	N/A		
	C D	Access to tank	N/A N/A	N/A N/A	N/A N/A		

Q

15	Exit	Signage:	Required	Provided	MR		
16	Provision of Lifts:						
	A	Pressurization of lift shaft	N/A	N/A	N/A		
	В	Pressurization of lift lobby	N/A	N/A	N/A		
	C	Communication in lift car	N/A	N/A	N/A		
	D	Firemen's grounding switch	N/A	N/A	N/A		
	E	Lift signage	N/A	N/A	N/A		
17	Sta	ndby Power Supply:	N/A	N/A	N/A		
18	Refuge Area:						
F	A	Total area	N/A	N/A	N/A		
	В	Location	N/A	N/A	N/A		
19	Fire Control Room:						
	A	Detector system panel	N/A	N/A	N/A		
	В	Flow switch panel	N/A	N/A	N/A		
	C	PA system panel	N/A	N/A	N/A		
	D	Battery backup	N/A	N/A	N/A		
	E	Building floor plans	N/A	N/A	N/A		
20	Sp	ecial Fire Protection systems for otection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter F6/DFS/MS/School/2018/SZ/919 dated 04/05/2018, renewal under Rule 35(6) of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer
Name Yashwant Singh Meena
Designation ADO/BCP

D.O/SD Ravinder Singh

Djegley

A. K. MALIK

Princi Dal Dhuelin

by. Cro to Desem

m. cf. (s =)

10/12/22

July MALIK

son Bay