

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

ग्राह्मिक आज़ादीक अमृत महोत्सव

No.F6/DFS/MS/School/SZ/2025/ 1038

Dated: 21/08/2025

FIRE SAFETY CERTIFICATE

Issued on 2108 2025 at New Delhi by

(Virendra Singh) Chief Fire Officer

Copy to:-

- 1. The Dy. Director of Education, GNCT of New Delhi DISST. South Block-C, Defence Colony, New Delhi-24.
- 2. The Principal, St. Paul's Diocesan School located at Hospital Road, Jangpura, New Delhi-14.

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures; management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

21/14

			INSPE	CTION REPORT			
	Name			St. Paul's Diocesan School located at Hospital Road, Jangpura, New Delhi-14.			
	Build	ding	s is comprised of	Ground + 02 upper floors			
	Туре	of	occupancy	Group B- Educational building			
e l	Туре	of	case	Renewal	ounding		
			of previous FSC	F6/DFS /MS/School/S	7/2022/708 dated 2	7.06.2022	
,	Fire	safe	ety direction letter no.	F6/MS/DFS/2004/2753		(New York of the Control of the Cont	
	Date	of	inspection	14.08.2025	dated 11/11/2001		
3	Nam	ne o	f the inspecting officers	Rajesh Kumar Shukla,	ADO (M.Road)		
)	Nam	ne o	f the designation of officer e building side	Mrs. Rohini Juliaana D			
10	Yea	r of	construction	1976		0	
11			int's letter no.		2 dated-30.07.2025		
S.No	Mir			Outdoor diary no. 4302 dated-30.07.2025 Requirement as per Provided at site Rem			
31210	prevention and fire safety U/R			Rule 35 (6)		MR/NMR	
1	Acc	ess	to Building:			T-2	
	A	_	oad width	6.0 mtrs.	6.0 mtrs.	MR	
	В	G	ate width	4.5m	Provided	MR	
	C	W	idth of internal road	NA	NA	NA	
2	Nu	mb	er, Width, Type and Arran	gement of Exits:			
	A Number of staircases						
it.		a	Upper floor	2 nos.	02 nos.	MR	
		b	Basement	NA	NA	NA	
	В	V	Vidth of staircases		1.14 mtrs &	MR	
	=	а	Upper floor	1 staircase of 1.5 mtrs or if main staircase width is < 1.5 mtrs an additional staircase of 0.75 mtrrs width is required	1.05 mtrs.	î	
	-	b	Basement	NA	NA	NA	
	C	F	Protection of exits				
-		a	Fire check door	NA	NA	NA	
		b	Pressurization	NA .	NA	NA	
	D	t	No. of continuous staircases o terrace	Markey Dy Cont.	Provided	MR	
	E		Width of corridor	1.5 mtrs	1.5 mtrs	MR	
	F		Door size	1.0 mtrs.	Provided	MR	
3	C		partmentation:				
	A		Fire check door	NA	NA	NA	
	В	_	Sealing of electrical shafts	NA	NA	NA	
	C	_	Fire rating of shaft door	NA	NA	NA	
	D		Water curtain	NA	NA	NA	
	E		Fire dampers	NA	NA	NA	
4	Smoke Management System:						
	A		Basement	NA	NA	NA	
-	B		Upper floor	NA	NA	NA	
5.	765		Extinguisher:				
1	A	-	Total numbers	06 nos.	07 nos.	MR	
1	В		Туреѕ	CO ₂ & ABC	CO ₂ & ABC	MR	
	C		ISI marking	ISI marked	Provided	MR	
6	-		-Aid-Hose Reel:			-	
	A		Total numbers of each floor	02 nos.	02 nos.	MR	
	B		Length of hose reel hose	30 mm	30 mm	MR	
	(-	Nozzle diameter	05 mm	05 mm	MR	

NIIB

. 1.	A	omatic Fire Detection and Ala Type of detectors	NA	NA	NIA				
-	В	Location of main panel	NA	NA NA	NA				
_	C	Location of repeater panel	NA	NA NA	NA NA				
F	D	Alternate source of power	NA	NA	NA NA				
H	E	Hooters	NA	NA NA					
		EFA:	NA		NA				
	- 17			NA	NA				
_	_	lic Address System:	NA	NA	NA				
10	Automatic Sprinkler System: A Basement								
-	A		NA	NA	NA				
	В	Upper floor	NA	NA	NA				
	C	Sprinkler above false ceiling	NA	NA	NA				
11	Internal Hydrants:								
	A	Size of riser/down-comer	NA	NA	NA				
	В	Number of hydrants per floor	NA	NA	NA				
114	С	Hose box	NA	NA	NA				
12	Yard Hydrants:								
	A	Total number of hydrants	NA	NA	NA				
	В	Hose box	NA ·	NA NA					
13			INA	INA	NA				
13 A	Pumping Arrangements: Ground level								
Λ.	_		Tara	1					
	a)	Discharge of main pump	NA	NA	NA				
	b)	Head of main pump	NA	NA	NA				
	c)	Number of main pumps	NA	NA	NA				
	d)	Jockey pump out put	NA .	NA	NA				
	e)	Jockey pump head	NA	NA	NA				
	f)	Standby pump out put	NA	NA	NA				
	g)	Standby pump head	NA	NA	NA				
	h)	Auto starting /manual	NA	NA	NA				
	i)	stopping Pump house access	NIA	N.A.	_				
В		rrace Level	NA	NA	NA				
-	District Control of the Control of t								
-	a) b)	Discharge of pump Head of the pump	450 LPM 40m	Provided	MR				
	c)	Power supply	Required	Provided	MR				
	d)	Auto starting of pump	Required	Provided	MR				
14	1.5			Provided	MR				
14		ptive Water Storage for Fire							
	A	Underground tank capacity	NA	NA	NA				
	B	Draw-off connection	NA	NA	NA				
		m:							
	C	Fire service inlet	NA	NA	NA				
	C D	Access to tank	NA	NA NA	NA NA				
	C D E	Access to tank Overhead tank capacity	NA 3,000 ltr						
15	C D E Ex	Access to tank Overhead tank capacity it Signage:	NA	NA	NA				
15 16	C D E Ex Pr	Access to tank Overhead tank capacity it Signage: ovision of Lifts:	NA 3,000 ltr	NA 5,000 ltr	NA MR				
	C D E Ex Pr	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft	NA 3,000 ltr	NA 5,000 ltr Provided	NA MR MR				
	C D E Ex Pr A B	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby	NA 3,000 ltr Required	NA 5,000 ltr Provided	NA MR MR				
	C D E Ex Pr A B C	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car	NA 3,000 ltr Required NA NA	NA 5,000 ltr Provided	NA MR MR NA				
	C D E Ex Pr A B C D	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch	NA 3,000 ltr Required NA NA	NA 5,000 ltr Provided NA NA	NA MR MR NA NA				
16	C D E Ex Pr A B C D E	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage	NA 3,000 ltr Required NA NA NA NA NA NA NA	NA 5,000 ltr Provided NA NA NA	NA MR MR NA				
16 17	C D E Ex Pr A B C D E Sta	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply:	NA 3,000 ltr Required NA NA NA NA NA	NA 5,000 ltr Provided NA NA NA NA NA	NA MR MR NA NA NA				
16	C D E Ex Pr A B C D E Sta	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area:	NA 3,000 ltr Required NA NA NA NA NA NA NA	NA 5,000 ltr Provided NA NA NA NA NA NA NA	NA MR MR NA NA NA NA				
16 17	C D E Ex Pr A B C D E Sta	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area	NA 3,000 ltr Required NA NA NA NA NA NA NA	NA 5,000 ltr Provided NA	NA MR MR NA NA NA NA NA				
16 17 18	ExPr A B C D E Sta Re	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area Location	NA 3,000 ltr Required NA NA NA NA NA NA NA NA NA	NA 5,000 ltr Provided NA	NA MR MR NA NA NA NA NA				
16 17	ExPr A B C D E Sta Re	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area	NA 3,000 ltr Required NA	NA 5,000 ltr Provided NA	NA MR MR NA NA NA NA NA				
16 17 18	C D E Ex Pr A B C D E Sta Re A B Fin	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area Location re Control Room:	NA 3,000 ltr Required NA	NA 5,000 ltr Provided NA	NA MR MR NA NA NA NA NA				
16 17 18	C D E Ex Pr A B C D E Sta Re A B Fin	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area Location re Control Room: Detector system panel Flow switch panel	NA 3,000 ltr Required NA	NA 5,000 ltr Provided NA	NA MR MR NA				
16 17 18	C D E Ex Pr A B C D E Sta Re A B Fin	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area Location re Control Room: Detector system panel Flow switch panel PA system panel	NA 3,000 ltr Required NA	NA 5,000 ltr Provided NA	NA MR MR NA				
17 18	C D E Ex Pr A B C D E Sta Re A B Fin	Access to tank Overhead tank capacity it Signage: ovision of Lifts: Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: fuge Area: Total area Location re Control Room: Detector system panel Flow switch panel	NA 3,000 ltr Required NA	NA 5,000 ltr Provided NA	NA MR MR NA				

117

20 Special Fire Protection systems for protection of special Risks, if any:

Meeting Requirement (MR), Not Meeting Requirement (NMR), Not Applicable (NA), Provided but Not Functional (PNF), Not Provided (NP).

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS /MS/School/SZ/2022/708 dated 27.06.2022 is recommended to be renewed.

Signature of the Inspecting Officer
Name Rajesh Kumar Shukla
Designation ADO (M. Road)

Designation

Designation

Allo (MRd)

Finished Director

Also (MRd)

Finished Livertor

Also (MRd)

Finished Livertor

Also (MRd)

Cro | Nmg x181/2015

MS