



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

F.6/DFS/MS/2025/SZ/547 No.

Dated. D& /I.Q. /2025

FIRE SAFETY CERTIFICATE

Certified that the M/s TDI Mall Property Development Area located at Nehru Place Metro Station, New Delhi 110019 Comprised of Basement, lower ground & upper ground floor, owned/occupied by M/s TDI Mall, Delhi Metro was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/2022/SZ/434 dated 29/08/2022. The premise was re-inspected by the officer concerned of this department on 22/09/2025 in the presence of Sh. Brijesh Panday and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class "Mixed Occupancy" (Lower & Upper Ground Floor:- Restaurant & Food Court) with effect from O. 2./. LO. 2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 08 / 10 /2025 at New Delhi by

M. K MALIK) Dy. CFO (SOUTH ZONE) **DELHI FIRE SERVICE**

1. M/s TDI Mall Property Development Area at Nehru Place Metro Station, New Delhi 19

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. The basement shall be used as per the provisions of BBL /NBC Part- IV

6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.

"The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six

month prior to its expiry."

W/22

	INSI ECTION OF THE Ruilding	ON REPORT	आज़ा	दीका	
	Name & Address of the Building	M/s TDI Mall,	Nehru place Metro S	tation Nov	
ă.	20 manay	Delhi 110019 Mixed		11011, 1101	
2	Type of Occupancy				
$\frac{2}{3}$	Building Comprised of	Basement, Lower ground floor & upper ground flo			
-3-	CCace	33.00			
5	- 1- of previous NOC	F6/DFS/MS/2022/SZ/434 dated 29/08/2022			
$\frac{3}{6}$	Fire Safety Directives Letter No NII				
$-\frac{6}{7}$	CI-spection	22/09/2025			
8	Calca Incheciting Officers	Sh. Rajesh Kumar DO			
-8-	Name & Designation of Officers	Sh. Brijesh Panday			
9	from the building side	2009			
10	Ver of construction				
$\frac{10}{11}$	Applicant letter No.	DFS Outdoor diary no 5511 dated 02/09/2025			
3.1	Minimum standards on Fire Prevention	Old NOC Provided at Site Remarks			
S. No.	Minimum standards on The Tree Man	Requirements	1 Tovided at Site	MR/NM	
	and Fire Safety U/R 33			MINIMI	
1	Access to Building.	20			
	Road width	30 mtr 6 mtr	Provided	MR	
	Gate width	N. C.	Provided	MR	
	Width of internal road	6 mtr	Provided	MR	
	Number, width, type & arrangement of ex	cits.		Paralle Service	
2	a) Number of Staircase				
	> Upper floors.	04 Nos	Provided	MR	
	> Basement floor.	07 Nos	Provided	MR	
	b) Width of Staircase				
	> Upper floors	1.50 mtr	1.80 mtr (each)	MR	
	> Basement floor	1.50 mtr	1.80 mtr (each)	MR	
	c) Protection of exits				
	> Fire check door	Required	Provided	MR	
	> Pressurization	Required	Provided	MR	
	d) No. of continuous staircase to terrace	Required	Two	MR	
	e) Width of corridor	Required	2.50 mtr	MR	
	f) Door size	Required	1.2 mtr	MR	
3	Compartmentation.				
	Fire check door.	Required	Provided	MR	
	Sealing of electrical shafts.	Required	Provided	MR	
	Fire rating of shaft door.	Required	Provided	MR	
	Water curtain	N/A	N/A	N/A	
	Fire dampers.	Required	Provided	MR	
4	Smoke Management system.	10	*		
		20 ACDU	Provided	MR	
	Basement	30 ACPH	Provided	MR	
	• Upper floors	12 ACPH	Provided	IVIIC	
5	Fire Extinguishers.				
	Total numbers	82 Nos	Provided	MR	
	Types	ABC/CO ₂	ABC- & CO ₂	MR	
61-	ISI Marking	ISI marked	Provided	MR	
6	First Aid Hose Reels.				
7.00	Total numbers on each floor.	04 Nos each	Provided	MR	
777		30m	Provided	MR	
	Length of hose-reel hose.			MR	
	Length of hose-reel hose. Nozzle Diameter	5mm	Provided	MK	
7	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming system	5mm	STATE OF THE STATE		
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming system Type of detectors	5mm Required	Smoke type	MR	
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming system Type of detectors Location of Main Panel	5mm Required Required	Smoke type Lower ground	MR MR	
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming system Type of detectors Location of Main Panel Location of Repeater Panel	5mm Required Required Required	Smoke type Lower ground Basement	MR MR MR	
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming system Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power	5mm Required Required Required Required Required	Smoke type Lower ground Basement Battery backup	MR MR MR MR	
	Length of hose-reel hose. Nozzle Diameter Automatic fire detection & alarming system Type of detectors Location of Main Panel Location of Repeater Panel	5mm Required Required Required	Smoke type Lower ground Basement	MR MR MR	



N/56

10	N/56			
-	Automatic Sprinkler System			MR
	Dasement		Provided	MR
	 Ground floor. 	Required	provided	MR
11	Sprinkler above C t	Required	Provided	
11	ants.	Required		MR
	Size of Riser/Down-comer	120000	Provided	MR
	Number of Hydrant per floor	150 mm	Provided	MR
	TIUSE DOX	04 Nos	Provided	
12	Yard Hydrants.	04 Nos		MR
	• Total number of hydrants.	0437	Provided	MR
	Hose box	04 Nos	Provided	
13	Pumping arrangements.	04 Nos		
	• Ground Level) (P
	Discharge of main pump.	2222 I D1 (Provided	MR
	riead of main numn	2280 LPM	Provided	MR
	Number of main numps	70 m	Provided	MR
	Jockey Pump output	02 280 & 180 LPM	Provided	MR
	Jockey Pump head	70 m	Provided	MR
	Standby Pump output	2280 LPM	Provided	MR
	Standby Pump head	70 m	Provided	MR
	➤ Auto Starting/Manual Stopping	Required	Provided	MR
	Pump house access.	Required	Provided	MR
	Terrace Level	Required	Tioviaci	
	Discharge of pump.	N/A	N/A	N/A
	Head of pump.	N/A	N/A	N/A
	Power supply.	N/A	N/A	N/A
	Auto starting of pump.	- F 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	N/A	N/A
14		N/A	IV/A	
14	Captive water storage for fire fighting.	1 00 000 1	Provided	MR
	 Underground tank capacity. Draw-off connection. 	1,00,000 ltrs	Provided	MR
	Fire Service Inlet.	Required Required	Provided	MR
	Access to tank.	Required	Provided	MR
	Overhead tank capacity.	10,000 ltrs	Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	Required	riovided	WIIX
10	Pressurization of lift shaft.	N/A	N/A	N/A
	Pressurization of lift lobby.	N/A	N/A	N/A
	Communication in lift car.	N/A	N/A	N/A
	Fireman's switch.	N/A	N/A	N/A
	en de	N/A	N/A	· N/A
17	Lift signage. Standby Power Symply	Required	90 700000	
17 18	Standby Power Supply Refuge Area	Required	Provided (DG set)	MR
10	ACTUBO TATOM			
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room.			
	 Detector system panel. 	Required	Provided	MR
	 Flow switch panel. 	Required	Provided	MR
	PA system panel.	Required	Provided	MR
	Battery backup.	Required	Provided	MR
	Building floor plan.	N/A	N/A	N/A
20	Special Fire Protection System for the	NT/A	NUA	24/4
40	Protection of special Risk, if any.	N/A	N/A	N/A



The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and Keeping in the Keepin fire safety included safety results of the Delhi Fire Service rules, the FSC issued vide letter no F6/DFS/MS/2022/SZ/434 dated 29/08/2022, renewal under rule 37 of the Delhi Fire Service rules,

2010 is recommended. Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Designation: Divisional Officer

DO (South)

Dp. CFO (52)

sir. F.T Letter is putup tox Sign, Fleosy