GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHIO HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/GH/SZ/2025/ 449

Dated: 11 07 2025

FIRE SAFETY CERTIFICATE

Certified that the M/s "The Grand Vikalp" Guest House, located at C-48A, Greater Kailash, New Delhi-110048, comprised of basement, ground plus three upper floors only, was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/GH/2020/SZ/136 dated 11/09/2020. The said premise was re-inspected by the officer concerned of this department on 03/07/2025 in the presence of Sh. Ravi Sial (Manager) and found that the premises have deemed complied with the fire prevention and fire safety requirements in accordance with the Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises/building is fit for (Basement-Storage only, Ground Floor-Reception & 02 guest rooms, 1st floor-06 guest rooms, 2nd to 3rd floor- 07 guest rooms at each floor), Total-22 guest rooms only, occupancy class "Residential Group-A" (Lodging or Rooming House only) as above with effect from 1107 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 printed below.

Issued on 11 07/2075 at New Delhi by

Copy to:-

- 1. The Commissioner, Municipal Corporation of Delhi, Civic Centre, Minto Road, New Delhi-110002:in r/o computer id no. 2025061810213 dated 18/06/2025, also to ensure occupancy as detailed above and deviation, if any.
- 2. The Joint Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.
- 3. The Authorized Signatory, M/s "The Grand Vikalp" Guest House, located at C-48A, Greater Kailash, New Delhi-110048.

Conditions for the validity of fire safety certificate:-

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry. The hacement chall he used as ner RRI

INSPECTION REPORT

Name & address of the building : M/s The Grand Vikalp (Unit of Todoslosantos Global

Pvt. Ltd.) located at C 48-A, GF, FS, SF, TF, Greater

Kailash Part-1, Delhi-110048

Type of Occupancy : Residential, "Group-A" Basement + Ground + 03

Upper Floors, basement - storage, ground - reception & 02 guest rooms, 1st floor - 06 guest rooms. 2nd floor to 3rd floor – 07 guest rooms at each floor, Total

22 guest rooms only

: Renewal Type of Case

: F6/DFS/MS/GH/2020/SZ/136 dated 11/09/2020 Details of previous NOC

Fire Safety directives Letter No.

: 03/07/2025 Date of inspection

: Aman Kumar Lathar, ADO (JWP) Name of the Inspecting Officer

Name and designation of Officer

: Sh. Ravi Sial (Manager) from the building side

Year of Construction

: 2011

Ю	Minimum standards on fire prevention and fire safety U/R 33	Requirements as per earlier FSC issued dated 11/09/2020		Provided at site	Remarks MR/NMR	
	Access of building			00	MR	
	Road width	Required	-	09 m	NA	
	Gate width	NA		NA	NA	
	my the of internal road	NA		NA	****	
	Number, width, Type & Arrangeme	ents of exits				
					MR	
	T-wee	Required		One	MR	
		Required		Two	WIK	
	True 1.1 Cataireases		0.939	-	MR	
		Required		25 m	MR	
	• Upper floors	Required	1.05 m	& 1.0 m	IVIK	
	Basements Protection of exits					
	c. Protection of Carlo	Required	I	rovided	MR	
	Fire check door	NA		NΛ	NA	
	Pressurization No of continuous staircase	Required		One	MR	
	to terrace	NA	1	NA	NA	
	e. Width Of Corridor	1.0 m	1 20 1	n (final exit)	MR	
	f. Door Size	1.0 m	1.20	(
	Compartmentation	Required	p p	rovided	MR	
•	ring check door	Required		rovided	MR -	
	Scaling of electrical shalls	NA	1 - 1	NA	NA	
	Fire Rating of shall door	NA NA		NA	NA	
	Water Curtain	NA		NA	NA	
	- Fire Dampers	1471		12-12-15 (1991)	19 (1.0) (8)	
	Smoke managements System	Required	Ev	haust Fan	MR	
	 Basements 	Required	1	haust Fan	MR	
	 Upper floors 	Required	12.	naust I all	WIK	
	Fire Extinguishers		-			
	Total numbersTypes	12 nos.		rovided	MR	
		ABC & CO ₂		rovided	MR	
	ISI marking	ISI marked	Provided		MR	

		11/48		1		
6.	First – Aid Hose Reels					
	Total numbers on each floor	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	 Nozzle diameter 	05 mm	Provided	MR		
7.	Automatic fire detection and alarmin	g system				
	 Type of detectors 	CO type	Provided	MR		
	 Location of Main Panel 	N/A	N/A	N/A		
	 Location of Repeater Panel 	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
0			2 1000			
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System		1	2.40		
	Basements	Required	Provided	MR		
	Upper Floor	N/A	NΛ	N/A		
	Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants:			2 5270		
	Size of riser/down- comer	N/A	N/A	N/A		
	 Number of hydrants per 	N/A	N/A	N/A		
	floor					
	Hose Box	N/A	N/A	N/A		
12.	Yard Hydrants		9			
	Total number of hydrants	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13.	Pumping Arrangements:			1		
	Ground Level					
	Discharge of main pump	N/A	N/A	N/A		
	> Head of main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	> Jockey pump out put	N/A	N/A	N/A		
	> Jockey pump head	N/A	N/A	N/A		
	Standby Pump out put	N/A	N/A	N/A		
	Standby Pump Head	N/A	N/A	N/A		
	> Auto Staring/Manual	N/A	N/A	N//		
	stopping	5,492-4,65				
	> Pump House Access	N/A	N/A	N/A		
	Terrace level					
	> Discharge of pump	450 lpm	Provided	MI		
	Head of the pump	40 m	Provided	MI		
	> Power supply	Required	Provided	MI		
	> Auto starting of pump	Required	Provided	M		
		The state of the s	Tortaga			
14.	 Under ground tank 	N/A	N/A	N/A		
	capacity Draw off connection	N/A	N/A	N//		
	12 Marie 24 June 4 200 Marie	N/A	N/A	N//		
	and the same and t	- N/A	N/A	N//		
		5,000 ltrs.	5,000 ltrs.	MI		
10.00	Overhead Tank capacity	Required	Provided	MI		
15	27.10	required	Tortaca	IVII		
16.		NUA	NI/A	N. V.		
	> Pressurization of Lift Shaft	N/A	N/A	N/A		
	 Pressurization of lift lobby 	N/A	N/A	N/.		
	 Communication in lift Car 	N/A	N/A	N/		
	 Fireman's Grounding Switch 	Required	Provided	М		
	Lift Signage	Required	Provided	M		
17	The state of the s	Required	Provided (DG set)	M		
1747.911						
18	Total area	N/A	N/A	N		

10/44 Fire control room Detector system panel N/A N/A N/A N/A Flow Switch Panel N/A N/A N/A PA System Panel N/A N/A N/A Battery backup N/A N/A N/A Building Floor Plans N/A N/Λ N/A Special Fire Protection Systems N/A N/A 20. for Protection of special Risks, if The fire protection systems provided in the building were checked and found functional at the time of inspection. The shortcomings issued vide letter no. F6/DFS/MS/GH/2023/SZ/564 dated 15/11/2023 found rectified. Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no. F6/DFS/MS/GH/2020/SZ/136 dated 11/09/2020, renewal under rule 37 of the Delhi Fire Service Rule 2010, is recommended. Accordingly, DFA is put up for approval & signature please. ADO (JWP) F.T. letter is mosup for your signature pli PIII or 125 m owp)

D