GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/NDZ/2025/36

Dated: 20 01 2025

FIRE SAFETY CERTIFICATE

Certified that The Spot Guest House located at 867-868, Gali Chandiwali Main Bazar, Paharganj, New Delhi- 110055, in a building Comprised of Basement + Ground + 04 upper Floors. Basement (storage), ground floor (reception + lobby + store + 03 guest room), 1st Floor to 3rd Floor (07 guest rooms at each floor), 4th floor - sealed by MCD, total 24 guest rooms owned/occupied by the Spot Guest House, was issued FSC vide letter no. F6/DFS/MS/GH/NDZ/2021/500 dated 12/11/2024. owner has given an undertaking dated 24/01/2020 that no floor above third floor will be used for any purpose. The building/premises was re-inspected by the officer concerned of this department on 06/01/2025 in the presence of Mr. Himanshu Katyal and observed that all the Fire Prevention Fire safety arrangements provided in the premises/ building found in good working condition. The premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" Sub Division A-1 ground Floor (03 guest rooms) 1st Floor (07 guest rooms), 2nd Floor (07guest rooms), 3rd floor (07 guest rooms), (Total 24 guest rooms only), validity upto 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010. Conditions Printed Overleaf.

Issued on 20 01 2025 at New Delhi by.

(Atul Garg) Director

Copy to:-

- The Commissioner, MCD, Civic Centre, New Delhi. to insure the occupancy as detailed above.
- 2. The Joint C.P. (Lic.), Police Station, Defence Colony, ^{1st} floor, New Delhi. Email Id:-(addlcp.lic-dl@nic.in) ID:-2024122118247.
- 3. The owner/occupier The Spot Guest House located at 867868, Gali Chandiwali Main Bazar, Paharganj, New Delhi- 110055.

| - | | | - M | 31 | | | | |
|------|----------|--|---|-----------------------------|-------------------|--|--|--|
| | | n | NSPECTION REP | ORT | | | | |
| • | Name | & address of the building | The Spot Guest House Locate at 867-868, Gali Chandiwa Main Bazar, Paharganj, New Delhi- 110055. | | | | | |
| | Туре | of Occupancy | Residential (Guest House) | | | | | |
| | | of Case | | | | | | |
| | | | Renewal | | | | | |
| | Detai | ls of previous NOC | F6/DFS/MS/GH/ NDZ/2021/500 dated 12/11/2021. | | | | | |
| | Fire S | afety directives letter No | Nil | | | | | |
| | | of inspection | 08/01/2025 | | | | | |
| | | of the Inspecting Officers | Sarabjeet Singh ADO (MN) | | | | | |
| | Name | and designation of officers the building side | Mr. Himanshu Katyal | | | | | |
| | Year | of Construction | 2002(As per MHA Portal) | | | | | |
| 0. | Appl | cant's letter No | Online Application | n No.2024122118247 date | ed-21/12/2024 | | | |
| loor | ound+(| uest rooms) reception at g 3 Upper Floors. nimum Standards on fire F | or (03 guest rooms)1 st floor (07 rooms) & 2 nd fround floor, in a building comprised of B equired as per Provided at site | | Remarks MR/NMR | | | |
| 10. | prev | ention and fire safety U/R 33 | Rule 35(6) of DFS Rule 2010 | | 95.75 (25) 3 | | | |
| | Acce | ss to building | | | | | | |
| | | Road width | NA | 2.5 mtr | NA | | | |
| | | Gate width | NA | NA | NA | | | |
| | | Width of internal road | NA | NA | NA | | | |
| 2 | Num | ber, Width, Type & Arrange | ement of Exits | | | | | |
| -/- | a. Ni | mber of staircases | (A) | | | | | |
| | | Upper Floors | 01 | 01 Provided | MR(old case | | | |
| | | Basements | 01 | 01 Provided | MR(old case | | | |
| | b. W | dth of staircases | 0.00 | 1 10 mtm (| MR(old case | | | |
| | | Upper Floors | 0.80 mtr | 1.18 mtr | MR(old case | | | |
| | | Basements | 0.80 mtr | 1.10 mtr | WIN(Old case | | | |
| | c. Pr | otection of exits | Required | Provided | MR | | | |
| | | Fire check door | NA | NA | NA | | | |
| | | Pressurization of continuous staircases to terra | 17 | NA | NA | | | |
| | 23.5 1-1 | idth of Corridor | NA | NA | NA | | | |
| | | or Size | 01 mtr | 01 mtr | MR | | | |
| 2 | 1100000 | partmentation. | | | | | | |
| 3 | Com | Fire check door | Required | Provided | MR | | | |
| | | Sealing of electrical shafts | NA | Sealed | NA | | | |
| | | Fire Rating of shaft door | NA | NA | NA | | | |
| | | Water Curtain | NA | NA | NA . | | | |
| | | Fire Dampers | NA | NA In and | NA | | | |
| 4 | Smo | oke Management System. | | | | | | |
| | 2.1.0 | Basements | Required | Exhaust fans | MR | | | |
| | | Upper floors | Required | Natural Ventilation | MR | | | |
| £ | Fire | Extinguishers | المستوط | | 110.1 | | | |
|) | | Total numbers | 12 nos. | 12 Provided / | MR | | | |
| 3 | | The state of the s | E 22 55 | | | | | |
| 5 | | Types | CO ₂ , ABC type | ABC & CO ₂ Types | MR | | | |

Provided

Provided Provided MR

MR

MR

01

30m

5mm

First-Aid Hose Reels.

Total numbers on each floor

Length of hose reel hose

Nozzle diameter

| 7 | Automoti- 6 1 1 1 1 1 1 | P 32 | | | | |
|----|--|--------------|---------------|----------|--|--|
| - | Automatic fire detection and alarmi | CO% & Smoke | Provided | | | |
| | Type of detectors | Ground Floor | Provided | | | |
| | Location of Main Panel | NA | NA | | | |
| | Location of Repeater Panel | Required | Provided | | | |
| | Alternate source of power | Ground Floor | Provided | | | |
| | Hooters' Location | NA NA | NA | + | | |
| 8 | MOEFA | Required | Provided | | | |
| 9 | Public Address System. | | | | | |
| 10 | Automatic Sprinkler System. NA NA NA | | | | | |
| | Basement | NA NA | NA | | | |
| | Upper Floor | NA NA | NA | | | |
| | Sprinkler above false ceiling | IVA | • • • • | 4 | | |
| 11 | Internal Hydrants | T NA | NA | | | |
| | Size of riser/down-comer | NA NA | NA NA | + | | |
| | Number of hydrants per floor | NA NA | NA NA | | | |
| | Hose Box | NA | NA | | | |
| 12 | Yard Hydrants. | | | | | |
| | Total number of hydrants | NA | NA | | | |
| | Hose Box | NA | NA | | | |
| 13 | Pumping Arrangements. | | | | | |
| | Ground Level | 7. | | | | |
| | Discharge of main Pump | NA | NA |]] | | |
| | ➤ Head of Main pump | NA | NA | 1 | | |
| ь. | ➤ Number of main pumps | NA | NA | 1 | | |
| | Jockey Pump out put | NA | NA | 1 | | |
| | Jockey pump head | NA | NA | 1 | | |
| | ➤ Standby Pump out put | NA | NA | ı | | |
| | Standby Pump Head | NA | NA | N | | |
| | > Auto Starting/ Manual stopping | · NA | NA | N | | |
| | > Pump House Access | NA | NA | N | | |
| | Terrace level | | | | | |
| | Discharge of pump | 180 lpm | Provided | M | | |
| | > Head of the pump | 30 mtr | Provided . | M | | |
| | > Power Supply | Required | Provided | M | | |
| | ➤ Auto Starting of pump | Required | Provided | M | | |
| 14 | Captive Water Storage for fire fightin | | 1 | | | |
| | Underground tank capacity | NA | NA | N. | | |
| | > Draw-off connection | NA | NA NA | N. | | |
| | > Fire service inlet | NA | NA NA | | | |
| | > Access to tank | NA | NA 2,500 ltrs | N/ MI | | |
| | Overhead Tank capacity | 2,500 ltrs | Provided / | MI | | |
| 15 | Exit Signage. Required | | | | | |
| 16 | | | | | | |
| | Pressurization of Lift Shaft | NA | NA | NA | | |
| | Pressurization of Lift lobby | NA | NA | NA | | |
| | Communication In lift Car | NA | NA NA | NA NA | | |
| | Fireman's Grounding Switch | NA | NA NA | NA NA | | |
| - | Lift Signage | NA | NA NA | MR | | |
| 17 | Standby power supply | Required | Provided | IVIK | | |

×

M

| | | m/ | 33 | | | | |
|---------|--|----|----|----|--|--|--|
| Defu | ge Area. | | | | | | |
| 8 Ko. | Total Area | NA | NA | NA | | | |
| | Location | NA | NA | NA | | | |
| 19 Fire | Fire Control Room | | | | | | |
| 13 | Detector System Panel | NA | NA | NA | | | |
| | Flow Switch Panel | NA | NA | NA | | | |
| İ | PA System Panel | NA | NA | NA | | | |
| | Battery backup | NA | NA | NA | | | |
| | Building Floor Plans | NA | NA | NA | | | |
| | ial Fire Protection Systems for ection of special Risks, if any: | NA | NA | NA | | | |

NOTE: - 4th Floor is sealed by MCD & The Owner/Occupier has given Undertaking/affidavit Which is placed at C/49, that 4rd floor is not in used for any purpose, if it is used in Future FSC shall be null & void automatically.

The fire protection systems provided in the building were checked and found functional at the time of inspection. Earlier all the shortcoming issued by this department have been compiled by the guest house management/owener/occupier.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the NOC vide letter no F6/DFS/MS/GH/ NDZ/2021/500 dated 12/11/2021 renewal under the rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer
Sarabjeet Singh ADO (MN)

14 of 2025

Director My

SIN

your Rinel

Soft

pm

Uplandes D