GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110001

No. F6/DFS/MS/School/2025/SZ/ 483

Dated: 15/04/2025

FIRE SAFETY CERTIFICATE

Certified that the Tirupati Public School at 127A, Vikar Vihar, Opp. Sahib Singh Verma Stadium, Main Kakrola Road, Sector-15, Dwarka, New Delhi- 110078, comprised of ground plus one upper floor only, owned/occupied by Tirupati Public School, was issued FSC by this department vide letter No. F.6/DFS/MS/school/2022/SZ/433 dated 21.04.2022. The school building was re-inspected by the officer concerned of this department on dated 07.04.2025 in the presence of Smt. Suman (Headmistress), and found that the school management have deemed complied with the fire prevention and fire safety requirements in accordance with the Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 issued by the Director of Education and that the building/ premises (ground and first floor only) is fit for occupancy class "Educational Building" w.e.f. 15 04 2025 for a period of three years, subject to compliance of the conditions printed as under.

Issued on 15 04 2025 at New Delhi by.

Delhi Fire Service

Copy to: -

1. Director of Education, GNCT of NCT of Delhi, Old Secretariat, New Delhi- 110054.

2. The Principal, Tirupati Public School at 127A, Vikar Vihar, Opp. Salab Singh Verma Stadium, Main Kakrola Road, Sector-15, Dwarka, New Delhi- 110078.

Conditions for the validity of fire safety certificate: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the schedule of Delhi Service Rules Fire 2010, form is www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

Tirupati Public School at 127A, Vikar Vihar, Opp. Sahib Singh Verma Stadium,

Main Kakrola Road, Sector-15, Dwarka, New Delhi- 110078.

2. Building is comprised of

Groundplus one upper Floor

3. Type of Occupancy

Educational

4. Type of Case

Renewal

5. Details of Previous NOC

F.6/DFS/MS/school/2022/SZ/433 dated 21.04.2022

6. Fire Safety direction letter No

: N/A

7. Date of Inspection

07.04.2025

8. Name of the Inspecting Officers:

ADO R.K. YADAV

9. Name of the designation of Officer

from the building side

Smt. Suman (Headmistress)

10. Year of Construction

Before 2009

11. Applicant's letter No

Nil, dated 24.03.2025

Sr. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement	Provided at Site	Remarks MR/NMR		
Ĺ	Access to building					
	Road width	Required	12 m	MR		
	Gate width	N.A.	N.A.	N.A.		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases					
	Upper Floor	Old case	02 no.	MR		
	Basement	N.A.	N.A.	N.A.		
	B. Width of Staircases	1				
	Upper Floor	Old case	1.50 & 1.15 m	MR		
	Basement	N.A.	N.A.	N.A.		
	c. Protection of exits					
	Fire check door	N.A.	N.A.	N.A.		
	Pressurization	N.A.	N.A.	N.A.		
	e. No. of continuous staircases to terrace	01 no.	01 no.	MR		
	g. Width of Corridor	1.50 m	1.50 m	MR		
	h. Door Size	1 m	1 m	MR		
3	Compartmentation.					
7-17-	Fire check door	N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	N.A.	N.A.	N.A.		
	Upper floor	Required	Natural Ventilation	MR		

$\mathbf{I} \setminus \mathcal{I}$	П	

		O7 Noc	MR	
Cotal numbers	07 Nos.	07 Nos.	MR	
ypes			MR	
S marking	ISI marked	151 marked	1.21	
First-aid-Hose Reels.				
Total numbers of each floor	N.A.	N.A.	N.A.	
The Property of the Control of the C	N.A.	N.A.	N.A.	
Nozzle diameter	N.A.	N.A.	N.A.	
A description and alarming sys	tem.			
		N.A.	N.A.	
• •		N.A.	N.A.	
		N.A.	N.A.	
		N.A.	N.A.	
-		- AR SOM STORY	N.A.	
			N.A.	
MOEFA			MR	
Public address System.	N.A.	Provided	IVIK	
Automatic Sprinkler System.			27.4	
basement	N.A.		N.A.	
upper floor	N.A.	N.A.	N.A.	
sprinkler above false ceiling	N.A.	N.A.	N.A.	
Internal Hydrants				
	N.A.	N.A.	N.A.	
		N.A.	N.A.	
1	N.A.	N.A.	N.A.	
HOSE BOX				
	NΔ	N.A.	N.A.	
1		- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	N.A.	
	4 7,14 6.	An one selfer		
		NT A	N.A.	
Ground Level		16-1-15-	N.A.	
Discharge of main Pump			N.A.	
Head of Main Pump				
			N.A.	
	N.A.	N.A.	IV.A.	
		N A	N.A.	
			N.A.	
			N.A.	
			N.A.	
Auto Starting of pump	N.A.	14,73.		
Continue Water Stanger for Fire Fight	ling.			
	- 10	N.A.	N.A	
The second of th	I. I		N.A	
			N.A	
Fire service inlet Access to tank	N.A.	N.A.	N.A	
	IN A	A 114 B1	1	
Overhead Tank capacity	N.A.	N.A.	N.A	
	First-aid-Hose Reels. Fotal numbers of each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sys Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. • Ground Level • Discharge of main Pump • Head of Main Pump • Number of main pumps • Jockey pump out put • Jockey pump out put • Standby pump out put • Standby pump out put • Standby pump Head • Standby pump Head • Auto Starting /Manual stopping • Pump House Access • Terrace Level • Discharge of pump • Head of the Pump • Power supply • Auto Starting of pump	Smarking CO2 & ABC Smarking Sist marked Sistal-Add-Bose Reels. Fotal numbers of each floor N.A. Length of hose reel hose N.A. N.A. Automatic fire detection and alarming system. Type of detectors N.A. Location of main panel N.A. Location of repeater panel N.A. Hooters N.A. Hooters N.A. Automatic Sprinkler System. N.A. Automatic Sprinkler System. N.A. Automatic Sprinkler System. N.A. Internal Hydrants N.A. For interpolation N.A. Internal Hydrants N.A. Internal	CO	

1	Provision of Lifts.				
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.	
1	Pressurization of Lift lobby Communication in lift car	N.A.	N.A.	N.A.	
	Firemen's grounding switch	N.A.	N.A.	N.A.	
	Lift Signage	N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
	Standby power supply	N.A.	N.A.	N.A.	
8	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel	N.A.	,N.A.	N.A.	
	Batter backup	N.A.	N.A.	N.A.	
	Building Floor Plans	N.A.	N.A.	N.A.	
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter number F.6/DFS/MS/school/2022/SZ/433 dated 21.04.2022, renewal in accordance with the Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011, issued by the Director of Education is recommended.

Signature of Inspecting Officer

Name: - R.K. Yadav

Designation: - ADO (JKP)

<u>w</u>

Ció

11 141

Sinector

 \sim