GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/GH/2025/SZI 54

Dated: 28 01 2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Venus Dx. Guest House at 3423, Hari Mandir, Pahar Ganj, New Delhi, comprised of ground floor (reception & 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor) (total 14 guest rooms only) 4th floor (not in use), was issued FSC by this department vide letter No. F.6/DFS/MS/GH/2022/38 dated 19.01.2022. The premises was re-inspected by the officer concerned of this department on dated 14.01.2025 in the presence of Manager and found that the guest house have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class "Residential" (Guest house) (14 guest rooms only upto 3rd floor only) w.e.f 28 of 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 28 01 2025 at New Delhi.

Delhi Eire Service

Copy to: -

The Commissioner, MCD, Delhi: to ensure the occupancy as detailed above and deviation, if any.

Online application Id 2024123118559 dated 01.01.2025.

Conditions for the validity of fire safety certificate: -

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.

3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

4. The trained staff should be available round the clock.

5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning

6. The certificate may not be treated in any case for the regularization of the unauthorized

7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

: Venus DX. Guest House at 3423, Hari Mandir,

2. Building is comprised of

Pahar Ganj, New Delhi. : G+4 upper floors (total 14 guest rooms), Ground (Reception & 02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor)

4th floor (02 rooms & 01 store not in uses)

3. Type of Occupancy

: Residential (Guest House)

4. Type of Case

: Renewal

5. Details of Previous FSC letter

: F.6/DFS/MS/GH/2022/38 dated 19.01.2022

Fire Safety direction letter No

: N/A

7. Date of Inspection

: 14.01.2025

8. Name of the Inspecting officers

: ADO R.K. Yadav (JKP)

9. Name and designation of officer from the building side

IS marking

: Manager

10. Year of construction 11 Applicant's letter No

1991 : ID No. 2024123118559 dated 01.01.2025

Remarks Provided at Site Sr. Minimum Standards on Fire Requirement MR/NMR No. Prevention and Fire Safety U/R33 1 Access to Building. N/A 06 m N/A Road width N/A N/A N/A Gate width N/A N/A N/A Width of internal road Number, Width, Type and Arrangement of Exits. a. Number of Staircases MR 01 Nos. 01 Nos. Upper floor N/A N/A N/A Basement B. Width of Staircases MR 1.18 to 1.21 m .80 m Upper floor N/A N/A N/A Basement c. Protection of Exits N/A N/A N/A Fire check door N/A N/A N/A Pressurization MR 01 d. No. of Continuous Staircases to 01 Terrace N/A N/A N/A e. Width of Corridor MR 1.0 m 1.0 m f. Door Size Compartmentation. 3 N/A N/A N/A Fire check door N/A N/A N/A Sealing of electrical shafts N/A N/A N/A Fire rating of shaft door N/A N/A N/A Water curtain N/A N/A N/A Fire dampers Smoke Management System. 4 N/A N/A N/A Basement Provided 12 ACPH MR Upper floor Fire Extinguishers. 5. 12 nos. Provided MR Total numbers ABC/CO₂ MR Provided Types ISI marked MR Provided

06	First-Aid-Hose Reels.					
	Total numbers on each floor	01 No	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	05 mm	Provided	MF		
07	Automatic Fire Detection, CO detection and Alarming System.					
	CO Type of detectors	Required	Provided	MR		
	Location of main panel	Ground floor	Provided	MR		
	Location of repeater panel	N/A	N/A	N/A		
	 Alternate source of power Hooter's location 	Required	Provided	MR		
		Ground floor	Provided	MR		
08	MOEFA	Required	Provided	MR		
09	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement & Stilt	N/A	N/A	N/A		
	 upper floor 	N/A	N/A N/A	N/A N/A		
	 sprinkler above false ceiling 	N/A	N/A N/A			
11	Internal Hydrants	IV.A	N/A	N/A		
	HI WITH THE PARTY OF THE PARTY					
	size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose box	N/A	N/A	N/A		
12	Yard Hydrants.			2222.00.2		
¥	Total number of hydrants	N/A	NI/A			
	Hose box	N/A	N/A N/A	N/A		
3	Pumping Arrangements.	104 10	IN/A	N/A		
	> Ground Level		V . I V XI III X			
-	The second secon	Part of the last o	Land Control of the C			
	Discharge of main pump					
	Head of main pump Number of main pump	N/A	N/A	N/A		
- 1	Number of main pumps lockey pump out of the lockey pump out	N/A	N/A	N/A N/A		
- 1	Jockey pump out put	N/A	N/A			
	Jockey pump head Standbare	N/A	N/A	N/A		
	Standby pump out put	N/A	N/A	N/A		
	Standby pump head	N/A	N/A	N/A		
- 1	Auto starting /manual	N/A	N/A	N/A		
	stopping	N/A	N/A	N/A		
-	 Pump house access Terrace Level 		.ua	N/A		
	Discharge of pump	225 LPM	225 LPM	100		
	Head of the pump	40 M	Provided	MR		
	• Power supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR MR		
C	aptive Water Storage for Fire Fight	ing.	1	IVIK		
	Underground tank capacity		1 - A			
	Draw-off connection	N/A	N/A	N/A		
	• Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
		N/A	N/A			
	 Overhead Tank capacity 	2500 ltrs .	2500 ltrs	N/A		
E.	xit Signage.	Required	Provided	MR		
E						

1	Provision of Lifts.		21/4	1 277			
1	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	• Communication in me can	h N/A	N/A	N/A			
	 Firemen's grounding switch Lift Signage Standby power supply	N/A	N/A	N/A			
		Required	Provided	MR			
-5	Refuge Area.						
	Relago		N/A	N/A			
_	Total area	N/A	N/A	N/A			
	• Location	N/A	IN/A				
	Fire Control Room						
Ý.	D	N/A	N/A	N/A			
	Detector system panel	N/A	N/A	N/A			
	Flow switch panel	N/A	N/A	N/A			
	PA system panel	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
	Puilding Floor Plans			MR			
	Building Floor Plans Special Fire Protection systems for	r Required	Provided	IVIIC			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: - As per affidavit submitted by guest house management (placed at C-105) the building is comprised of ground plus four upper floors. 4th floor of the building is not in use and guest house running at ground to 3rd floor only (total 14 guest rooms only).

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/GH/2022/38 dated 19.01.2022, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of happecting Officer 2015

Name: - R.K. Yadav Designation: - ADO (JKP)

DOJED

21/1/25

Lycro (102)

LIV 31/01/25

CFO Must

Director

portu