GOVERNMENT OF NATIONAL CAPITALTERRITORYOF DELHI HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI – 110001

No. F6/DFS/MS/2025/EH 1.5

Dated:-. 08/01/2025

FIRE SAFETY CERTIFICATE

Certified that the M/S VVSSIGNATURE SERVICES PRIVATE LIMITED at Shop no.2, Lajpat Nagar Metro Station, South East, Delhi comprised of ground and first floor, was inspected by the officer concerned of this department on 31-12-2024 in the presence of Sh. Sunil Joshi, Manager and found that the said restaurant in the Metro Station premises has complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said restaurant premises is fit for occupancy class Assembly Building with effect from 08. 2025 up to three year in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 08. 01. 2025... at New Delhi by.

Copy to:-

- 1. The Addl. Commissioner of Police, First floor, Defence colony, Police Station New Delhi ID no. 2024121117904 dated 11.12.24.
- The GM/E & M/RC, Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi.
- 3. The Manager VVSSIGNATURE SERVICES PRIVATE LIMITED at Shop no.2, Lajpat Nagar Metro Station, South East, Delhi.

Conditions for the validity of Fire Safety Certificate

- This FSC is valid only for restaurant at ground and first floor only.
- All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- The trained fire fighting staff should be available round the clock.
- 5. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 10. Any flammable material for interior decoration shall strictly be prohibited.

INSPECTION REPORT

1. Name & address of the building : VVSSIGNATURE SERVICES PRIVATE

LIMITED at Shop no.2, Lajpat Nagar Metro

Station, South East, Delhi.

2. Type of Occupancy : Assembly building

Restaurant at ground and first floor

3. Type of Case : fresh 4. Details of previous FSC : N/A

5. Fire Safety directives Letter No. : F6/DFS/MS/BP/2024/417 dated 20.12.2024 &

No. 1832 dated 19.07.2021

Date of inspection : 30/12/2024

 Name of the Inspecting Officer
 Name and designation of Officer : Sh. Ravinder Singh ADO/CC

8. N	ame and designation of Officer				
fro	om the building side	: Sunil Joshi, M	fanager		
9. Y	ear of Construction	: 2005			
10. Ap	oplicant's letter No.	: Online id no. 2	2024121117904 da	ted 11.12.24.	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirements as per NBC part - 4/UBBL	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	06 mtr	06 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	02 Nos.	02 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	1.50 mtr.	1.80 m	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits	N/A	N/A	N/A	
	1. Fire check door				
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	2x 1.50 mtr.	2x2 m & 1x1mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	

	F. Door size	2x 1.50 mtr.	2x2 m & 1x1mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	· N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers			1711	

1) Total numbers 04 Nos. 04 Nos. MR 2) Types ABC & CO2 ABC & CO2 MR 3) ISI marking Required Provided MR First-Aid Hose Reel 1) Total number of each floor 01 Provided

MR

2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
3) Nozzle diameter	05 mm	05 mm	MR	
Automatic Fire Detection &	Alarming System	n		
1) Type of detectors	N/A	Provided	N/A	
2) Location of main panel	N/A	110	N/A	
3) Location of repeater panel	N/A	EVISOUS .	N/A	
4) Alternate source of power	N/A		N/A	
5) Hooter's Location	N/A	ground floor	N/A	
	Required	Provided	MR	
		N/A	N/A	
Automatic Sprinkler System				
	N/A	N/A	N/A	
		Provided	MR	
2) Opper Hoors 2) Sprinkler above false		N/A	N/A	
	1472	W		
	100 mm	Provided	MR	
			MR	
	01	11011404		
	01	01	MR	
	101	O1	1111	
	N/A	02 nos	N/A	
		N. S. SEND SHOWNERS	N/A	
	* ***			
/			MR	
	2830 LPM	Flovided	IVIK	
	99 m for hydran	t Provided	MR	
b) Head of main pump	A CONTRACTOR OF THE PARTY OF TH	riovided	MIK	
a) Number of main		Provided	MR	
The second secon	2 1105.	Tiovided	THE STATE OF THE S	
	2v 180 I PM	Provided	MR	
			MR	
e) Jockey pump nead		Tiovided	IVAL	
f) Stand by numn		Provided	MR	
	2A 2030 LF WI	Tiovided		
	88 m for hydrant	Provided	MR	
g) Stand by pump nead		Tiovided	, mic	
	10.00 //personal deposition of			
h) Auto		Provided	MR	
	required	Trovided		
		+		
	N/A	N/A	N/A	
			N/A	
			N/A	
			N/A	
	IV/A	N/A	INA	
niimn				
pump				
	3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System	3) Nozzle diameter Automatic Fire Detection & Alarming System 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box 01 Yard Hydrants 1) Total number of hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Head of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump output g) Stand by pump head stopping 2) Terrace level a) Discharge of pump b) Head of pump C) Power supply N/A N/A Required N/A N/A 100 mm 100 m	3) Nozzle diameter 05 mm 05 mm Automatic Fire Detection & Alarming System 1) Type of detectors N/A ground floor 2) Location of main panel N/A N/A Provided 4) Alternate source of power N/A ground floor 3) Location of repeater panel N/A Provided 4) Alternate source of power N/A ground floor 5) Hooter's Location N/A ground floor MOEFA Required Provided Public Address System N/A N/A Automatic Sprinkler System 1) Basement N/A N/A 2) Upper floors Required Provided 3) Sprinkler above false ceiling N/A N/A Internal Hydrants 1) Size of riser/down-comer 100 mm Provided 2) Number of hydrants per floor 3) Hose box 01 01 Yard Hydrants 1) Total number of hydrants N/A N/A N/A Pumping Arrangement Provided and maintained by m Provided a) Discharge of main pump b) Head of main pump 88 m for hydrant Provided c) Number of main pump b) Head of main pump 88 m for hydrant Provided c) Number of main pump d) Jockey pump out put 2x 180 LPM Provided e) Jockey pump head 88 m for hydrant Provided floor f) Stand by pump out put 2x 2850 LPM Provided g) Stand by pump head 88 m for hydrant Provided for sprinkler f) Stand by pump out put 2x 2850 LPM Provided g) Stand by pump head 88 m for hydrant Provided A 75 m for sprinkler f) Stand by pump head 88 m for hydrant Provided Starting/Manual stopping 2) Terrace level a) Discharge of pump N/A N/A N/A b) Head of pump N/A N/A c) Power supply N/A N/A	

		NI	8	
	Under ground tank appoint	2,00,000liter	Provided	MR
	a) Draw-off connection	Required	Provided	MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	N/A	N/A	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst Risk, if any:	em for Protecti	on of special	NA

The fire protection systems provided for the said restaurant in the metro station were randomly tested, checked and found functional at the time of inspection. Further, FSC to metro station has already issued vide letter no. F6/DFS/MS/metro/SZ/2024/508 dated 08.08.2024.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may issue the FSC to said premises as required under Rules 2010. Accordingly reply letter is prepared and put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: -Ravinder Sing

Designation: - ADO (CC)