

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/EH/SZ/2025/ 106

Dated: 24 03

FIRE SAFETY CERTIFICATE

Certified that the M/s WOS LAIDBACK CAFÉ (A Unit World of Shalom Restaurant Pvt. Ltd) located at 2nd floor (Rest. 1 & 2), Plot No 9, Sangam Cinema Building. Sector 9, R.K. Puram New Delhi 110022 in the building comprised of 03 tier Basement + Ground + 03 upper floors & was granted Fire Safety Certificate by this department vide letter no. F6/DFS/MS/EH/2022/SZ/181 dated 17.06.2022. The building was re-inspected by officer concerned from this department on 19.03.2025 in the presence of Mr. Rohit Gopal Sharma (Manager) and found that the Restaurant has complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. Accordingly, the said Restaurant is fit for occupancy of Group D "Assembly Building" (Restaurant) and valid upto 31.03.2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire service Rules, 2010 printed below.

Issued on 34,03,8025 at New Delhi by

Della Fire Service

Reference: etl.mcdonline application no. 2025030703017.

Conditions for the validity of Fire Safety Certificate

- 1. This Fire Safety Certificate is valid for restaurant at 2nd floor (Rest. 1 & 2 only).
- 2. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 3. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- 4. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 5. The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 10. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

INSPECTION REPORT

1.	Name and address of the building:		M/s WOS L	AIDBACK CAFÉ (A	Unit World			
			Shalom Restaurant Pvt. Ltd) located at 2 nd flo (Rest. 1 & 2), Plot No 9, Sangam Cinema Buildin Sector 9, R.K. Puram New Delhi 110022 (FSC issu					
			9					
				mplex in the name of N				
				omplex located at Plo				
			Cinema Building. Sector 9, R.K. Puram New Del 110022).					
2.	Time							
3.	Type of occupancy			Group D, "Assembly" (Restaurant)				
ა.	Building comprised of		03 tier Basement + Ground + 03 upper floors.					
			(Restaurant running at 2 nd floor Rest. 1 & 2 of the					
			building)					
4.		of case:	Renewal					
5.	Detai	ils of previous FSC		1/2022/SZ/181 dated 17	Contraction of the Contraction o			
6.	Fire s	safety directives no.	F6/DFS/MS/BP	/2010/1304 dated 04.05	5.2010			
7.	Date	of inspection:	19.03.2025					
8.	Name	e of the inspecting officer:	Rajesh Kumar S	hukla, ADO (M. Road)			
9.		e and designation of the officer	Mr. Rohit Gopal Sharma (Manager)					
	from the building side:		Control Contro					
10		of construction:	2014					
11		rence letter no.:		plication no. 20250307	703017			
	1112.0000	SPANNES DE MESSIGNES DE PRESE DA REMAIN		150				
S. N	No Minimum standard of Fire		Requirements	Provide at site	Remarks MR/NMI			
	636	evention and Fire Safety U/R			MINIMI			
	33		(6)					
1	_	cess to Building:	- Contraction	Ta	1 MD			
	A	Road width	6.0 mtrs	Provided	MR			
. 1	В	Gate width	NA	NA	NA			
	C	Width of internal roads	NA	NA	NA			
2	Number, Width, Type & Arrangement of Exits:							
	A	No. of Staircase:		The second				
		a) Upper floor	02 nos.	02 nos.	MR			
		b) Basements	NA	NA	NA			
	В	Width of the Staircase:						
		a) Upper floors	2.0 m each	Provided	MR			
		b) Basement	NA	NA	NA			
	C	Protection of Exits						
		a) fire check door	Required	Provided	MR			
	D	b) pressurization	NA	NA	NA			
		No. of continuous staircase	1 no.	Provided	MR			
		to terrace	1 110.	Tiovided				
	177	Width of the corridor	NA	NA	NA			
	E	TANKS OF THE PARTY	200000		MR			
	F	Door Size	2.0 m & 1.50 m	2.10 m & 1.85 m	IVIK			
3		npartmentation:	I .	T n 3 1	MD			
	A	Fire check doors	Required	Provided	MR			
	В	Sealing of horizontal &	Required	Provided	MR			
		vertical opening	<u>.</u>		100			
	C	Fire rating of shaft doors	Required	Provided	MR			
	D	Water curtain	NA	NA	NA			
	E	Fire dampers	NA	NA	NA			
4	Sm	oke Management System:						
4	A	Basements	NA	NA	NA			
4		Restaurant area	Required	Provided	MR			
4	В							
5	В	Extinguishers:						
	B Fire	Extinguishers:	06 nos	06 nos	MR			
	B Fire	Total numbers	06 nos.	06 nos.	3000			
	B Fire	27	06 nos. ABC ISI marked	06 nos. ABC ISI marked	MR MR MR			

			1 no.	building managen Provided near	MR			
	A	Total no. at each floor	1 110.	exits	= 1			
	В	Length of hose reel	30 m	30 m	MR			
	C	Nozzle diameter	5 mm	5 mm	MR			
7	Automatic Fire Detection and Alarm System (ADAS): (Provided & maintained by							
			b	uilding managemen Smoke/heat	NA			
	A	Type of detectors	NA NA	Provided	NA NA			
		Location of main panel	NA NA	NA	NA NA			
	_	Location of repeater panel Alternate power source	NA NA	NA	NA NA			
	D E	Hooter's location	NA	Provided	NA NA			
8		DEFA:	Required	Provided	MR			
9		blic Address System:	Required	Provided	MR			
10	Automatic Sprinkler System: (Provided & maintained by building management)							
	A	Basement	NA	NA	NA			
	В	Ground floor	Required	Provided	MR			
	C	Sprinklers above false ceiling	NA	NA	NA			
11	_		d & maintained by					
	A	Size of down comer	100 mm	100 mm	MR			
	В	No. of hydrants per floor	01 no.	Provided	MR			
	C	Hose box	01 no.	Provided	MR			
12			d & maintained by					
	A	Total no. of hydrants	NA	Provided	NA			
13	B	Hose box mping Arrangements: (Common	NA	Provided m provided & mai	NA			
	A	Ground Level a) Discharge & head of main pump	Required	2850 LPM &	MR			
		- A. C		70 m				
		b) Number of main pump	Required	02 nos.	MR			
		c) Discharge & head of jockey pum	p Required	180 LPM & 70 m	MR			
			1	/0 m				
		d) Discharge & head of standby pur	p Required	2850 LPM &	MR			
	=	d) Discharge & head of standby pume) Auto starting/ manual stopping	Required Required	2850 LPM &	MR MR			
	В	e) Auto starting/ manual stopping Terrace Level (Commo building	Required on fire fighting system on the fighting system of the fight	2850 LPM & 70 m	MR			
	В	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump	Required on fire fighting system of the fighting system of the fighting system of the first system of the	2850 LPM & 70 m Provided stem provided & 1 Better system provided	MR maintained by m MR			
	В	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump	Required on fire fighting system anagement) 450 LPM	2850 LPM & 70 m Provided stem provided & 1 Better system provided NA	MR maintained by MR			
	В	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply	Required on fire fighting system g management) 450 LPM NA NA	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA	MR maintained by m MR NA NA			
14		e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump	Required on fire fighting system g management) 450 LPM NA NA NA	2850 LPM & 70 m Provided stem provided & 1 Better system provided NA NA NA	MR maintained by m MR NA NA			
14	C	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh	Required on fire fighting system of the fight	2850 LPM & 70 m Provided stem provided & 1 Better system provided NA NA NA NA fire tank provided g management)	MR maintained by m MR NA NA NA NA d & maintained			
14	C	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh	Required on fire fighting system g management) 450 LPM NA NA NA NA NA NA NA NA NA N	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA NA NA fire tank provided g management) 2,00,000 ltm	MR maintained by m MR NA NA NA NA d & maintained rs NA			
14	C A B	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection	Required on fire fighting system g management) 450 LPM NA NA NA NA NA NA NA NA NA N	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA NA NA fire tank provided g management) 2,00,000 lt Provided	MR maintained by m MR NA NA NA NA NA NA NA NA NA N			
14	C A B C	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet	Required on fire fighting system g management) 450 LPM NA NA NA NA NA NINA NA N	2850 LPM & 70 m Provided stem provided & 1 Better system provided NA NA NA NA fire tank provided ag management) 2,00,000 lt Provided Provided	MR maintained by m MR NA NA NA NA d & maintained rs NA			
14	C A B C E	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank	Required on fire fighting system g management) 450 LPM NA NA NA NA NA NA NA NA NA N	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA NA NA fire tank provided g management) 2,00,000 lt Provided	MR maintained by m MR NA NA NA NA NA NA NA NA NA N			
120-49	C A B C C E D	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Fight Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity	Required on fire fighting system g management) 450 LPM NA NA NA NA NA NINA NA N	2850 LPM & 70 m Provided stem provided & 1 Better system provided NA NA NA NA fire tank provided g management) 2,00,000 lt Provided Provided Provided	MR maintained by m MR NA			
15	C A B C E D E	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Fight Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity Exit Signage:	Required on fire fighting system of the fight	2850 LPM & 70 m Provided stem provided & r Better syster provided NA NA NA NA fire tank provided g management) 2,00,000 lt Provided Provided Provided Provided	MR maintained by m MR NA			
120-49	C A B C E D E	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity xit Signage: rovision of lift: (Prov	Required on fire fighting system of the fight	2850 LPM & 70 m Provided stem provided & respectively a provided NA NA NA NA fire tank provided g management) 2,00,000 ltm Provided Provided Provided 20,000 ltm Provided Provided Provided	MR maintained by m MR NA NA NA NA NA NA NA NA NA N			
15	C A B C E D E	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity xit Signage: rovision of lift: (Prov.	Required on fire fighting system of the fight	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA NA Interpretable provided provided Provided Provided Provided 20,000 ltrs Provided ed by building management provided p	MR maintained by MR MR MR NA			
15	C A B C E D D E P A A B	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity ixit Signage: rovision of lift: (Prov. Pressurization of lift shaft Pressurization of lift lobby	Required on fire fighting system on fighting system on fire fighting system on	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA NA NA Sire tank provided Provided Provided Provided Provided 20,000 ltrs Provided ed by building median NA	MR maintained by m MR NA NA NA NA NA NA NA NA NA N			
15	C A B C E D E P A	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity ixit Signage: rovision of lift: (Prov. Pressurization of lift shaft Pressurization of lift lobby	Required on fire fighting system of fire fighting syst	2850 LPM & 70 m Provided stem provided & respectively a stem provided NA NA NA NA NA fire tank provided provided Provided Provided Provided Provided 20,000 ltrs Provided by building med NA NA NA	MR maintained by m MR NA			
15	C A B C E D D E P A A B	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity xit Signage: rovision of lift: (Prov. Pressurization of lift lobby C Communication in lift car	Required on fire fighting system of fire fighting syst	2850 LPM & 70 m Provided stem provided & 1 Better syster provided NA NA NA In NA In NA In Provided Provided Provided Provided Provided Provided Provided A 1 Provided Provided Provided Provided NA NA NA NA NA NA NA NA	MR maintained by m MR NA NA NA NA NA NA NA NA NA N			
15	A B C E D A B C C D E E	e) Auto starting/ manual stopping Terrace Level (Commo building a) Discharge of terrace pump b) Head of terrace pump c) Alternate power supply d) Auto starting of pump aptive Water Storage for Fire Figh Underground tank capacity Draw off connection Fire service inlet Access to tank Overhead tank capacity ixit Signage: rovision of lift: (Provision of lift shaft Pressurization of lift lobby Communication in lift car Fireman switch	Required on fire fighting system of fire fighting syst	2850 LPM & 70 m Provided stem provided & respectively a stem provided NA NA NA NA NA fire tank provided provided Provided Provided Provided Provided 20,000 ltrs Provided by building med NA NA NA	MR maintained by MR MR MR NA			

M/s WOS LAIDBACK CAFÉ (A Unit World of Shalom Restaurant Pvt. Ltd) located at (2nd floor Rest. 1 & 2), Plot No 9, Sangam Cinema Building. Sector 9, R.K. Puram New Delhi 110022. M/s WOS LAIDBACK CAFÉ (A Unit World of Shalom Restaurant Pvt. Ltd) located at (2rd floor Rest. 1 & 2), Plot No 9, Sangam Cinema Building. Sector 9, R.K. Puram New Delhi 110022.

18	Refuge Area:					
	A	location	NA	NA	NA	
	В	Total area	NA	NA	NA	
19	Fire Control Room: (Provided & maintained by building management)					
	A	Fire detection system panel	NA	Provided	NA	
	В	Flow switch panel	NA	Provided	NA	
_	C	P a system panel	NA	Provided	NA	
	D	Battery backup	NA	Provided	NA	
	E	Building floor plan	NA	Provided	NA	
20	Special Fire Protection for special risk if any					
	A	Special Fire Protection system for Protection of Special Risk, if any:	NA	NA	NA	

LEGENDS:-Meeting Requirement (MR), Not Meeting Requirement (NMR), Not Applicable (NA), Not Provided (NP) Provide But Not Functional (PNF).

Note:- During the course of inspection it was observed that the Restaurant running at 2nd floor (Rest. 1 & 2) of the existing building of Mini Cinema Cum Commercial Complex located at Plot No 9, Sangam Cinema Building. Sector 9, R.K. Puram New Delhi 110022 which has been already issued the FSC by this department vide letter no. F.6/DFS/MS/Cinema/2023/SZ/576 dated 01.12.2023.

The fixed fire installation has been provided & maintained by the building management which is common to the entire building. The installed fire system is of higher capacity and category then required for the individual restaurant and same was found functional at the time of inspection.

If agreed to the note above & in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/EH/2022/SZ/181 dated 17.06.2022 is recommended to be renewed under Rule 37 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer
Name Rajesh Kumar Shukla
Designation ADO (M.Road)

DO (\$D) /////

20131 2025

She upload

Dollar

M. B. Cell

54/03/52 Mayor